



**Safety Data Sheet**  
prepared to UN GHS Revision 3

## 1. Identification of the Substance/Mixture and the Company/Undertaking

- 1.1 Product Identifier** 1033B1NL
- Product Name:** CARBOMASTIC 18 BT PART B **Revision Date:** 05/30/2015
- 1.2 Relevant identified uses of the substance or mixture and uses advised against** No Information **Supersedes Date:** 29/05/2015
- 1.3 Details of the supplier of the safety data sheet**
- Manufacturer:** Carboline Company  
2150 Schuetz Road  
St. Louis, MO USA 63146
- Regulatory / Technical Information:  
Contact Carboline Technical Services at  
1-800-848-4645
- Datasheet Produced by:** Schlereth, Ken - ehs@stoncor.com
- 1.4 Emergency telephone number:** CHEMTREC 1-800-424-9300 (Inside US)  
CHEMTREC +1 703 5273887 (Outside US)  
HEALTH - Pittsburgh Poison Control 1-412-681-6669

## 2. Hazard Identification

### 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2  
Flammable Liquid, category 3  
Skin Corrosion, category 1  
Skin Sensitizer, category 1

## 2.2 Label elements

### Symbol(s) of Product



### Signal Word

Danger

### Named Chemicals on Label

N-BUTANOL, CYCLOHEXANAMINE, PHENOL, METHYLSTYRENATED, AMINE POLYMER

### GHS HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Corrosion, category 1	H314-1	Causes severe skin burns and eye damage.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

### GHS PRECAUTION PHRASES

P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

## 2.3 Other hazards

Not applicable

### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## 3. Composition/Information On Ingredients

### 3.2 Mixtures

#### Hazardous Ingredients

CAS-No.	Chemical Name	%
---------	---------------	---

14807-96-6	TALC	10-25
135108-88-2	AMINE POLYMER	2.5-10
PROPRIETARY	PHENOL, METHYLSTYRENATED	2.5-10
108-38-3	META-XYLENE	2.5-10
PROPRIETARY	HYDROCARBON COMPOUND	2.5-10
67-63-0	ISOPROPANOL	2.5-10
71-36-3	N-BUTANOL	1.0-2.5
64742-95-6	AROMATIC HYDROCARBON	1.0-2.5
106-42-3	PARA-XYLENE	1.0-2.5
100-41-4	ETHYL BENZENE	1.0-2.5
95-47-6	ORTHO-XYLENE	1.0-2.5
1761-71-3	CYCLOHEXANAMINE	1.0-2.5

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
14807-96-6			0
135108-88-2	GHS05-GHS07	H302-312-314	0
PROPRIETARY	GHS06	H315-317-303-313-402-412	0
108-38-3	GHS02-GHS07	H226-312-315-332	0
PROPRIETARY	GHS09	H410	0
67-63-0	GHS02-GHS07	H225-319-336	0
71-36-3	GHS02-GHS05-GHS07	H226-302-315-318-335-336	0
64742-95-6	GHS02-GHS08-GHS09	H226-411	0
106-42-3	GHS02-GHS07-GHS08	H226-312-315-332-335-371	0
100-41-4	GHS02-GHS07	H225-332	0
95-47-6	GHS02-GHS07	H226-312-315-332	0
1761-71-3	GHS05-GHS07-GHS08-GHS09	H314-317-373-411	0

**Additional Information:** The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

### 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

## 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open

flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

## 5.2 Special hazards arising from the substance or mixture

No Information

## 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

# 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8. Ensure adequate ventilation. Evacuate personnel to safe areas. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment.

## 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

## 6.3 Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

# 7. Handling and Storage

## 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Heat, flames and sparks.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

## 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (US)

Name	%	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	OEL Note
TALC	10-25	N/E	N/E	N/E	N/E	
AMINE POLYMER	2.5-10	N/E	N/E	N/E	N/E	
PHENOL, METHYLSTYRENATED	2.5-10	N/E	N/E	N/E	N/E	
META-XYLENE	2.5-10	100 PPM	150 PPM	435 MG/M3	N/E	
HYDROCARBON COMPOUND	2.5-10	N/E	N/E	N/E	N/E	
ISOPROPANOL	2.5-10	200 PPM	400 PPM	980 MGM3	N/E	
N-BUTANOL	1.0-2.5	20 PPM	50 ppm	300.0 MG/M3	150 MGM3	
AROMATIC HYDROCARBON	1.0-2.5	N/E	N/E	N/E	N/E	
PARA-XYLENE	1.0-2.5	100 PPM	150 PPM	435 MGM3	N/E	
ETHYL BENZENE	1.0-2.5	20 PPM	N/E	435 MGM3	N/E	
ORTHO-XYLENE	1.0-2.5	100 PPM	150 PPM	435 MG/M3	N/E	
CYCLOHEXANAMINE	1.0-2.5	N/E	N/E	N/E	N/E	

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

**EYE PROTECTION:** Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves Request information on glove permeation properties from the glove supplier.

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. Lightweight protective clothing

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance:	Viscous Light Brown Liquid
Physical State	Liquid
Odor	Slight
Odor threshold	
pH	N/D
Melting point / freezing point (°C)	N/D
Boiling point/range (°C)	176 F (80 C) - 531 F (277 C)
Flash Point, (°C)	27
Evaporation rate	

**Flammability (solid, gas)**

Upper/lower flammability or explosive limits Not determined

Vapour Pressure, mmHg N/D

Vapour density

Relative density

Solubility in / Miscibility with water N/D

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Decomposition temperature (°C)

Viscosity

Explosive properties

Oxidising properties

**9.2 Other information**

VOC Content g/l: 223

Specific Gravity (g/cm<sup>3</sup>) 1.59

## 10. Stability and Reactivity

**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation does not occur.

**10.4 Conditions to avoid**

Heat, flames and sparks.

**10.5 Incompatible materials**

Strong oxidizing agents.

**10.6 Hazardous decomposition products**

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## 11. Toxicological Information

### 11.1 Information on toxicological effects

#### Acute Toxicity:

Oral LD50:	N/D
Inhalation LC50:	N/D

#### Irritation:

#### Corrosivity:

#### Sensitization:

#### Repeated dose toxicity:

#### Carcinogenicity:

#### Mutagenicity:

#### Toxicity for reproduction:

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.  
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
14807-96-6	TALC	Not Available		Not Available
135108-88-2	AMINE POLYMER	367 mg/kg, oral, rat		Not Available
PROPRIETARY	PHENOL, METHYLSTYRENATED	3600 mg/kg rat, oral		4.9 mg/L / 4h, INH rat
108-38-3	META-XYLENE	Not Available		Not Available
PROPRIETARY	HYDROCARBON COMPOUND	Not Available		Not Available
67-63-0	ISOPROPANOL	4720 mg/kg rat, oral		22500 ppm/8hrs rat, inhalation
71-36-3	N-BUTANOL	790 mg/kg rat, oral	3400 mg/kg, dermal, rabbit	8000 ppm / 4hrs rat, inhalation
64742-95-6	AROMATIC HYDROCARBON	4700 mg/kg, oral, rat		3670 ppm/8 hours, rat, inhalation
106-42-3	PARA-XYLENE	Not Available		Not Available
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr
95-47-6	ORTHO-XYLENE	Not Available		Not Available
1761-71-3	CYCLOHEXANAMINE	>2000 mg/kg oral, rat	2110 mg/kg, rat	Not Available

**Additional Information:**

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

## 12. Ecological Information

**12.1 Toxicity:**

EC50 48hr (Daphnia):

IC50 72hr (Algae):

LC50 96hr (fish):

**12.2 Persistence and degradability:****12.3 Bioaccumulative potential:****12.4 Mobility in soil:****12.5 Results of PBT and vPvB assessment:**

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**12.6 Other adverse effects:**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
14807-96-6	TALC	No information	No information	No information
135108-88-2	AMINE POLYMER	No information	No information	No information
PROPRIETARY	PHENOL, METHYLSTYRENATED	No information	No information	No information
108-38-3	META-XYLENE	No information	No information	No information
PROPRIETARY	HYDROCARBON COMPOUND	No information	No information	No information
67-63-0	ISOPROPANOL	No information	No information	No information
71-36-3	N-BUTANOL	1328 mg/l (Daphnia magna)	225 mg/l (Algae)	1376 mg/l (Fathead minnow)
64742-95-6	AROMATIC HYDROCARBON	No information	No information	No information
106-42-3	PARA-XYLENE	No information	No information	No information
100-41-4	ETHYL BENZENE	No information	No information	No information
95-47-6	ORTHO-XYLENE	No information	No information	No information
1761-71-3	CYCLOHEXANAMINE	No information	No information	No information

## 13. Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.



## 14. Transport Information

14.1	UN number	UN 1263
14.2	UN proper shipping name	Paint
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	
14.4	Packing group	III
14.5	Environmental hazards	
14.6	Special precautions for user	
	EmS-No.:	
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	

## 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

### U.S. Federal Regulations: As follows -

#### CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
META-XYLENE	108-38-3
ISOPROPANOL	67-63-0
N-BUTANOL	71-36-3
PARA-XYLENE	106-42-3
ETHYL BENZENE	100-41-4
ORTHO-XYLENE	95-47-6

#### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
----------------------	----------------

No TSCA 12(b) components exist in this product.

#### U.S. Clean Air Act:

EPA Coating Category:

EPA VOC Content Limit (g/l):

Product VOC Content (g/l)

Thinning Recommendations:

Application Recommendations:

Harmful if swallowed.

**U.S. State Regulations: As follows -****New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
----------------------	----------------

No NJ Right-To-Know components exist in this product.

**Pennsylvania Right-To-Know**

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

**California Proposition 65:**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
ETHYL BENZENE	100-41-4
CUMENE	98-82-8
BENZENE	71-43-2

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
TOLUENE	108-88-3
BENZENE	71-43-2

**International Regulations: As follows -****\* Canadian DSL:**

No Information

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**16. Other Information****Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.

H373	May cause damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Reasons for revision**

No Information

No Information