

Carbocoat® 8215 Non-Skid



Carbocoat 8215 Non-Skid is a fast dry, direct to metal, non-skid alkyd enamel for applications where worker safety is required. It incorporates a unique non-skid filler package which requires no agitation during application. |

PRODUCT DETAILS Typical non-skid enamels incorporate large, heavy aggregate (sand) fillers that must be agitated during application to prevent settling. Carbocoat 8215 Non-Skid uses an innovative filler package that does not settle during storage nor requires agitation during application to prevent settling. The unique composition of the fillers provides a superior non-skid surface; even when wet.

Carbocoat 8215 Non-Skid has very friendly application properties and is suitable for use on properly prepared steel surfaces on railcars, barges, ships, walkways, or other applications where light to moderate duty service is required.

APPLICATIONS

- MARINE
- ARCHITECTURAL
- INDUSTRIAL
- WET WALKWAYS/STEPS
- EYEWASH STATIONS
- RAMPS
- RAILCAR

FEATURES

- › Quick-dry, DTM, non-skid alkyd
- › Easy mix; non settling; Single-component
- › Constant agitation not required during installation
- › Unique aggregate package for improved non-slip properties
- › Non-sparking aggregate
- › Dry hard overnight

Carboline® 8215 Non-Skid

Quality Product Backed by Quality Service

- › Carboline Company has been solving tough corrosion and fireproofing problems since 1947
- › Industrial service centers and sales offices located around the world
- › Over 20 worldwide manufacturing locations with a global network of sales and technical support
- › Industry leading field service and technical engineering support team
- › Certified to ISO 9001

Reasons to Use Carboguard 8215 Non-Skid

PERFORMANCE FEATURE	ADVANTAGE	BENEFIT
Innovative Aggregate Package	Eliminates settling during storage	Easier to mix; less labor, longer shelf life
Aggregate package has same density as coating	Constant agitation not required during application	Less labor; easier to use
High friction properties	Better grip (non-slip) characteristics	Reduces worker tendency to slip
Low profile aggregate	Less chance to get "cut" if worker slips and falls	A safer non-skid surface for workers



Carboline Company
Global Headquarters
2150 Schuetz Road
St. Louis, MO 63146 USA
PH: +1-314-644-1000
www.carboline.com