



Safety Data Sheet

prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	1528A1NL		
Product Name:	CARBOTHANE 134 CLEAR COAT PART A	Revision Date:	05/30/2015
1.2 Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.	Supersedes Date:	29/05/2015
1.3 Details of the supplier of the safety data sheet			
Manufacturer:	Carboline Company 2150 Schuetz Road St. Louis, MO USA 63146		
	Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
Datasheet Produced by:	Schlereth, Ken - ehs@stoncor.com		
1.4 Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-681-6669		

2. Hazard Identification

2.1 Classification of the substance or mixture

Carcinogenicity, category 1A
Eye Irritation, category 2
Flammable Liquid, category 2
Reproductive Toxicity, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

TOLUENE

GHS HAZARD STATEMENTS

Other EU extensions	EUH208	Contains BIS 1,2,6-PENTAMINE, METHYL SEBACATE. May produce an allergic reaction.
Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.

GHS PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P235	Keep cool.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P308+P313	IF exposed or concerned: Get medical advice/attention
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Not applicable

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
110-43-0	METHYL N-AMYL KETONE	10-25
616-38-6	DIMETHYL CARBONATE	10-25

540-88-5	TERT-BUTYL ACETATE	2.5-10
78-93-3	METHYL ETHYL KETONE	2.5-10
TRADE		
SECRET	ALIPHATIC DIOL	2.5-10
108-88-3	TOLUENE	2.5-10
123-86-4	N-BUTYL ACETATE	1.0-2.5
123-54-6	2,4-PENTANEDIONE	0.1-1.0
64742-46-7	DEFOAMER	0.1-1.0
100-41-4	ETHYL BENZENE	0.1-1.0

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
110-43-0	GHS02-GHS07	H226-302-332	0
616-38-6	GHS02	H225	0
540-88-5	GHS02	H225	0
78-93-3	GHS02-GHS07	H225-319-336	0
TRADE			
SECRET	GHS07	H315-319	0
108-88-3	GHS02-GHS07-GHS08	H225-315-319-336-361-373	0
123-86-4	GHS02-GHS07	H226-336	0
123-54-6	GHS02-GHS07	H226-302	0
64742-46-7	GHS08	H350	0
100-41-4	GHS02-GHS07	H225-332	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

6. Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures**

For personal protection see section 8. Ensure adequate ventilation. Evacuate personnel to safe areas. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage**7.1 Precautions for safe handling**

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection**8.1 Control parameters****Ingredients with Occupational Exposure Limits (US)**

Name	%	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	OEL Note
METHYL N-AMYL KETONE	10-25	50 PPM	N/E	465 MG/M3	N/E	
DIMETHYL CARBONATE	10-25	N/E	N/E	N/E	N/E	
TERT-BUTYL ACETATE	2.5-10	200 PPM	N/E	950 MGM3	N/E	
METHYL ETHYL KETONE	2.5-10	200 PPM	300 PPM	590 MGM3	N/E	
ALIPHATIC DIOL	2.5-10	25 PPM	N/E	25 PPM	N/E	

TOLUENE	2.5-10	20 PPM	N/E	375 MGM3	N/E
N-BUTYL ACETATE	1.0-2.5	150 PPM	200 PPM	710 MG/M3	N/E
2,4-PENTANEDIONE	0.1-1.0	25 PPM	N/E	N/E	N/E
DEFOAMER	0.1-1.0	N/E	N/E	N/E	N/E
ETHYL BENZENE	0.1-1.0	20 PPM	N/E	435 MGM3	N/E

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves Request information on glove permeation properties from the glove supplier.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. Lightweight protective clothing

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Clear, Slightly Amber Liquid
Physical State	Liquid
Odor	Solvent
Odor threshold	
pH	N/D
Melting point / freezing point (°C)	N/D
Boiling point/range (°C)	149 F (65 C) - 518 F (270 C)
Flash Point, (°C)	10
Evaporation rate	
Flammability (solid, gas)	
Upper/lower flammability or explosive limits	Not determined
Vapour Pressure, mmHg	N/D
Vapour density	
Relative density	
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	
Auto-ignition temperature (°C)	
Decomposition temperature (°C)	
Viscosity	Unknown

Explosive properties**Oxidising properties****9.2 Other information**

VOC Content g/l:	240
Specific Gravity (g/cm ³)	0.99

10. Stability and Reactivity**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information**11.1 Information on toxicological effects****Acute Toxicity:**

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
110-43-0	METHYL N-AMYL KETONE	1670 mg/kg rat oral		2000 ppm, 4 hours
616-38-6	DIMETHYL CARBONATE	12900 mg/kg, oral, rat	>2000 mg/kg, dermal, rabbit	Not Available
540-88-5	TERT-BUTYL ACETATE	3160 mg/kg, oral, rat		4000 ppm/6 hours, rat inhalation
78-93-3	METHYL ETHYL KETONE	2194 mg/kg rat, oral		34.5 mg/L/ 4 hour rat, inhalation
TRADE SECRET	ALIPHATIC DIOL	Not Available		Not Available
108-88-3	TOLUENE	5000 mg/kg rat oral	12267 mg/kg, dermal, rabbit	8000 ppm/4 hrs, rat, inhalation
123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4/h, Inh. rat
123-54-6	2,4-PENTANEDIONE	55 mg/kg oral, rat		10 mg/24 hours rabbit
64742-46-7	DEFOAMER	>5000 mg/kg, rat, oral		NOT AVAILABLE
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr

Additional Information:

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	Unknown
IC50 72hr (Algae):	Unknown
LC50 96hr (fish):	Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: Unknown

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
110-43-0	METHYL N-AMYL KETONE	No information	No information	No information
616-38-6	DIMETHYL CARBONATE	100 mg/l (Daphnia magna)	100 mg/l (Algae)	100 mg/l (Zebra Fish)
540-88-5	TERT-BUTYL ACETATE	No information	No information	No information
78-93-3	METHYL ETHYL KETONE	308 mg/l (Daphnia magna)	No information	2993 mg/l (Pimephales promelas)

TRADE SECRET	ALIPHATIC DIOL	No information	No information	No information
108-88-3	TOLUENE	6 mg/l (Daphnia magna)	12.5 mg/L (Algae)	5.8 mg/L (Fish)
123-86-4	N-BUTYL ACETATE	44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)
123-54-6	2,4-PENTANEDIONE	No information	No information	No information
64742-46-7	DEFOAMER	No information	No information	No information
100-41-4	ETHYL BENZENE	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number	UN 1263
14.2 UN proper shipping name	Paint
Technical name	N/A
14.3 Transport hazard class(es)	3
Subsidiary shipping hazard	N/A
14.4 Packing group	II
14.5 Environmental hazards	Unknown
14.6 Special precautions for user	Unknown
EmS-No.:	F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
TOLUENE	108-88-3
ETHYL BENZENE	100-41-4

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name**CAS-No.**

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:

EPA VOC Content Limit (g/l):

Product VOC Content (g/l)

Thinning Recommendations:

Application Recommendations:

Harmful if swallowed.

U.S. State Regulations: As follows -**New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name**CAS-No.**

ACRYLIC COPOLYMER

TRADE SECRET

ACRYLIC POLYOL

TRADE SECRET

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name**CAS-No.**

ACRYLIC COPOLYMER

TRADE SECRET

ACRYLIC POLYOL

TRADE SECRET

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name**CAS-No.**

ETHYL BENZENE

100-41-4

BENZENE

71-43-2

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name**CAS-No.**

TOLUENE

108-88-3

METHYL ALCOHOL

67-56-1

BENZENE

71-43-2

International Regulations: As follows -*** Canadian DSL:**

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Reasons for revision

No Information

No Information