

## SELECTION & SPECIFICATION DATA

<b>Generic Type</b>	Specially formulated citric acid solution
<b>Description</b>	<p>Carbozinc (water based) Neutralizing Solution is an organic and biodegradable product designed specifically for use with Carbozinc and Carboweld water-based, inorganic primers, including:</p> <p>Carbozinc 11 WB Carbozinc 18 WB Carboweld 9 WB Carboweld 11 WB Carboweld 14 WB</p> <p>It is an environmentally safe product that will clean, neutralize (lower the surface pH), and degrease the waterbased Carbozinc/weld primers for topcoating. This product does not contain any bleach, chlorinated solvents, phosphates, muriatic or ozone depleting ingredients.</p>
<b>Features</b>	<ul style="list-style-type: none"> <li>• Water-based, biodegradable</li> <li>• Easy to use</li> <li>• Prepares water-based inorganic zincs for topcoating</li> </ul>
<b>Color</b>	Clear liquid
<b>Coverage Rate</b>	<p>Approximately 200-250 ft<sup>2</sup>/gal (4.9-6.1 m<sup>2</sup>/gal)</p> <p>Apply liberally.</p>

## APPLICATION PROCEDURES

<b>General</b>	Apply liberally by brush, roller, pumpstyle sprayer, airless or pressure washer. On vertical surfaces start from the bottom and work up. Wait 2 hours; agitate the surface with scrub brushes or similar and then rinse thoroughly or power wash with clean potable water. Allow to thoroughly dry and check for pH. Optimum pH should be in the 5-7 range.
----------------	---

## CLEANUP & SAFETY

<b>Safety</b>	Read and follow all caution statements on this product data sheet and on the SDS for this product. Employ normal workmanlike safety precautions. Solution is corrosive. Wear chemical resistant gloves, apron, footwear, and eye/face protection. Use adequate ventilation. Keep container closed when not in use.
---------------	--

## PACKAGING, HANDLING & STORAGE

<b>Shelf Life</b>	<p>36 months at 75 °F (24 °C)</p> <p>*Shelf Life: (actual stated shelf life) when kept at recommended storage conditions and in original unopened containers.</p>
<b>Storage Temperature &amp; Humidity</b>	<p>40-110 °F (4-43 °C)</p> <p>0-90% Relative Humidity</p>
<b>Storage</b>	Store Indoors.
<b>Shipping Weight (Approximate)</b>	<p>5 Gal - 45 lbs (20 kg)</p> <p>50 Gal Drum - 485 lbs (220 kg)</p>

# CZ (WB) Neutralizing Solution

## PRODUCT DATA SHEET

---



### WARRANTY

---

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Carboline Company to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Carboline quality control. We assume no responsibility for coverage, performance, injuries or damages resulting from use. Carbolines sole obligation, if any, is to replace or refund the purchase price of the Carboline product(s) proven to be defective, at Carbolines option. Carboline shall not be liable for any loss or damage. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY CARBOLINE, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. All of the trademarks referenced above are the property of Carboline International Corporation unless otherwise indicated.