

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

Product Identifier 8808B1NL

URETHANE CONVERTER 8800 **Revision Date:** 05/17/2019 **Product Name:**

Component of multicomponent

Supercedes Date: 04/15/2016

1.2 Relevant identified uses of the substance or mixture and uses

advised against

industrial coatings - Industrial

use.

1.3 Details of the supplier of the safety data sheet

Carboline Company Manufacturer:

2150 Schuetz Road St. Louis, MO USA 63146

Regulatory / Technical Information: Contact Carboline Technical Services at

1-800-848-4645

Alotta, Vicki - ehs@stoncor.com **Datasheet Produced by:**

CHEMTREC 1-800-424-9300 (Inside US) 1.4 Emergency telephone number:

CHEMTREC +1 703 5273887 (Outside US)

HEALTH - Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification

Classification of the substance or mixture 2.1

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 2 Eye Irritation, category 2 Flammable Liquid, category 2 Respiratory Sensitizer, category 1 STOT, single exposure, category 3, NE STOT, single exposure, category 3, RTI Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

METHYL ETHYL KETONE, N-BUTYL ACETATE, HEXAMETHYLENE DIISOCYANATE, HOMOPOLYMER OF HDI, AROMATIC HYDROCARBON

HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P285	In case of inadequate ventilation wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P341	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342+311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	<u>Chemical Name</u>	<u>%</u>
28182-81-2	HOMOPOLYMER OF HDI	50 - <75
78-93-3	METHYL ETHYL KETONE	25 - <50
123-86-4	N-BUTYL ACETATE	2.5 - <10
64742-95-6	AROMATIC HYDROCARBON	2.5 - <10
822-06-0	HEXAMETHYLENE DIISOCYANATE	0.1 - <1.0

<u>CAS-No.</u>	GHS Symbols	GHS Hazard Statements	M-Factors
28182-81-2	GHS07-GHS09	H317-332-335-411	0
78-93-3	GHS02-GHS07	H225-319-336	0
123-86-4	GHS02-GHS07	H226-336	0
64742-95-6	GHS02-GHS07-GHS08-GHS09	H226-304-315-319-332-335-336-411	0
822-06-0	GHS06-GHS08	H302-315-317-319-330-334-335	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Humid air and/or water will produce carbon dioxide which will pressurize the container. Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks. Exposure to moisture.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
HOMOPOLYMER OF HDI	28182-81-2	N/E	N/E	N/E
METHYL ETHYL KETONE	78-93-3	200 PPM	300 PPM	N/E
N-BUTYL ACETATE	123-86-4	50 PPM	150 PPM	N/E
AROMATIC HYDROCARBON	64742-95-6	300.0 PPM	N/E	N/E
HEXAMETHYLENE DIISOCYANATE	822-06-0	0.005 PPM	N/E	N/E
<u>Name</u>	CAS-No.	OSHA PEL	OSHA STEL	
HOMOPOLYMER OF HDI	28182-81-2	N/E	N/E	

METHYL ETHYL KETONE 78-93-3 590 MGM3, 200 885 MGM3, 300

PPM PPM

N-BUTYL ACETATE 123-86-4 710 MGM3, 150 950 MGM3, 200

PPM PPM

AROMATIC HYDROCARBON 64742-95-6 500.0 PPM N/E

HEXAMETHYLENE DIISOCYANATE 822-06-0 N/E N/E

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Colorless, Mobile Liquid

Physical State Liquid
Odor Solvent
Odor threshold N/D
pH N/D
Melting point / freezing point (°C) N/D

Boiling point/range 262 F (128 C) - 262F (128C)

Flash Point 28F (-2C)

Evaporation rate Slower Than Ether

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive 0.9 - 10.1

limits

Vapour Pressure, mmHg N/D

Vapour density Heavier than Air
Relative density Not determined

Solubility in / Miscibility with water Reacts

Partition coefficient: n-octanol/water Not determined

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity Unknown

Explosive properties Not determined

Oxidising properties Not determined

9.2 Other information

VOC Content g/l: See Part A MSDS

Specific Gravity (g/cm3) 1.00

10. Stability and Reactivity

10.1 Reactivity

Water reactive

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks. Exposure to moisture.

10.5 Incompatible materials

Never allow product to get in contact with water during storage. Water in the container will lead to increased pressure and risk of explosion. Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: N/D Inhalation LC50: N/D

Irritation: Eye Irritation, category 2

Corrosivity: Unknown

Sensitization: Skin Sensitizer and Respiratory Sensitizer, category 1

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

STOT-single exposure: STOT, single exposure, category 3, NE & RTI

STOT-repeated exposure: Unknown

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
28182-81-2	HOMOPOLYMER OF HDI	5000 mg/kg, oral, rat	Not Available	390 mg/m3, inhalation, rat	0.000	0.000
78-93-3	METHYL ETHYL KETONE	2194 mg/kg rat, oral	Not Available	34.5 mg/L/ 4 hour rat, inhalation	0.000	0.000
123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4/h, Inh. rat		
64742-95-6	AROMATIC HYDROCARBON	4700 mg/kg, oral, rat	Not Available	3670 ppm/8 hours, rat, inhalation	0.000	0.000
822-06-0	HEXAMETHYLENE DIISOCYANATE	710 mg/kg, oral rat	>7000 mg/kg, dermal, rat	23 ppm / 4 hrs	0.000	0.000

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

Unknown

Unknown

Unknown

Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB

assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: Unknown

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
28182-81-2	HOMOPOLYMER OF HDI	>100 mg/l (Zebra Fish)	No information	>100 mg/l (Zebra Fish)
78-93-3	METHYL ETHYL KETONE	308 mg/l (Daphnia magna)	No information	2993 mg/l (Pimephales promelas)
123-86-4	N-BUTYL ACETATE	44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)
64742-95-6	AROMATIC HYDROCARBON	No information	No information	No information
822-06-0	HEXAMETHYLENE DIISOCYANATE	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN1993

14.2 UN proper shipping name Flammable Liquid NOS

Technical name Methyl Ethyl Ketone, Butyl Acetate

14.3 Transport hazard class(es)
Subsidiary shipping hazard
14.4 Packing group

14.5 Environmental hazards Unknown

14.6 Special precautions for user Unknown EmS-No.: F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Unknown

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Acute Toxicity (any route of exposure), Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.HEXAMETHYLENE DIISOCYANATE822-06-0

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u> <u>CAS-No.</u>

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour.

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.