



Safety Data Sheet
 prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

- 1.1 Product Identifier** G004A1NL
- Product Name:** CARBOZINC 858 (3K) PART A **Revision Date:** 09/03/2015
- 1.2 Relevant identified uses of the substance or mixture and uses advised against** Component of multicomponent industrial coatings - Industrial use. **Supersedes Date:** 05/30/2015
- 1.3 Details of the supplier of the safety data sheet**
- Manufacturer:** Carboline Company
 2150 Schuetz Road
 St. Louis, MO USA 63146
- Regulatory / Technical Information:
 Contact Carboline Technical Services at
 1-800-848-4645
- Datasheet Produced by:** Schlereth, Ken - ehs@stoncor.com
- 1.4 Emergency telephone number:** CHEMTREC 1-800-424-9300 (Inside US)
 CHEMTREC +1 703 5273887 (Outside US)
 HEALTH - Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 3
 Carcinogenicity, category 1A
 Eye Irritation, category 2
 Flammable Liquid, category 2
 Reproductive Toxicity, category 1A
 STOT, single exposure, category 3, RT1
 Skin Irritation, category 2
 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

N-BUTANOL, PARA-XYLENE, MICROCRYSTALLINE SILICA, EPOXY RESIN, ANHYDROUS ALUMINUM SILICATE

GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
Reproductive Toxicity, category 1A	H360-1A	May damage fertility or the unborn child.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

GHS PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+313	If skin irritation occurs: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
25036-25-3	EPOXY RESIN	25-50
66402-68-4	ANHYDROUS ALUMINUM SILICATE	10-25
78-93-3	METHYL ETHYL KETONE	10-25
25068-38-6	EPOXY RESIN	2.5-10
108-38-3	META-XYLENE	2.5-10
9003-53-6	POLYSTYRENE	2.5-10
110-12-3	METHYL ISOAMYL KETONE	2.5-10
100-41-4	ETHYL BENZENE	1.0-2.5
106-42-3	PARA-XYLENE	1.0-2.5
71-36-3	N-BUTANOL	1.0-2.5
95-47-6	ORTHO-XYLENE	1.0-2.5
14808-60-7	MICROCRYSTALLINE SILICA	0.1-1.0
121-44-8	TRIETHYLAMINE	<0.1

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
25036-25-3	GHS07	H315-317-319	0
66402-68-4	GHS07	H315-319-335	0
78-93-3	GHS02-GHS07	H225-319-336	0
25068-38-6	GHS07-GHS09	H315-317-319-335-411	0
108-38-3	GHS07-GHS07	H226-312-315-332	0
9003-53-6	GHS08	H360	0
110-12-3	GHS02-GHS07	H226-332	0
100-41-4	GHS02-GHS07	H225-332	0
106-42-3	GHS02-GHS07-GHS08	H226-312-315-332-335-371	0
71-36-3	GHS02-GHS05-GHS07	H226-302-315-318-335-336	0
95-47-6	GHS02-GHS07	H226-312-315-332	0
14808-60-7	GHS08	H350-370	0
121-44-8	GHS02-GHS05-GHS06	H225-302-312-314-331	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along

floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8. Ensure adequate ventilation. Evacuate personnel to safe areas. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

Name	%	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	OEL Note
EPOXY RESIN	25-50	N/E	N/E	N/E	N/E	
ANHYDROUS ALUMINUM SILICATE	10-25	10.0 MG/M3	N/E	5.0 MG/M3	N/E	
METHYL ETHYL KETONE	10-25	200 PPM	300 PPM	590 MGM3	N/E	
EPOXY RESIN	2.5-10	N/E	N/E	N/E	N/E	
META-XYLENE	2.5-10	100 PPM	150 PPM	435 MG/M3	N/E	
POLYSTYRENE	2.5-10	N/E	N/E	N/E	N/E	
METHYL ISOAMYL KETONE	2.5-10	50 PPM	N/E	240 MGM3	N/E	
ETHYL BENZENE	1.0-2.5	20 PPM	N/E	435 MGM3	N/E	
PARA-XYLENE	1.0-2.5	100 PPM	150 PPM	435 MGM3	N/E	
N-BUTANOL	1.0-2.5	20 PPM	50 ppm	300.0 MG/M3	150 MGM3	
ORTHO-XYLENE	1.0-2.5	100 PPM	150 PPM	435 MG/M3	N/E	
MICROCRYSTALLINE SILICA	0.1-1.0	0.025 MG/M3 (respirable)	N/E	0.1 MG/M3 (respirable)	N/E	
TRIETHYLAMINE	<0.1	1 PPM	3 PPM	40 PPM	N/E	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. Lightweight protective clothing

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Dark Yellow Liquid
Physical State	Liquid
Odor	Epoxy
Odor threshold	N/D
pH	N/D
Melting point / freezing point (°C)	N/D
Boiling point/range (°C)	173 F (78 C) - 500 F (260 C)
Flash Point, (°C)	14

Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	0.9 - 12.0
Vapour Pressure, mmHg	N/D
Vapour density	Heavier than Air
Relative density	Not determined
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Unknown
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	317
Specific Gravity (g/cm³)	1.16

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
25036-25-3	EPOXY RESIN	>2000 mg/kg, oral, rat	>2000 mg/kg, dermal, rat	Not Available
66402-68-4	ANHYDROUS ALUMINUM SILICATE	Not Available		Not Available
78-93-3	METHYL ETHYL KETONE	2194 mg/kg rat, oral		34.5 mg/L/ 4 hour rat, inhalation
25068-38-6	EPOXY RESIN	11400 mg/kg, rat, oral	23000 mg/kg, dermal, rabbit	>20 mL/kg skin, sensitizer
108-38-3	META-XYLENE	Not Available		Not Available
9003-53-6	POLYSTYRENE	Not Available		Not Available
110-12-3	METHYL ISOAMYL KETONE	5700 mg/kg, oral, rat		3813 ppm, 6 hours
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr
106-42-3	PARA-XYLENE	Not Available		Not Available
71-36-3	N-BUTANOL	790 mg/kg rat, oral	3400 mg/kg, dermal, rabbit	8000 ppm / 4hrs rat, inhalation
95-47-6	ORTHO-XYLENE	Not Available		Not Available
14808-60-7	MICROCRYSTALLINE SILICA	Not Available	Not Available	Not Available
121-44-8	TRIETHYLAMINE	460 mg/kg, oral, rat		6 gm/m ³ , mouse, inh

Additional Information:

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

12. Ecological Information

12.1 Toxicity:	
EC50 48hr (Daphnia):	Unknown
IC50 72hr (Algae):	Unknown
LC50 96hr (fish):	Unknown
12.2 Persistence and degradability:	Unknown
12.3 Bioaccumulative potential:	Unknown
12.4 Mobility in soil:	Unknown
12.5 Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.
12.6 Other adverse effects:	Unknown

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
25036-25-3	EPOXY RESIN	No information	No information	No information
66402-68-4	ANHYDROUS ALUMINUM SILICATE	No information	No information	No information
78-93-3	METHYL ETHYL KETONE	308 mg/l (Daphnia magna)	No information	2993 mg/l (Pimephales promelas)
25068-38-6	EPOXY RESIN	2.1 mg/l (daphnia)	11 mg/l (algae)	1.3 mg/l (fish)
108-38-3	META-XYLENE	No information	No information	No information
9003-53-6	POLYSTYRENE	No information	No information	No information
110-12-3	METHYL ISOAMYL KETONE	No information	No information	No information
100-41-4	ETHYL BENZENE	No information	No information	No information
106-42-3	PARA-XYLENE	No information	No information	No information
71-36-3	N-BUTANOL	1328 mg/l (Daphnia magna)	225 mg/l (Algae)	1376 mg/l (Fathead minnow)
95-47-6	ORTHO-XYLENE	No information	No information	No information
14808-60-7	MICROCRYSTALLINE SILICA	No information	No information	No information
121-44-8	TRIETHYLAMINE	No information	No information	No information

13. Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number	UN 1263
14.2 UN proper shipping name	Paint
Technical name	Unknown
14.3 Transport hazard class(es)	3
Subsidiary shipping hazard	N/A
14.4 Packing group	II
14.5 Environmental hazards	Marine Pollutant: Yes (Epoxy Resin)
14.6 Special precautions for user	Unknown
EmS-No.:	F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
META-XYLENE	108-38-3
ETHYL BENZENE	100-41-4
PARA-XYLENE	106-42-3
N-BUTANOL	71-36-3
ORTHO-XYLENE	95-47-6
TRIETHYLAMINE	121-44-8

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
----------------------	----------------

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
CLAY	TRADE SECRET

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
CLAY	TRADE SECRET
MODIFIED RESIN	TRADE SECRET
YELLOW IRON OXIDE	51274-00-1

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
ETHYL BENZENE	100-41-4
MICROCRYSTALLINE SILICA	14808-60-7
FORMALDEHYDE	50-00-0
CUMENE	98-82-8
BENZENE	71-43-2

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
TOLUENE	108-88-3
BENZENE	71-43-2

International Regulations: As follows -*** Canadian DSL:**

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H371	May cause damage to organs.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

No Information

