



# Material Safety Data Sheet

**CHEMTREC Transportation  
Emergency Phone: 800-424-9300**

**Pittsburgh Poison Control  
Center  
Health Emergency No.: 412-681-6669**

•NOTE: The CHEMTREC Transportation  
•Emergency Phone is to be used only in the  
•event of chemical emergencies involving a  
•spill, leak, fire, exposure or accident  
•involving chemicals

## Section 1 - Chemical Product / Company Information

**Product Name:** CARBOCRYLIC 3359 FLAT  
**Identification Number:** PLMSDS P420S1NL  
**Product Use/Class:** FOR INDUSTRIAL USE ONLY  
**Revision Date:** 03/30/2011  
**Supersedes :** 05/03/2010  
**Preparer:** Regulatory, Department  
**Manufacturer:** Carboline Company  
2150 Schuetz Road  
St. Louis, MO 63146  
(800) 848-4645

## Section 2 - Composition / Information On Ingredients

Chemical Name	CAS Number	Weight % Less Than	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA-CEIL
TITANIUM DIOXIDE	13463-67-7	20.0	10 MGM3	N/E	10 MGM3	N/E
SILICA GEL	7631-86-9	10.0	3 MGM3	N/E	6 MGM3	NE
DM GLYCOL ETHER	111-77-3	5.0	NE	NE	NE	NE
DIBUTYL PHTHALATE	84-74-2	5.0	5 MGM3	N/E	5 MGM3	NE
GLYCOL ETHER SOLVENT	112-34-5	5.0	NE	N/E	NE	NE
CARBON BLACK	1333-86-4	1.0	3.5 MG/M3	N/E	3.5 MG/M3	N/E

## Section 3 - Hazards Identification

**Emergency Overview:** Use ventilation necessary to keep exposures below recommended exposure limits, if any.

**Effects Of Overexposure - Eye Contact:** May cause eye irritation.

**Effects Of Overexposure - Skin Contact:** May cause skin irritation.

**Effects Of Overexposure - Inhalation:** Harmful if inhaled, may affect the brain or nervous system, causing dizziness, headache, or nausea. May cause nose and throat irritation. Use in inadequately ventilated areas may result in irritation headache and nausea.

**Effects Of Overexposure - Ingestion:** May be harmful if swallowed.

**Effects Of Overexposure - Chronic Hazards:** Under normal use conditions, this product is not expected to cause adverse health effects. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

**Primary Route(s) Of Entry:** Skin Contact, Inhalation, Ingestion, Eye Contact

**Medical Conditions Prone to Aggravation by Exposure:** If you have a condition that could be aggravated by exposure to dust or organic vapors, see a physician prior to use.

## Section 4 - First Aid Measures

**First Aid - Eye Contact:** If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

**First Aid - Skin Contact:** Launder clothing before reuse. In case of contact, wash skin immediately with soap and water.

**First Aid - Inhalation:** If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

**First Aid - Ingestion:** If swallowed do not induce vomiting. Seek immediate medical attention.

## Section 5 - Fire Fighting Measures

**Flash Point, F:** 239F (115C)  
(Setaflash)

**Lower Explosive Limit, %:** 0.6  
**Upper Explosive Limit, %:** 24.6

**Extinguishing Media:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**Unusual Fire And Explosion Hazards:** This is a water based product, however it does contain small amounts of volatile organic compounds (See Section II). Vapors are heavier than air and will accumulate. Vapors will form explosive concentrations with air. Vapors travel long distances and will flashback.

**Special Firefighting Procedures:** Evacuate hazard area of unprotected personnel. Use a NIOSH approved self-contained breathing unit and complete body protection. Cool surrounding containers with water in case of fire exposure.

## Section 6 - Accidental Release Measures

**Steps To Be Taken If Material Is Released Or Spilled:** Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Evacuate the area of unprotected personnel. Wear appropriate personal protection clothing and equipment. Follow exposure controls/personal protection guidelines in Section 8. Contain and soak up residual with an absorbent (clay or sand). Take up absorbant material and seal tightly for proper disposal. Dispose of in accordance with local, state and federal regulations. Refer to Section 15 for SARA Title III and CERCLA information.

## Section 7 - Handling And Storage

**Handling:** Do not get in eyes, on skin, or on clothing. Keep container tightly closed when not in use. Wear personal protection equipment. Do not breathe vapors. Wash thoroughly after handling. If pouring or transferring materials, ground all containers and tools. Do not weld, heat, cut or drill on full or empty containers. Use only in accordance with Carboline application instructions, container label and Product Data Sheet. Avoid breathing vapors or spray mist.

**Storage:** Protect from Freezing! Keep away from heat, sparks, open flames and oxidizing agents. Keep containers closed. Store in a cool, dry place with adequate ventilation.

## Section 8 - Exposure Controls / Personal Protection

**Engineering Controls:** Use explosion-proof ventilation when required to keep below health exposure guidelines and Lower Explosion Limit (LEL).

**Respiratory Protection:** Use only with ventilation to keep levels below exposure guidelines listed in Section 2. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use MSHA/NIOSH approved supplied air respirator. Follow all current OSHA requirements for respirator use. For silica containing coatings in a liquid state, and/or if no exposure limits are established in Section 2 above, supplied air respirators are generally not required.

**Skin Protection:** Recommend impervious gloves and clothing to avoid skin contact. If material penetrates to skin, change gloves and clothing. The use of protective creams may be beneficial to certain individuals. Protective creams should be applied before exposure.

**Eye Protection:** Recommend safety glasses with side shields or chemical goggles to avoid eye contact.

**Other protective equipment:** Eye wash and safety showers should be readily available.

**Hygienic Practices:** Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Use of a hand cleaner is recommended. Launder contaminated clothing before reuse. Leather shoes can absorb and allow hazardous materials to pass through. Check shoes carefully after soaking before reuse. Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited.

## Section 9 - Physical And Chemical Properties

<b>Boiling Range:</b>	212 F (100 C) - 644 F (340 C)	<b>Vapor Density:</b>	Heavier than Air
<b>Odor:</b>	Ammoniacal	<b>Odor Threshold:</b>	N/D
<b>Appearance:</b>	Viscous Black or Grey Liquid	<b>Evaporation Rate:</b>	Slower Than Ether
<b>Solubility in H<sub>2</sub>O:</b>	N/D		
<b>Freeze Point:</b>	32F (0C)	<b>Specific Gravity:</b>	app. 1.06
<b>Vapor Pressure:</b>	N/D	<b>PH:</b>	N/D
<b>Physical State:</b>	Liquid		

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

**Conditions To Avoid:** Heat, sparks and open flames.

**Incompatibility:** Avoid contact with strong oxidizing agents.

**Hazardous Decomposition Products:** Carbon monoxide, nitrogen oxides, and unidentified organic compounds. Consider all smoke and fumes from burning material as very hazardous. Welding, cutting or abrasive grinding can create smoke and fumes. Do not breathe any fumes or smoke from these operations.

**Hazardous Polymerization:** Will not occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

## Section 11 - Toxicological Information

Product LD50: N/D

Product LC50: N/D

<u>Chemical Name</u>	<u>CAS Number</u>	<u>LD50</u>	<u>LC50</u>
TITANIUM DIOXIDE	13463-67-7	>25 G/KG, ORAL, RAT	>6.82 MG/L 4 HR, RAT
SILICA GEL	7631-86-9	NOT AVAILABLE	NOT AVAILABLE
DM GLYCOL ETHER	111-77-3	>7000 MG/KG, ORAL, RAT	NOT AVAILABLE
DIBUTYL PHTHALATE	84-74-2	20,000 MG/KG, ORAL, RAT	NOT AVAILABLE
GLYCOL ETHER SOLVENT	112-34-5	7292MG/KG,ORAL,RAT 2406MG/KG,ORAL MOUSE	NOT AVAILABLE
CARBON BLACK	1333-86-4	NOT AVAILABLE	>8000 MG/KG, ORAL, RAT

## Section 12 - Ecological Information

Ecological Information: No data

## Section 13 - Disposal Information

**Disposal Information:** Dispose of in accordance with State, Local, and Federal Environmental regulations. Responsibility for proper waste disposal is with the owner of the waste.

## Section 14 - Transportation Information

<b>DOT Proper Shipping Name:</b>	Not Regulated	<b>Packing Group:</b>	N/A
<b>DOT Technical Name:</b>	N/A	<b>Hazard Subclass:</b>	N/A
<b>DOT Hazard Class:</b>	None	<b>Resp. Guide</b>	N/A
		<b>Page:</b>	
<b>DOT UN/NA Number:</b>	None		

**Additional Notes:** None.

## Section 15 - Regulatory Information

### CERCLA - SARA HAZARD CATEGORY

This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS Number</u>
DIBUTYL PHTHALATE	84-74-2
GLYCOL ETHER SOLVENT	112-34-5

### TOXIC SUBSTANCES CONTROL ACT

All components of this product are listed on the TSCA inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if

exported from the United States:

No TSCA 12(B) Substances exist in this product

#### U.S. STATE REGULATIONS AS FOLLOWS:

##### NEW JERSEY RIGHT-TO-KNOW

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS Number</u>
WATER	7732-18-5
ACRYLIC RESIN	TRADE SECRET

##### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS Number</u>
WATER	7732-18-5
ACRYLIC RESIN	TRADE SECRET

##### CALIFORNIA PROPOSITION 65

**Warning: The following ingredients present in the product are known to the state of California to cause Cancer:**

<u>Chemical Name</u>	<u>CAS Number</u>
CARBON BLACK	1333-86-4

**Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards:**

<u>Chemical Name</u>	<u>CAS Number</u>
DIBUTYL PHTHALATE	84-74-2

#### INTERNATIONAL REGULATIONS AS FOLLOWS:

##### CANADIAN WHMIS

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** D2B

### Section 16 - Other Information

#### HMIS Ratings

Health: 2

Flammability: 1

Reactivity: 1

Personal Protection: X

**VOLATILE ORGANIC COMPOUNDS, GR/LTR MIXED (UNTHINNE):** 132

**REASON FOR REVISION:** Name change from "Carboline 3359 Flat" to "Carbocrylic 3359 Flat"

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations