

Carbocrylic® 3359 DTM



Carbocrylic 3359 DTM is a single-component durable, high performance direct-to-metal acrylic coating for use where excellent weathering properties and chemical resistance are required.

PRODUCT DETAILS A modified acrylic terpolymer that has excellent flash-rust resistance and weatherability. Use as a direct-to-metal acrylic coating for tank exteriors, piping, and structural steel, as well as other exterior and interior uses. May also be used as a finish coat over recommended primers. A true high-gloss appearance, it has excellent color and gloss retention. It has high-build features and does not require a special primer for adhesion or performance. In addition, its dry-fall properties makes it ideal for elevated spray applied projects.

APPLICATIONS

- MARINE
- TANKS AND VESSELS
- PIPELINE AND TERMINALS
- OIL AND GAS
- POWER
- RAILCAR
- PULP AND PAPER
- CHEMICAL PROCESSING
- WATER - WASTEWATER

FEATURES

- › Smooth, attractive, high build finish
- › Excellent weatherability, gloss and color retention
- › Low Odor
- › Excellent corrosion protection
- › Meets most VOC regulations
- › Outstanding application characteristics
- › Dry fall characteristics
- › Use 3359 DTMC for projects that require VOC less than 100 g/l

Carbocrylic® 3359 DTM

Quality Product Backed by Quality Service

- › Carboline Company has been solving tough corrosion and fireproofing problems since 1947
- › Industrial service centers and sales offices located around the world
- › Over 20 worldwide manufacturing locations with a global network of sales and technical support
- › Industry leading field service and technical engineering support team
- › Certified to ISO 9001

Reasons To Use Carbocrylic 3359 DTM

PERFORMANCE FEATURE	ADVANTAGE	BENEFIT
Smooth, Attractive, High Build Finish	Excellent barrier protection	Longer service life
Unique acrylic terpolymer formula	Excellent weatherability gloss and color retention	Great looking appearance for long period, extending repaints.
Low Odor	Less ventilation requirements, can apply more square feet over a given period.	Safer to use, faster production
Flash rust inhibitor	Prevents rusting over steel substrates	Longer service life



Carboline Company
Global Headquarters
2150 Schuetz Road
St. Louis, MO 63146 USA
PH: +1-314-644-1000
www.carboline.com