



Safety Data Sheet

Prepared in Accordance with HCS 29
C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

- | | | | |
|--|--|-------------------------|------------|
| 1.1 Product Identifier | 0374S1NL | Revision Date: | 06/02/2023 |
| Product Name: | THINNER 241 | Supersedes Date: | 12/06/2022 |
| 1.2 Relevant identified uses of the substance or mixture and uses advised against | Thinner for industrial coatings - Industrial use. | | |
| 1.3 Details of the supplier of the safety data sheet | | | |
| Manufacturer: | Carboline Global Inc.
2150 Schuetz Road
St. Louis, MO USA 63146 | | |
| | Regulatory / Technical Information:
Contact Carboline Technical Services at
1-800-848-4645 | | |
| Datasheet Produced by: | Beebe, Hayli - regulatory@carboline.com | | |
| 1.4 Emergency telephone number: | CHEMTREC 1-800-424-9300 (Inside US)
CHEMTREC +1 703 5273887 (Outside US)
HEALTH - Pittsburgh Poison Control 1-412-681-6669 | | |

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
Hazardous to the aquatic environment, Chronic, category 3
Aspiration Hazard, category 1
Carcinogenicity, category 1A
Eye Irritation, category 2
Flammable Liquid, category 3
STOT, single exposure, category 3, RT1
Skin Irritation, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

ORTHO-XYLENE, ETHYL BENZENE, PARA-XYLENE, META-XYLENE, AROMATIC HYDROCARBON

HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P331	Do NOT induce vomiting.
P332+313	If skin irritation occurs: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

ADDITIONAL INFORMATION

Note_P 64742-95-6	Note P : The classification as a carcinogen or mutagen need not apply; the substance, CAS 64742-95-6, contains less than 0,1 % w/w benzene
----------------------	--

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
1-METHOXY-2-PROPANOL ACETATE	203-603-9	108-65-6	10 - <25	H226	Flam. Liq. 3
AROMATIC HYDROCARBON	265-199-0	64742-95-6	10 - <25	H226-304-315-319-331-335-336-351-411	Acute Tox. 3 Inhalation, Aquatic Chronic 2, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI
META-XYLENE	203-576-3	108-38-3	10 - <25	H312-315-332	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Skin Irrit. 2
PARA-XYLENE	203-396-5	106-42-3	2.5 - <10	H304-312-315-332-335-371	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Asp. Tox. 1, Skin Irrit. 2, STOT SE 2, STOT SE 3 RTI
ETHYL BENZENE	202-849-4	100-41-4	2.5 - <10	H225-304-315-319-332-351-373-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2
ORTHO-XYLENE	202-422-2	95-47-6	2.5 - <10	H312-315-332	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Skin Irrit. 2
HEXYL ACETATE	205-572-7	142-92-7	1.0 - <2.5	H226	
CUMENE	202-704-5	98-82-8	0.1 - <1.0	H226-304-335-350-411	Aquatic Chronic 2, Asp. Tox. 1, Carc. 1A, Flam. Liq. 3, STOT SE 3 RTI
TOLUENE	203-625-9	108-88-3	0.1 - <1.0	H225-304-315-319-332-335-336-361-370-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 1, STOT SE 3 NE, STOT SE 3 RTI

<u>CAS-No.</u>	<u>M-Factors</u>
108-65-6	0
64742-95-6	0
108-38-3	0
106-42-3	0
100-41-4	0
95-47-6	0
142-92-7	0
98-82-8	0
108-88-3	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms

continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
1-METHOXY-2-PROPANOL ACETATE	108-65-6	N/E	N/E	N/E
AROMATIC HYDROCARBON	64742-95-6	300.0 PPM	N/E	N/E
META-XYLENE	108-38-3	100 PPM	150 PPM	N/E
PARA-XYLENE	106-42-3	100 PPM	150 PPM	N/E
ETHYL BENZENE	100-41-4	20 PPM	125 ppm	
ORTHO-XYLENE	95-47-6	100 PPM	150 PPM	N/E
HEXYL ACETATE	142-92-7	N/E	N/E	N/E
CUMENE	98-82-8	50 PPM	N/E	N/E
TOLUENE	108-88-3	20 PPM	N/E	N/E

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
1-METHOXY-2-PROPANOL ACETATE	108-65-6	N/E	N/E
AROMATIC HYDROCARBON	64742-95-6	500.0 PPM	N/E
META-XYLENE	108-38-3	100.00 PPM	N/E
PARA-XYLENE	106-42-3	100.00 PPM	N/E
ETHYL BENZENE	100-41-4	435 MGM3, 100 PPM	145 MGM3, 125 PPM
ORTHO-XYLENE	95-47-6	100.00 PPM	N/E

HEXYL ACETATE	142-92-7	N/E	N/E
CUMENE	98-82-8	245 MGM3, 50 PPM	N/E
TOLUENE	108-88-3	200 ppm	560 MGM3, 150 PPM

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Clear Liquid
Physical State	Liquid
Odor	Solvent
Odor threshold	N/D
pH	N/D
Melting point / freezing point (°C)	N/D
Boiling point/range (°C)	298 F (147 C) - 435 F (224 C)
Flash Point (°C)	81F (27C)
Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	1.2 - 8.0
Vapour Pressure, mmHg	3.9 mmHg @ 20 C
Vapour density	Heavier than Air
Relative density	Not determined
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined

Viscosity	Not Determined
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	886
Specific Gravity (g/cm3)	0.89

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Eye Irritation and Skin Irritation, category 2

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Carcinogenicity, category 1A

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

STOT-single exposure: STOT, single exposure, category 3, RTI

STOT-repeated exposure: Unknown

Aspiration hazard: Aspiration Hazard, category 1

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
108-65-6	1-METHOXY-2-PROPANOL ACETATE	8532 mg/kg, oral (rat)	>5000 mg/kg	101 ppm/4 hr, rat, inh	No Information	No Information
64742-95-6	AROMATIC HYDROCARBON	2001 mg/kg, rat	2001 mg/kg, rabbit	9 mg/l, rat, 4hr	0.000	0.000
108-38-3	META-XYLENE	No Information	No Information	No Information	No Information	No Information
106-42-3	PARA-XYLENE	No Information	No Information	No Information	No Information	No Information
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	No Information	No Information
95-47-6	ORTHO-XYLENE	No Information	No Information	No Information	No Information	No Information
142-92-7	HEXYL ACETATE	36230 mg/kg, oral, rat	5000 mg/kg, dermal, rat	Not Available	0.000	0.000
98-82-8	CUMENE	2910 mg/kg, oral, rat	12300 MG/KG (RABBIT)	8000 ppm / 4 hours	0.000	0.000
108-88-3	TOLUENE	5000 mg/kg rat oral	12267 mg/kg, dermal, rabbit	8000 ppm/4 hrs, rat, inhalation	No Information	No Information

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	Unknown
IC50 72hr (Algae):	Unknown
LC50 96hr (fish):	Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

12.6 Other adverse effects: Unknown

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
108-65-6	1-METHOXY-2-PROPANOL ACETATE	408 mg/l (Daphnia Magna)	>1000 mg/l (Green Algae)	161 mg/l (Fathead Minnow)
64742-95-6	AROMATIC HYDROCARBON	No information	No information	No information
108-38-3	META-XYLENE	No information	No information	No information
106-42-3	PARA-XYLENE	No information	No information	No information
100-41-4	ETHYL BENZENE	1.8 mg/l (Daphnia Magna)	4.6 mg/l (Green Algae)	4.2 mg/l (Rainbow Trout)
95-47-6	ORTHO-XYLENE	No information	No information	No information
142-92-7	HEXYL ACETATE	No information	No information	3.7 mg/L (fish)
98-82-8	CUMENE	No information	No information	6/32 mg/l (Fish)
108-88-3	TOLUENE	6 mg/l (Daphnia magna)	12.5 mg/L (Algae)	5.8 mg/L (Fish)

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number	UN 1263
14.2 UN proper shipping name	Paint Related Material
Technical name	N/A
14.3 Transport hazard class(es)	3
Subsidiary shipping hazard	N/A
14.4 Packing group	III
14.5 Environmental hazards	Unknown
14.6 Special precautions for user	Unknown
EmS-No.:	F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Aspiration Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>%</u>
META-XYLENE	108-38-3	17.92
PARA-XYLENE	106-42-3	7.79
ORTHO-XYLENE	95-47-6	5.65
1,2,4 TRIMETHYLBENZENE	95-63-6	0.2
TOLUENE	108-88-3	0.19
BENZENE	71-43-2	0

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
----------------------	----------------

ACETIC ACID ESTERS (C7-C9)

108419-32-5

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name**CAS-No.**

ACETIC ACID ESTERS (C7-C9)

108419-32-5

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -*** Canadian DSL:**

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H370	Causes damage to organs.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.