

## Safety Data Sheet prepared to UN GHS Revision 3

## 1. Identification of the Substance/Mixture and the Company/Undertaking

104RA1NL 1.1 Product Identifier

> CARBOGUARD 995 PART A **Product Name: Revision Date:** 05/04/2016

> > **Supercedes Date:** New SDS

Relevant identified uses of the substance or mixture and uses

advised against

Component of multicomponent industrial coatings - Industrial

use.

#### 1.3 Details of the supplier of the safety data sheet

Carboline Company Manufacturer:

2150 Schuetz Road St. Louis, MO USA 63146

Regulatory / Technical Information: Contact Carboline Technical Services at

1-800-848-4645

Schlereth, Ken - ehs@stoncor.com **Datasheet Produced by:** 

CHEMTREC 1-800-424-9300 (Inside US) 1.4 Emergency telephone number:

CHEMTREC +1 703 5273887 (Outside US)

HEALTH - Pittsburgh Poison Control 1-412-681-6669

## 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Acute, category 1 Hazardous to the aquatic environment, Chronic, category 1 Carcinogenicity, category 1A Reproductive Toxicity, category 2 Skin Corrosion, category 1 Skin Sensitizer, category 1

#### 2.2 Label elements

## Symbol(s) of Product



## Signal Word

Danger

#### **Named Chemicals on Label**

AMINOETHYLPIPERAZINE, POLYOXYPROPYLENEDIAMINE, MICROCRYSTALLINE SILICA, NONYL PHENOL

#### **GHS HAZARD STATEMENTS**

Skin Corrosion, category 1	H314-1	Causes severe skin burns and eye damage.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment, Acute, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, Chronic, category 1	H410	Very toxic to aquatic life with long lasting effects.

#### **GHS PRECAUTION PHRASES**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+313 P391	If skin irritation or rash occurs: Get medical advice/attention. Collect spillage.

#### 2.3 Other hazards

No Information

## Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

#### 3.2 Mixtures

#### **Hazardous Ingredients**

CAS-No.	<u>Chemical Name</u>	<u>%</u>
25154-52-3	NONYL PHENOL	25-50
13463-67-7	TITANIUM DIOXIDE	10-25
1317-65-3	LIMESTONE	10-25
9046-10-0	POLYOXYPROPYLENEDIAMINE	10-25
140-31-8	AMINOETHYLPIPERAZINE	2.5-10
TRADE SECRET	POLYAMIDE WAX	0.1-1.0
100-41-4	ETHYL BENZENE	0.1-1.0
14808-60-7	MICROCRYSTALLINE SILICA	0.1-1.0
122-99-6	2-PHENOXYETHANOL	<0.1

CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
25154-52-3	GHS05-GHS07-GHS08-GHS09	H302-314-361-400-410	0
13463-67-7			0
1317-65-3	GHS07	H315-319	0
9046-10-0	GHS05-GHS09	H314-411	0
140-31-8	GHS05-GHS07	H312-314-317-412	0
TRADE SECRET	GHS06	H331	0
100-41-4	GHS02-GHS07	H225-332	0
14808-60-7	GHS08	H350-372	0
122-99-6	GHS07	H302-319	0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

#### 4. First-aid Measures

#### 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**AFTER INGESTION**: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Causes burns. May be harmful if swallowed. Corrosive after repeated contact with skin and mucous membranes. This product contains silica which is classified by IARC as a known human carcinogen (Group 1). Crystalline silica is known to cause silicosis.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required.

When symptoms persist or in all cases of doubt seek medical advice.

## 5. Fire-fighting Measures

## 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Vapors may spread long distances and ignite.

#### 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Evacuate personnel to safe areas. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers.

#### 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## 7. Handling and Storage

#### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING**: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection.

**PROTECTION AND HYGIENE MEASURES**: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Heat, flames and sparks.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

#### 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

Name	<u>%</u>	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	OEL Note
NONYL PHENOL	25-50	N/E	N/E	N/E	N/E	
TITANIUM DIOXIDE	10-25	10 MGM3	N/E	10 MGM3	N/E	
LIMESTONE	10-25	N/E	N/E	5 MGM3	N/E	
POLYOXYPROPYLENEDIAMINE	10-25	N/E	N/E	N/E	N/E	
AMINOETHYLPIPERAZINE	2.5-10	N/E	N/E	N/E	N/E	
POLYAMIDE WAX	0.1-1.0	N/E	N/E	N/E	N/E	
ETHYL BENZENE	0.1-1.0	20 PPM	N/E	435 MGM3	N/E	
MICROCRYSTALLINE SILICA	0.1-1.0	0.025 MG/M3 (respirable)	N/E	0.1 MG/M3	N/E	
2-PHENOXYETHANOL	<0.1	25.0 PPM SKI	NN/E	N/E	N/E	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

#### 8.2 Exposure controls

#### **Personal Protection**

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

**EYE PROTECTION:** Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. Lightweight protective clothing

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Use only in an area equipped with explosion proof exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Viscous Liquid, Various Colors

Physical State Liquid
Odor Mild
Odor threshold N/D
pH N/D
Melting point / freezing point (°C) N/D

**Boiling point/range (°C)** 176 F (80 C) - 500 F (260 C)

Flash Point, (°C) 93

Evaporation rate Slower Than Ether
Flammability (solid, gas) Not determined

Upper/lower flammability or explosive 0.8 - 17.4

limits

Vapour Pressure, mmHg N/D

Vapour density Heavier than Air
Relative density Not determined

Solubility in / Miscibility with water Negligible

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not Determined

Viscosity

Not Determined

Explosive properties

Not determined

Oxidising properties

Not determined

#### 9.2 Other information

VOC Content g/l:

9

Specific Gravity (g/cm3) 1.4

## 10. Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Heat, flames and sparks.

#### 10.5 Incompatible materials

Strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

## 11. Toxicological Information

#### 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: N/D Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
25154-52-3	NONYL PHENOL	1620 mg/kg oral		Not Available
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available
1317-65-3	LIMESTONE	6450 mg/kg, oral, rat	Not Available	Not Available
9046-10-0	POLYOXYPROPYLENEDIAMINE	480 mg/kg, oral, rat	1550 mg/kg, dermal,	Not Available

140-31-8 **AMINOETHYLPIPERAZINE** 2140 mg/kg, oral, rat Not Available TRADE >2000 MG/KG, ORAL, POLYAMIDE WAX >5MG/M3 INH, RAT SECRET RAT >5000 mg/l, dermal 100-41-4 ETHYL BENZENE 3500 mg/kg rat, oral 17.2 mg/L lnh, Rat, 4Hr rabbit 14808-60-7 MICROCRYSTALLINE SILICA 22500 mg/kg Not Available Not Available

122-99-6 2-PHENOXYETHANOL 1400 mg/kg, oral, rat

#### Additional Information:

Causes burns. May be harmful if swallowed. Corrosive after repeated contact with skin and mucous membranes. This product contains silica which is classified by IARC as a known human carcinogen (Group 1). Crystalline silica is known to cause silicosis.

## 12. Ecological Information

#### 12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

Unknown

Unknown

Unknown

Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

**12.4 Mobility in soil:** Unknown

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

**12.6 Other adverse effects:** Unknown

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
25154-52-3	NONYL PHENOL	No information	No information	No information
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
1317-65-3	LIMESTONE	No information	No information	No information
9046-10-0	POLYOXYPROPYLENEDIAMINE	No information	No information	No information
140-31-8	AMINOETHYLPIPERAZINE	No information	No information	No information
TRADE SECRET	POLYAMIDE WAX	No information	No information	No information
100-41-4	ETHYL BENZENE	1.8 mg/l (Daphnia Magna)	4.6 mg/l (Green Algae)	4.2 mg/l (Rainbow Trout)
14808-60-7	MICROCRYSTALLINE SILICA	No information	No information	No information
122-99-6	2-PHENOXYETHANOL	No information	No information	No information

## 13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

**UN number** UN 3066 14.2 UN proper shipping name Paint Technical name N/A 8 14.3 Transport hazard class(es) N/A Subsidiary shipping hazard 14.4 Packing group 14.5 Environmental hazards Unknown 14.6 Special precautions for user Unknown EmS-No.: F-A, S-B 14.7 Transport in bulk according to Annex II Unknown of MARPOL 73/78 and the IBC code

## 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

## U.S. Federal Regulations: As follows -

### **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.ETHYL BENZENE100-41-4

#### **Toxic Substances Control Act:**

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u> CAS-No.

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

#### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

No NJ Right-To-Know components exist in this product.

#### Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

#### California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

 Chemical Name
 CAS-No.

 TITANIUM DIOXIDE
 13463-67-7

 ETHYL BENZENE
 100-41-4

 MICROCRYSTALLINE SILICA
 14808-60-7

 CUMENE
 98-82-8

 BENZENE
 71-43-2

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

 Chemical Name
 CAS-No.

 TOLUENE
 108-88-3

 BENZENE
 71-43-2

## International Regulations: As follows -

#### \* Canadian DSL:

No Information

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16. Other Information

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Reasons for revision

No Information

No Information