Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 1512S1NL

Revision Date: 02/16/2026

Product Name: FLEXXIDE ELASTOMER

Supercedes Date: 12/06/2022

1.2 Relevant identified uses of the substance or mixture and uses advised against Monocomponent industrial coating - Industrial use.

1.3 Details of the supplier of the safety data sheet

Manufacturer:

Carboline Global Inc.
2150 Schuetz Road
St. Louis, MO USA 63146

Regulatory / Technical Information:
Contact Carboline Technical Services at
1-800-848-4645

Datasheet Produced by: Brombach, Jennifer - regulatory@carboline.com

1.4 Emergency telephone number:

CHEMTREC 1-800-424-9300 (Inside US)
CHEMTREC +1 703 5273887 (Outside US)
HEALTH - Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 3
Carcinogenicity, category 2
Eye Irritation, category 2
Skin Irritation, category 2
Skin Sensitizer, category 1
STOT, repeated exposure, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word

Warning

Named Chemicals on Label

STODDARD SOLVENT, ATTAPULGITE, TITANIUM DIOXIDE, 3-IODO-2-PROPYNYL CARBAMATE, DIATOMACEOUS EARTH, AMORPHOUS

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

Unknown

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

Name According to EEC	EINEC No.	CAS-No.	%	Classifications	
TITANIUM DIOXIDE	236-675-5	13463-67-7	10 - <30	H351	
STODDARD SOLVENT	232-489-3	8052-41-3	5.0 - <10	H226-304-372	Asp. Tox. 1, Flam. Liq. 3, STOT RE 1
DIATOMACEOUS EARTH, AMORPHOUS	272-489-0	68855-54-9	5.0 - <10	H373	

ATTAPULGITE	601-805-5	12174-11-7	1.0 - <5.0	H351	Carc. 2
3-IODO-2-PROPYNYL CARBAMATE	259-627-5	55406-53-6	1.0 - <5.0	H312-317-318-331-372-400-410	Acute Tox. 3 Inhalation, Acute Tox. 4 Dermal, Aquatic Acute 1, Aquatic Chronic 1, Eye Dam. 1, Skin Sens. 1, STOT RE 1
ALKYL AMINE	203-542-8	108-01-0	1.0 - <5.0	H226-302-312-314-331	

CAS-No. **M-Factors**

13463-67-7
8052-41-3
68855-54-9
12174-11-7
55406-53-6
108-01-0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.
AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.
AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.
When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Evacuate personnel to safe areas. The product is not flammable. Use NIOSH approved respiratory protection.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Remove all sources of

ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Avoid breathing vapors, mist or gas. Wash thoroughly after handling.
PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks. Do not freeze.
STORAGE CONDITIONS: Do not freeze. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits
(US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
TITANIUM DIOXIDE	13463-67-7	10 MGM3 10 MGM3	N/E	N/E
STODDARD SOLVENT	8052-41-3	100 ppm	N/E	N/E
DIATOMACEOUS EARTH, AMORPHOUS	68855-54-9	10.0 mg/m3	N/E	N/E
ATTAPULGITE	12174-11-7	10.00 MG/M3	N/E	N/E
3-IODO-2-PROPYNYL CARBAMATE	55406-53-6	N/E	N/E	N/E
ALKYL AMINE	108-01-0	5.0 PPM	N/E	N/E

Name	CAS-No.	OSHA PEL	OSHA STEL
TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E
STODDARD SOLVENT	8052-41-3	525 MGM3, 100 PPM	N/E
DIATOMACEOUS EARTH, AMORPHOUS	68855-54-9	15.0 mg/m3	N/E
ATTAPULGITE	12174-11-7	15.00 MG/M3	N/E

3-IODO-2-PROPYNYL CARBAMATE	55406-53-6	N/E	N/E
ALKYL AMINE	108-01-0	5.0 PPM	N/E

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

BODY PROTECTION: Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Visocus Liquid, Various Colors
Physical State	Liquid
Odor	Slight
Odor threshold	N/D
pH	8.25 - 9.5
Melting point / freezing point (°C)	32F (0C)
Boiling point/range (°C)	212 F (100 C) - 471 F (244 C)
Flash Point (°C)	Non Flammable
Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	1.0 - 17.4
Vapour Pressure, mmHg	N/D
Vapour density	Heavier than Air
Relative density	Not determined
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Unknown
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	96
Specific Gravity (g/cm3)	app. 1.4

10. Stability and Reactivity

10.1 Reactivity
No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability
Stable under normal conditions.

10.3 Possibility of hazardous reactions
Hazardous polymerisation does not occur.

10.4 Conditions to avoid
Heat, flames and sparks. Do not freeze.

10.5 Incompatible materials
Strong oxidizing agents.

10.6 Hazardous decomposition products
Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50:	N/D
Inhalation LC50:	N/D
Irritation:	Skin Irritation and Eye Irritation, category 2
Corrosivity:	Unknown
Sensitization:	Unknown
Repeated dose toxicity:	Unknown
Carcinogenicity:	Carcinogenicity, category 2
Mutagenicity:	Unknown
Toxicity for reproduction:	Unknown
STOT-single exposure:	Unknown
STOT-repeated exposure:	Unknown
Aspiration hazard:	Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
13463-67-7	TITANIUM DIOXIDE	25000 mg/ m3, oral (rat)		Not Available	0.000	0.000
8052-41-3	STODDARD SOLVENT	6001 mg/kg, oral, rat	Not Available	5500 mg/m3, 4h, inhalation	0.000	0.000
55406-53-6	3-IODO-2-PROPYNYL CARBAMATE	Not Available		Not Available	0.000	0.000
108-01-0	ALKYL AMINE	1183 mg/kg, oral, rat	1219 mg/kg, dermal, rabbit	5.1 mg/l / 4h, rat, inh	0.000	0.000

Additional Information:

The classification(s) is/are relevant when exposed to these respirable substances in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): Unknown

IC50 72hr (Algae): Unknown

LC50 96hr (fish): Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB assessment: Unknown

12.6 Other adverse effects: Unknown

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
8052-41-3	STODDARD SOLVENT	No information	No information	No information
68855-54-9	DIATOMACEOUS EARTH, AMORPHOUS	No information	No information	No information
12174-11-7	ATTAPULGITE	No information	No information	No information
55406-53-6	3-IODO-2-PROPYNYL CARBAMATE	No information	No information	No information
108-01-0	ALKYL AMINE	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1	UN number	None
14.2	UN proper shipping name	Not Regulated
	Technical name	N/A
14.3	Transport hazard class(es)	None
	Subsidiary shipping hazard	N/A
14.4	Packing group	N/A
14.5	Environmental hazards	Unknown
14.6	Special precautions for user	Unknown
	EmS-No.:	N/A
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown
	Additional Notes:	No Information

15. Regulatory Information

15.1 **Safety, health and environmental regulations/legislation for the substance or mixture:**

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

CERCLA - Sara Hazard Category

Carcinogenicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

3-IODO-2-PROPYNYL CARBAMATE	55406-53-6	1.5

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
ACRYLIC POLYMER	TRADE SECRET
WATER	7732-18-5
NEPHELINE SYENITE	37244-96-5
PROPYLENE GLYCOL	57-55-6

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
ACRYLIC POLYMER	TRADE SECRET
WATER	7732-18-5
NEPHELINE SYENITE	37244-96-5
PROPYLENE GLYCOL	57-55-6
ESTER ALCOHOL	25265-77-4
CALCINED KAOLIN	92704-41-1

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.