



## Safety Data Sheet

Prepared in Accordance with HCS 29  
C.F.R. 1910.1200

### 1. Identification of the Substance/Mixture and the Company/Undertaking

- 1.1 Product Identifier** 189SS1NL
- Product Name:** DRIQUIK 91 ENAMEL **Revision Date:** 09/19/2018
- 1.2 Relevant identified uses of the substance or mixture and uses advised against** RESTRICTED DISTRIBUTION. **Supersedes Date:** New SDS  
Monocomponent industrial coating - Industrial use.
- 1.3 Details of the supplier of the safety data sheet**
- Manufacturer:** Carboline Company  
2150 Schuetz Road  
St. Louis, MO USA 63146
- Regulatory / Technical Information:  
Contact Carboline Technical Services at  
1-800-848-4645
- Datasheet Produced by:** Schlereth, Ken - ehs@stoncor.com
- 1.4 Emergency telephone number:** CHEMTREC 1-800-424-9300 (Inside US)  
CHEMTREC +1 703 5273887 (Outside US)  
HEALTH - Pittsburgh Poison Control 1-412-681-6669

### 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Allergic effects  
Carcinogenicity, category 1A  
Flammable Liquid, category 2  
Germ Cell Mutagenicity, category 1A

**2.2 Label elements****Symbol(s) of Product****Signal Word**

danger

**Named Chemicals on Label****HAZARD STATEMENTS**

Allergic effects	EUH208	Contains METHYL ETHYL KETOXIME. May produce an allergic reaction.
Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Germ Cell Mutagenicity, category 1A	H340-1A	May cause genetic defects.
Carcinogenicity, category 1A	H350-1A	May cause cancer.

**PRECAUTION PHRASES**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P235	Keep cool.
P284	Wear respiratory protection.
P308+313	IF exposed or concerned: Get medical advice/attention
P403+233	Store in a well-ventilated place. Keep container tightly closed.

**2.3 Other hazards**

No Information

**Results of PBT and vPvB assessment:**

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**3. Composition/Information On Ingredients****3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
64742-89-8	HIGH FLASH NAPHTHA	10-25
8032-32-4	VMP NAPHTHA	10-25
8052-41-3	STODDARD SOLVENT	10-25
1333-86-4	CARBON BLACK	1.0-2.5
13463-67-7	TITANIUM DIOXIDE	1.0-2.5
25013-15-4	VINYL TOLUENE	0.1-1.0
121-44-8	TRIETHYLAMINE	0.1-1.0
142-82-5	n-HEPTANE	<0.1

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
64742-89-8	GHS08	H304-340-350	0
8032-32-4	GHS08	H304-340-350	0
8052-41-3	GHS02-GHS08	H226-304	0
1333-86-4			0
13463-67-7			0

25013-15-4	GHS02-GHS07-GHS08-GHS09	H226-304-315-319-332-335-411	0
121-44-8	GHS02-GHS05-GHS06	H225-302-312-314-331	0
142-82-5	GHS02-GHS07-GHS08-GHS09	H225-304-315-336-400-410	0

**Additional Information:** The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

### 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

## 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

### 5.2 Special hazards arising from the substance or mixture

No Information

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Heat, flames and sparks.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
HIGH FLASH NAPHTHA	64742-89-8	300 PPM	N/E	N/E
VMP NAPHTHA	8032-32-4	300 PPM	N/E	N/E
STODDARD SOLVENT	8052-41-3	100 PPM 100 PPM	N/E	N/E
CARBON BLACK	1333-86-4	3 MGM3	N/E	N/E
TITANIUM DIOXIDE	13463-67-7	10 MGM3 10 MGM3	N/E	N/E
VINYL TOLUENE	25013-15-4	50 PPM	100 PPM	N/E
TRIETHYLAMINE	121-44-8	0.5 PPM	1 PPM	N/E
n-HEPTANE	142-82-5	400 PPM 400 PPM	500 PPM 500 PPM	N/E

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
HIGH FLASH NAPHTHA	64742-89-8	500 PPM	N/E
VMP NAPHTHA	8032-32-4	1350 MGM3, 300 PPM	1800 MGM3, 400 PPM
STODDARD SOLVENT	8052-41-3	525 MGM3, 100 PPM	N/E
CARBON BLACK	1333-86-4	3.5 MG/M3	N/E
TITANIUM DIOXIDE	13463-67-7	15.0 MG/M3	N/E
VINYL TOLUENE	25013-15-4	480 MGM3, 100 PPM	N/E

TRIETHYLAMINE	121-44-8	40 MGM3, 10 PPM	60 MGM3, 15 PPM
n-HEPTANE	142-82-5	1600 MGM3, 400 PPM	2000 MGM3, 500 PPM

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

## 8.2 Exposure controls

### Personal Protection

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	Viscous Liquid, Various
<b>Physical State</b>	Liquid
<b>Odor</b>	Aliphatic
<b>Odor threshold</b>	Not Determined
<b>pH</b>	Not Determined
<b>Melting point / freezing point (°C)</b>	Not Determined
<b>Boiling point/range</b>	97 F (36 C) - 424 F (218 C)
<b>Flash Point</b>	50F (10C)
<b>Evaporation rate</b>	Slower Than Ether
<b>Flammability (solid, gas)</b>	N/D
<b>Upper/lower flammability or explosive limits</b>	0.9 - 17.4
<b>Vapour Pressure, mmHg</b>	Not Determined
<b>Vapour density</b>	Heavier than Air
<b>Relative density</b>	N/D
<b>Solubility in / Miscibility with water</b>	Not Determined
<b>Partition coefficient: n-octanol/water</b>	N/D
<b>Auto-ignition temperature (°C)</b>	N/D
<b>Decomposition temperature (°C)</b>	N/D
<b>Viscosity</b>	Not Determined

**Explosive properties** N/D

**Oxidising properties** N/D

## 9.2 Other information

**VOC Content g/l:** 503

**Specific Gravity (g/cm<sup>3</sup>)** Unknown

## 10. Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

Strong oxidizing agents.

### 10.6 Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## 11. Toxicological Information

### 11.1 Information on toxicological effects

#### Acute Toxicity:

**Oral LD50:** N/D

**Inhalation LC50:** N/D

**Irritation:** No information available.

**Corrosivity:** No information available.

**Sensitization:** No information available.

**Repeated dose toxicity:** No information available.

**Carcinogenicity:** No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
64742-89-8	HIGH FLASH NAPHTHA	Not Available		Not Available	0.000	0.000
8032-32-4	VMP NAPHTHA	NOT AVAILABLE		NOT AVAILABLE	0.000	0.000
8052-41-3	STODDARD SOLVENT	6001 mg/kg, oral, rat	Not Available	5500 mg/m3, 4h, inhalation	0.000	0.000
1333-86-4	CARBON BLACK	8000 mg/kg oral, rat	Not Available	Not Available		
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available	0.000	0.000
25013-15-4	VINYL TOLUENE	3275 mg/kg, oral, rat	4400 mg/kg, dermal, rabbit	16.891 mg/l / 4h, Inh, Rat	0.000	0.000
121-44-8	TRIETHYLAMINE	460 mg/kg, oral, rat		6 gm/m3, mouse, inh	0.000	0.000

**Additional Information:**

No Information

## 12. Ecological Information

**12.1 Toxicity:**

**EC50 48hr (Daphnia):** No information available.

**IC50 72hr (Algae):** No information available.

**LC50 96hr (fish):** No information available.

**12.2 Persistence and degradability:**

No information available.

**12.3 Bioaccumulative potential:**

No information available.

**12.4 Mobility in soil:**

No information available.

**12.5 Results of PBT and vPvB assessment:**

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**12.6 Other adverse effects:**

No information available.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
64742-89-8	HIGH FLASH NAPHTHA	No information	No information	No information
8032-32-4	VMP NAPHTHA	No information	No information	No information
8052-41-3	STODDARD SOLVENT	No information	No information	No information
1333-86-4	CARBON BLACK	No information	No information	No information
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
25013-15-4	VINYL TOLUENE	1,3 mg/l (Daphnia magna)	2.6 mg/l (green algae)	5.2 mh/l (fathead minnow)
121-44-8	TRIETHYLAMINE	No information	No information	No information
142-82-5	n-HEPTANE	No information	No information	No information

## 13. Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

14.1 UN number	UN1263
14.2 UN proper shipping name	Paint
Technical name	Unknown
14.3 Transport hazard class(es)	3
Subsidiary shipping hazard	N/A
14.4 Packing group	II
14.5 Environmental hazards	No information available.
14.6 Special precautions for user	No information available.
EMs-No.:	F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No information available.

## 15. Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

### U.S. Federal Regulations: As follows -

#### CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Germ cell mutagenicity

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
TRIETHYLAMINE	121-44-8

#### Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
NONANE	111-84-2
n-HEPTANE	142-82-5

### U.S. State Regulations: As follows -

#### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
No Chemical Name Found	TRADE SECRET
TALC	14807-96-6



**Pennsylvania Right-To-Know**

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
No Chemical Name Found	TRADE SECRET
TALC	14807-96-6
ADDITIVE	TRADE SECRET

**CALIFORNIA PROPOSITION 65**

WARNING: Cancer and Reproductive Harm -- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**International Regulations: As follows -****\* Canadian DSL:**

All chemical ingredients included on inventory (DSL)

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**16. Other Information****Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

**Reasons for revision**

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.