

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 269DA1NL Revision Date: 03/04/2025

Supercedes Date:

New SDS

Product Name: Steri-Seal HC Part A

Component of

1.2 Relevant identified uses of the substance or mixture and uses

advised against

multicomponent industrial coatings - Industrial use.

1.3 Details of the supplier of the safety data sheet

Manufacturer: Dudick, a Division of Carboline

2150 Schuetz road St. Louis, Mo. 63146

Regulatory / Technical Information:

330-562-1970

Datasheet Produced by: Schlereth, Ken - regulatory@carboline.com

1.4 Emergency telephone number: CHEM-TEL (US Transportation): (800) 255-3924

CHEM-TEL (International Transportation): +01-813-248-0585

HEALTH: Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
Hazardous to the aquatic environment, Chronic, category 2
Carcinogenicity, category 2
Eye Irritation, category 2
Flammable Liquid, category 2
Germ Cell Mutagenicity, category 2
Skin Irritation, category 2
Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

METHYL ISOBUTYL KETONE, CRESYLGLYCIDYLETHER, ACRYLATE MONOMER, BISPHENOL A EPOXY RESIN, EPOXY PHENOL NOVOLAC RESIN

HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Germ Cell Mutagenicity, category 2	H341	Suspected of causing genetic defects.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Hazardous to the aquatic environment,	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

Name According to EEC BISPHENOL A EPOXY RESIN	EINEC No. 500-033-5	<u>CAS-No.</u> 25068-38-6	<u>%</u> 25 - <50	Classifications H315-317-319-411	Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1
EPOXY PHENOL NOVOLAC RESIN	608-164-0	28064-14-4	25 - <50	H315-317-319-411	
METHYL ISOBUTYL KETONE	203-550-1	108-10-1	10 - <25	H225-302-312-319-332-336-351	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Carc. 2, Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE
CRESYLGLYCIDYLET HER	218-645-3	2210-79-9	10 - <25	H315-317-341-411	Aquatic Chronic 2, Muta. 2, Skin Irrit. 2, Skin Sens. 1
ACRYLATE MONOMER	239-701-3	15625-89-5	2.5 - <10	H315-317-319-351-400-410	Aquatic Acute 1, Aquatic Chronic 1, Carc. 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1

<u>CAS-No.</u> <u>M-Factors</u>

25068-38-6 28064-14-4 108-10-1 2210-79-9 15625-89-5

Remarks: CAS No. 25068-38-6 identified as CAS No. 1675-54-3, EC No. 216-823-5 under REACH Registration

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness. Toxic to aquatic organisms.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
BISPHENOL A EPOXY RESIN	25068-38-6	N/E	N/E	N/E
EPOXY PHENOL NOVOLAC RESIN	28064-14-4	N/E	N/E	N/E
METHYL ISOBUTYL KETONE	108-10-1	20 PPM	75 PPM	N/E
CRESYLGLYCIDYLETHER	2210-79-9	N/E	N/E	N/E
ACRYLATE MONOMER	15625-89-5	N/E	N/E	N/E

<u>Name</u>	CAS-No.	OSHA PEL C	OSHA STEL
BISPHENOL A EPOXY RESIN	25068-38-6	N/E	N/E
EPOXY PHENOL NOVOLAC RESIN	28064-14-4	N/E	N/E
METHYL ISOBUTYL KETONE	108-10-1	205 MGM3, 50 PPM 3	300 MGM3, 75 PPM
CRESYLGLYCIDYLETHER	2210-79-9	N/E	N/E
ACRYLATE MONOMER	15625-89-5	N/E	N/E

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

BODY PROTECTION: Lightweight protective clothing OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

0.1	Information on	hagia physical	and shamical	proportion

Appearance: Viscous Liquid

Physical State Liquid
Odor Epoxy

 Odor threshold
 Not Determined

 pH
 Not Determined

 Melting point / freezing point (°C)
 Not Determined

Boiling point/range (°C) 201 F (94 C) - 500 F (260 C)

Flash Point (°C) 57F (14C)

Evaporation rate Slower Than Ether
Flammability (solid, gas) Not Determined

Upper/lower flammability or explosive 2.0 - 8.0

limits

Vapour Pressure, mmHg

Vapour density

Relative density

Not Determined

Not Determined

Not Determined

Not Determined

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not Determined

Decomposition temperature (°C)

Not Determined

Viscosity

Not Determined

Explosive properties

Not Determined

Oxidising properties

Not Determined

9.2 Other information

VOC Content g/l: 90

Specific Gravity (g/cm3) app. 1.34

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

STOT-single exposure: Unknown

STOT-repeated exposure: Unknown

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25068-38-6	BISPHENOL A EPOXY RESIN	11400 mg/kg, rat, oral	23000 mg/kg, dermal, rabbit	No Information	No Information	No Information
28064-14-4	EPOXY PHENOL NOVOLAC RESIN	>5000 mg/kg. oral, rat	>2000 mg/kg, rabbit	Not Available	0.000	0.000
108-10-1	METHYL ISOBUTYL KETONE	2000 mg/kg, oral, rat	2000 mg/kg, dermal, rat	5000 ppm/ 1 hr, Inh, rat	0.000	0.000
2210-79-9	CRESYLGLYCIDYLETHER	5800 mg/kg, oral, rat		1220 ppm/4 hr	0.000	0.000
15625-89-5	ACRYLATE MONOMER	5000 mg/kg, oral, rat	5170 mg/kg, dermal, rabbit	Not Available	0.000	0.000

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information available.

No information available.

No information available.

12.2 Persistence and degradability:No information available.

12.3 Bioaccumulative potential: No information available.

12.4 Mobility in soil:No information available.

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information available.

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
25068-38-6	BISPHENOL A EPOXY RESIN	2.1 mg/l (daphnia)	11 mg/l (algae)	1.3 mg/l (fish)
28064-14-4	EPOXY PHENOL NOVOLAC RESIN	No information	No information	No information
108-10-1	METHYL ISOBUTYL KETONE	200 mg/l (Daphnia magna)	No information	179 mg/l (Zebra fish)
2210-79-9	CRESYLGLYCIDYLETHER	No information	No information	No information
15625-89-5	ACRYLATE MONOMER	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN3082

14.2 UN proper shipping name Environmentally Hazardous Substance, Liquid, NOS

Technical name Epoxy Resin

14.3 Transport hazard class(es) 9

Subsidiary shipping hazard No Information

14.4 Packing group

14.5 Environmental hazards No information available.14.6 Special precautions for user No information available.

EmS-No.: Unknown

14.7 Transport in bulk according to Annex II No information available. of MARPOL 73/78 and the IBC code

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

CERCLA - Sara Hazard Category

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Germ cell mutagenicity

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u> <u>CAS-No.</u> <u>%</u>

METHYL ISOBUTYL KETONE 108-10-1 10

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

NON HAZARDOUS ADDITIVES TRADE SECRET

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> <u>CAS-No.</u>

NON HAZARDOUS ADDITIVES TRADE SECRET

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour.

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.