

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

substance or advised agair	ntified uses of the mixture and uses	SCRATCH-COAT 800 PART A Component of multicomponent industrial coatings - Industrial use.	Supercedes Date:	12/06/2022		
substance or advised agair1.3 Details of the	mixture and uses	multicomponent industrial				
Manufacture	.3 Details of the supplier of the safety data sheet					
	er :	Dudick, a Division of Carboline 2150 Schuetz road St. Louis, Mo. 63146				
		Regulatory / Technical Information: 330-562-1970				
Datasheet P	roduced by:	Schlereth, Ken - regulatory@carboline.com				
1.4 Emergency t	telephone number:	CHEM-TEL (US Transportation): (800) 255-39 CHEM-TEL (International Transportation): +0 HEALTH: Pittsburgh Poison Control 1-412-68	1-813-248-0585			

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 3 Eye Irritation, category 2 Flammable Liquid, category 3 Reproductive Toxicity, category 2 Skin Irritation, category 2 STOT, repeated exposure, category 1 STOT, single exposure, category 3, RTI

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label STYRENE

HAZARD STATEMENTS

Flammable Liquid, category 3 Skin Irritation, category 2 Eye Irritation, category 2 Acute Toxicity, Inhalation, category 4 STOT, single exposure, category 3, RTI Reproductive Toxicity, category 2 STOT, repeated exposure, category 1 Hazardous to the aquatic environment, Chronic, category 3 PRECAUTION PHRASES	H226 H315 H319 H332 H335 H361 H372 H412	Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
THEORO HONT HINGEO		
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a
	D005 . 051 . 000	position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so.
	D000-010	Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention
	P314	Get medical advice/attention if you feel unwell.
	P332+313 P403+233	If skin irritation occurs: Get medical advice/attention.
	г 4 00т200	Store in a well-ventilated place. Keep container tightly closed.
	P501	Dispose of contents/container to waste treatment/disposal
		facility in accordance with local, state, and federal
		regulations.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 **Mixtures**

Hazardous incredients

Name According to EEC STYRENE	<u>EINEC No.</u> 202-851-5	<u>CAS-No.</u> 100-42-5	<u>%</u> 25 - <50	<u>Classifications</u> H226-304-315-319-332-335-361 -372-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Repr. 2, Skin Irrit. 2, STOT RE 1, STOT SE 3 RTI
CAS-No.	<u>M-Fac</u>	tors			

100-42-5

M-Factors

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

First-aid Measures

Description of First Aid Measures 4.1

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

Extinguishing Media: 5.1

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture No Information

Advice for firefighters 5.3

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

Accidental Release Measures

Personal precautions, protective equipment and emergency procedures 6.1

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For

personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Inhibitor levels should be maintained. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

<u>Name</u> STYRENE	<u>CAS-No.</u> 100-42-5	ACGIH TWA 10 PPM	ACGIH STEL 20 PPM	<u>ACGIH Ceiling</u> N/E
Name	CAS-No.	<u>OSHA PE</u>	<u>IL OSHA ST</u>	<u>rel</u>
STYRENE	100-42-5	215 MGM3,	50 PPM 425 MGM PPM	•

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. F	9. Physical and Chemical Properties				
9.1	Information on basic physical and chemical properties				
	Appearance:	Clear, Viscous Liquid			
	Physical State	Liquid			
	Odor	Aromatic			
	Odor threshold	Not Determined			
	pH	Not Determined			
	Melting point / freezing point (°C)	Not Determined			
	Boiling point/range (°C)	277 F (136 C) - 400 F (204 C)			
	Flash Point (°C)	90°F (32°C)			
	Evaporation rate	Slower Than Ether			
	Flammability (solid, gas)	N/D			
	Upper/lower flammability or explosive limits	0.9 - 7.1			
	Vapour Pressure, mmHg	Not Determined			
	Vapour density	Heavier than Air			
	Relative density	N/D			
	Solubility in / Miscibility with water	Not Determined			
	Partition coefficient: n-octanol/water	N/D			
	Auto-ignition temperature (°C)	N/D			
	Decomposition temperature (°C)	N/D			
	Viscosity	Not Determined			
	Explosive properties	N/D			
	Oxidising properties	N/D			
9.2	Other information				
	VOC Content g/l:	87			
	Specific Gravity (g/cm3)	1.05			

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Hazardous polymerisation may occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxico	11. Toxicological Information					
11.1 Informat	Information on toxicological effects					
Acute Te	oxicity:					
Oral L	.D50:	N/D				
Inhala	tion LC50:	N/D				
Irritation	Irritation: Eye Irritation, category 2; Skin Irritation, category 2					
Corrosiv	/ity:	Unknown				
Sensitiza	ation:	Unknown				
Repeate	ed dose toxicity:	Unknown				
Carcino	genicity:	Unknown				
Mutager	nicity:	Unknown				
Toxicity	for reproduction:	Unknown				
STOT-si	ingle exposure:	STOT, single exposure, category 3, RTI				
STOT-re	epeated exposure:	STOT, repeated exposure, category 1				
Aspiratio	on hazard:	Unknown				

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
100-42-5	STYRENE	2650 mg/kg, oral, rat	>2000 mg/kg, dermal, rat	2800 ppm / 4hr, inh, rat	0.000	0.000

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

	EC50 48hr (Daphnia): IC50 72hr (Algae): LC50 96hr (fish):	No information available. No information available. No information available.
12.2	Persistence and degradability:	No information available.
12.3	Bioaccumulative potential:	No information available.
12.4	Mobility in soil:	No information available.

12.5 Results of PBT and vPvB assessment:		The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.			
12.6 Other adverse effects:		No information available.			
CAS-No.	Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>	
100-42-5	STYRENE	4.7 mg/l (daphnia)	4.9 mg/l (Green Algae)	4 - 10 mg/l (fathead minnow)	

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14.	Transport Information	
14.1	UN number	UN1866
14.2	UN proper shipping name	Resin Solution
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	PGIII
14.5	Environmental hazards	No information available.
14.6	Special precautions for user	No information available.
	EmS-No.:	F-E,S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No information available.

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.	<u>%</u>
STYRENE	100-42-5	45.5
COBALT 2-ETHOXYLHEXANOATE	136-52-7	0.21

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
No Chemical Name Found HYDROPHOBIC SILICA	TRADE SECRET 67762-90-7
	67762-90-7

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	<u>CAS-No.</u>
No Chemical Name Found	TRADE SECRET
CALIFORNIA PROPOSITION 65	

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

This product contains one or several components listed in the Canadian NDSL list.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 H304 H315 H319 H332 H335 H361 H372	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
H372 H412	Causes damage to organs through prolonged or repeated exposure.
H41Z	Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Product: 300DA1NL

Date Printed: 09/20/2024