

**Safety Data Sheet**

**Prepared in Accordance with HCS 29
C.F.R. 1910.1200**

1. Identification of the Substance/Mixture and the Company/Undertaking

- 1.1 Product Identifier** 307DA1NL **Revision Date:** 09/20/2024
Product Name: PROTECTO-COAT 900 PART A **Supersedes Date:** 12/06/2022
- 1.2 Relevant identified uses of the substance or mixture and uses advised against** Component of multicomponent industrial coatings - Industrial use.
- 1.3 Details of the supplier of the safety data sheet**
- Manufacturer :** Dudick, a Division of Carboline
2150 Schuetz road
St. Louis, Mo. 63146

Regulatory / Technical Information:
330-562-1970
- Datasheet Produced by:** Schlereth, Ken - regulatory@carboline.com
- 1.4 Emergency telephone number:** CHEM-TEL (US Transportation): (800) 255-3924
CHEM-TEL (International Transportation): +01-813-248-0585
HEALTH: Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification**2.1 Classification of the substance or mixture**

Acute Toxicity, Inhalation, category 4
Hazardous to the aquatic environment, Chronic, category 3
Carcinogenicity, category 1A
Eye Irritation, category 2
Flammable Liquid, category 3
Reproductive Toxicity, category 2
Skin Irritation, category 2
STOT, repeated exposure, category 1
STOT, single exposure, category 3, RTI

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

STYRENE, MICA, MICROCRYSTALLINE SILICA

HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to waste treatment/disposal facility in accordance with local, state, and federal regulations.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
STYRENE	202-851-5	100-42-5	25 - <50	H226-304-315-319-332-335-361-372-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Repr. 2, Skin Irrit. 2, STOT RE 1, STOT SE 3 RTI
MICA	310-127-6	12001-26-2	10 - <25	H319-335	Eye Irrit. 2, STOT SE 3 RTI
TITANIUM DIOXIDE	236-675-5	13463-67-7	2.5 - <10		
MICROCRYSTALLINE SILICA	238-878-4	14808-60-7	0.1 - <1.0	H350-372	Carc. 1A, STOT RE 1

CAS-No.

100-42-5
12001-26-2
13463-67-7
14808-60-7

M-Factors

Remarks: CAS No 13463-67-7: Note 10

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Vapours may spread long distances and ignite.

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Evacuate personnel to

safe areas. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Inhibitor levels should be maintained. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
STYRENE	100-42-5	10 PPM	20 PPM	N/E
MICA	12001-26-2	3 MGM3	N/E	N/E
TITANIUM DIOXIDE	13463-67-7	10 mg/m3	N/E	N/E
MICROCRYSTALLINE SILICA	14808-60-7	0.025 MGM3	N/E	N/E

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
STYRENE	100-42-5	215 MGM3, 50 PPM	425 MGM3, 100 PPM
MICA	12001-26-2	20. MPPCF	N/E

TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E
MICROCRYSTALLINE SILICA	14808-60-7	0.05 MGM3	N/E

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Use only in an area equipped with explosion proof exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Grey, Viscous Liquid
Physical State	Liquid
Odor	Aromatic
Odor threshold	Not Determined
pH	Not Determined
Melting point / freezing point (°C)	Not Determined
Boiling point/range (°C)	277 F (136 C) - 500 F (260 C)
Flash Point (°C)	90°F (32°C)
Evaporation rate	Slower Than Ether
Flammability (solid, gas)	N/D
Upper/lower flammability or explosive limits	0.9 - 8.1
Vapour Pressure, mmHg	Not Determined
Vapour density	Heavier than Air
Relative density	N/D
Solubility in / Miscibility with water	Not Determined
Partition coefficient: n-octanol/water	N/D
Auto-ignition temperature (°C)	N/D
Decomposition temperature (°C)	N/D
Viscosity	Not Determined
Explosive properties	N/D
Oxidising properties	N/D

9.2 Other information

VOC Content g/l:	73
Specific Gravity (g/cm3)	1.28

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Eye Irritation, category 2A; Skin Irritation, category 2

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Carcinogenicity, category 1A

Mutagenicity: Unknown

Toxicity for reproduction: Reproductive Toxicity, category 2

STOT-single exposure: Unknown

STOT-repeated exposure: STOT, repeated exposure, category 1

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
100-42-5	STYRENE	2650 mg/kg, oral, rat	>2000 mg/kg, dermal, rat	2800 ppm / 4hr, inh, rat	0.000	0.000
12001-26-2	MICA	No Information	No Information	No Information	No Information	No Information
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	No Information	No Information	No Information	No Information
14808-60-7	MICROCRYSTALLINE SILICA	22500 mg/kg	No Information	No Information	No Information	No Information

Additional Information:

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above the minimum exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): No information available.

IC50 72hr (Algae): No information available.

LC50 96hr (fish): No information available.

12.2 Persistence and degradability:

No information available.

12.3 Bioaccumulative potential:

No information available.

12.4 Mobility in soil:

No information available.

12.5 Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

12.6 Other adverse effects:

No information available.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
100-42-5	STYRENE	4.7 mg/l (daphnia)	4.9 mg/l (Green Algae)	4 - 10 mg/l (fathead minnow)
12001-26-2	MICA	No information	No information	No information
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
14808-60-7	MICROCRYSTALLINE SILICA	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1	UN number	UN1866
14.2	UN proper shipping name	Resin Solution
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	PGIII
14.5	Environmental hazards	No information available.
14.6	Special precautions for user	No information available.
	EmS-No.:	F-E,S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No information available.

15. Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>%</u>
STYRENE	100-42-5	25.85
COBALT 2-ETHOXYLHEXANOATE	136-52-7	0.04

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
No Chemical Name Found	TRADE SECRET
HYDROPHOBIC SILICA	67762-90-7

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
No Chemical Name Found	TRADE SECRET

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -*** Canadian DSL:**

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.