Semstone® Scrim Cloth

PRODUCT DATA SHEET

SELECTION & SPECIFICATION DATA

Description	Scrim Cloth is a woven, Type “E”, borosilicate glass fiber reinforcing fabric, specially designed for Semstone Systems. The glass filament fibers are bundled and woven at right angles to each other, which affords bidirectional strength. When Scrim Cloth is incorporated in a Semstone Epoxy, Novolac or Vinyl Ester coating/lining system, impact resistance, tensile strength and fatigue resistance of the system is increased.
Typical Uses	Scrim Cloth is typically used in such areas as concrete sumps, trenches and below grade concrete structures that require a reinforced coating/lining system.

APPLICATION PROCEDURES

General	If Scrim Cloth does absorb moisture or becomes saturated with water, discard it. Do not use. The use of wet Scrim Cloth in any Semstone Reinforced System will inhibit cure and reduce the corrosion resistance of the system.

PACKAGING, HANDLING & STORAGE

Packaging	Scrim Cloth is available in full rolls and custom cut lengths. A large roll is 58” wide and approximately 450’ long. It contains approximately 2,175 square feet and weighs approximately 280 lbs. net. Smaller rolls of 58” wide and 50’ long are also available.
Storage	Scrim Cloth must be stored in a cool, dry area. Precautions should be taken to insure that the material remains moisture free prior to and during application.

WARRANTY

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Carboline to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Carboline warrants our products to be free of manufacturing defects in accord with applicable Carboline quality control procedures. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT: (1) APPLIED IN ACCORDANCE WITH CARBOLINE’S SPECIFICATIONS, AND/OR (2) PROPERLY STORED, CURED, AND USED UNDER NORMAL OPERATING CONDITIONS. Carboline assumes no responsibility for coverage, performance, injuries, or damages resulting from use of the product. If this product is found not to perform as specified upon inspection by a Carboline representative during the warranty period, Carboline’s sole obligation, if any, is to replace the Carboline product(s) proven to be defective or refund the purchase price thereof, at Carboline’s sole option. Carboline shall not be liable for any other losses or damages. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY CARBOLINE, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. All of the trademarks referenced above are the property of Carboline International Corporation unless otherwise indicated. The whole text of this Product Data Sheet, as well as the documents derived from it, have been written in English, and for legal purposes the English version shall prevail.