

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

Product Identifier 390DB1NL 08/11/2025 **Revision Date:**

Supercedes Date:

New SDS

POLYMER STEEL SG **Product Name:**

CERAMIC PART B

Relevant identified uses of the

substance or mixture and uses

advised against

Component of

multicomponent industrial coatings - Industrial use.

Details of the supplier of the safety data sheet 1.3

> Dudick, a Division of Carboline Manufacturer:

> > 2150 Schuetz road St. Louis, Mo. 63146

Regulatory / Technical Information:

330-562-1970

Schlereth, Ken - regulatory@carboline.com **Datasheet Produced by:**

CHEMTREC 1-800-424-9300 (Inside US) 1.4 Emergency telephone number:

CHEMTREC +1 703 5273887 (Outside US)

HEALTH - Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 1 Hazardous to the aquatic environment, Chronic, category 2 $Reproductive_Toxic \dot{i} ty F_category_1B$ Skin Corrosion, category 1 Skin Sensitizer, category 1 STOT, single exposure, category 3, RTI

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

4,4'-ISOPROPYLIDENEDIPHENOL, DIETHYLENETRIAMINE, HYDROXY MODIFIED RESIN

HAZARD STATEMENTS

Acute Toxicity, Dermal, category 4	H312	Harmful in contact with skin.
Skin Corrosion, category 1	H314-1	Causes severe skin burns and eye damage.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 1	H330-1	Fatal if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Reproductive_ToxicityF_category_1B	H360F	May damage fertility.
Hazardous to the aquatic environment,	H411	Toxic to aquatic life with long lasting effects.
Chronic category 2		

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P352	Wash with plenty of soap and water.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly
	-1

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

closed.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous	ingrediente
i lazai uous	ingredients

Name According to EEC DIETHYLENETRIAMIN E	EINEC No. 203-865-4	<u>CAS-No.</u> 111-40-0	<u>%</u> 30 - <60	<u>Classifications</u> H302-312-314-317-330-335	Acute Tox. 1 Inhalation, Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Skin Corr. 1, Skin Sens. 1, STOT SE 3 RTI
4,4'- ISOPROPYLIDENEDIP HENOL	201-245-8	80-05-7	10 - <30	H317-318-335-360F-400-410	Aquatic Acute 1, Aquatic Chronic 1, Eye Dam. 1, Repr. 1B, Skin Sens. 1, STOT SE 3 RTI
HYDROXY MODIFIED RESIN	270-604-9	68457-74-9	10 - <30	H315-317-412	Aquatic Chronic 3, Skin Irrit. 2, Skin Sens. 1
ISOPROPANOL	200-661-7	67-63-0	1.0 - <5.0	H225-319-336	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE
CARBON BLACK	215-609-9	1333-86-4	0.1 - <1.0		

CAS-No.

M-Factors

111-40-0 80-05-7 68457-74-9 67-63-0 1333-86-4

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Causes burns. May be harmful if swallowed. Corrosive after repeated contact with skin and mucous membranes.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Evacuate personnel to safe areas. The product is not flammable. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Avoid breathing vapors, mist or gas. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
DIETHYLENETRIAMINE	111-40-0	1 PPM	N/E	N/E
4,4'-ISOPROPYLIDENEDIPHENOL	80-05-7	N/E	N/E	N/E
HYDROXY MODIFIED RESIN	68457-74-9	N/E	N/E	N/E
ISOPROPANOL	67-63-0	200 PPM	400 PPM	N/E
CARBON BLACK	1333-86-4	3 MGM3	N/E	N/E

<u>Name</u>	CAS-No.	OSHA PEL	OSHA STEL
DIETHYLENETRIAMINE	111-40-0	4 MGM3, 1 PPM	N/E
4,4'-ISOPROPYLIDENEDIPHENOL	80-05-7	N/E	N/E
HYDROXY MODIFIED RESIN	68457-74-9	N/E	N/E
ISOPROPANOL	67-63-0	980 MGM3, 400 PPM	1225 MGM3, 500 PPM
CARBON BLACK	1333-86-4	3.5 MGM3	N/E

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

BODY PROTECTION: Lightweight protective clothing OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas

9. Physical and Chemical Properties

9.1	Information on	basic phy	vsical and	chemical	properties

Appearance: Viscous Black Liquid

Physical State Liquid
Odor Irritating

Odor threshold

PH

Not Determined

Melting point / freezing point (°C)

Not Determined

Boiling point/range (°C) 176 F (80 C) - 404 F (207 C)

Flash Point (°C) 230F (110C)

Evaporation rate Slower Than Ether
Flammability (solid, gas) Not Determined

Upper/lower flammability or explosive 0.9 - 12.0

limits

Vapour Pressure, mmHg

Vapour density

Heavier than Air

Relative density

Not Determined

Solubility in / Miscibility with water

Not Determined

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not Determined

9.2 Other information

VOC Content g/l:

Specific Gravity (g/cm3) 1,96

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

STOT-single exposure: Unknown

STOT-repeated exposure: Unknown

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
111-40-0	DIETHYLENETRIAMINE	1080 mg/kg, oral, rat	1045 mg/kg, dermal, rabbit	No Information	No Information	No Information
80-05-7	4,4'- ISOPROPYLIDENEDIPHENOL	11400 mg/kg, oral, rat	No Information	No Information	No Information	No Information
68457-74-9	HYDROXY MODIFIED RESIN	Not Available	Not Available	Not Available	0.000	0.000
67-63-0	ISOPROPANOL	4720 mg/kg rat, oral	12800 mg/kg, dermal, rabbit	22500 ppm/8hrs rat, inhalation	0.000	0.000
1333-86-4	CARBON BLACK	8000 mg/kg oral, rat	No Information	No Information	No Information	No Information

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information available.

No information available.

No information available.

12.2 Persistence and degradability: No information available.

12.3 Bioaccumulative potential:No information available.

12.4 Mobility in soil:No information available.

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information available.

CAS-No.	<u>Chemical Name</u>	EC50 48hr	IC50 72hr	LC50 96hr
111-40-0	DIETHYLENETRIAMINE	32 mg/l (Daphnia)	1164 mg/l (Algae)	430 mg/l (Fish)
80-05-7	4,4'-ISOPROPYLIDENEDIPHENOL	No information	No information	No information
68457-74-9	HYDROXY MODIFIED RESIN	No information	No information	No information
67-63-0	ISOPROPANOL	13299 mg/l (Daphnia Magna)	>1000 m/gL (desmodesmus subspicatus)	9640 mg/L (pimphales promelas)
1333-86-4	CARBON BLACK	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1	UN number	UN2079

14.2 UN proper shipping name Diethylenetriamone Solution

Technical name No Information

14.3 Transport hazard class(es) 8

Subsidiary shipping hazard No Information

14.4 Packing group

14.5 Environmental hazards No information available.14.6 Special precautions for user No information available.

EmS-No.: Unknown

14.7 Transport in bulk according to Annex II
Of MARPOL 73/78 and the IBC code

No information available.

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

CERCLA - Sara Hazard Category

Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

4,4'-ISOPROPYLIDENEDIPHENOL

80-05-7

14.88

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> CAS-No.

MODIFIED ALIPHATIC AMINE 68610-56-0

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> <u>CAS-No.</u>

MODIFIED ALIPHATIC AMINE 68610-56-0

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

This product contains one or several components listed in the Canadian NDSL list.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H330 Fatal if inhaled. H335 May cause respiratory irritation. May cause drowsiness or dizziness. H336 H360F May damage fertility. H400 Very toxic to aquatic life. H410

H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.