



## Safety Data Sheet

Prepared in Accordance with HCS 29  
C.F.R. 1910.1200

### 1. Identification of the Substance/Mixture and the Company/Undertaking

<b>1.1 Product Identifier</b>	8845A1NL		
<b>Product Name:</b>	CARBOTHANE 8845 PART A	<b>Revision Date:</b>	06/03/2020
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>	Component of multicomponent industrial coatings - Industrial use.	<b>Supersedes Date:</b>	06/09/2015
<b>1.3 Details of the supplier of the safety data sheet</b>			
<b>Manufacturer:</b>	Carboline Company 2150 Schuetz Road St. Louis, MO USA 63146		
	Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
<b>Datasheet Produced by:</b>	Schlereth, Ken - ehs@stoncor.com		
<b>1.4 Emergency telephone number:</b>	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-681-6669		

### 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Allergic effects  
Flammable Liquid, category 2

#### 2.2 Label elements

##### Symbol(s) of Product



##### Signal Word

Danger

##### Named Chemicals on Label

#### HAZARD STATEMENTS

Allergic effects  
Flammable Liquid, category 2

EUH208  
H225

Contains ORGANIC TIN. May produce an allergic reaction.  
Highly flammable liquid and vapour.

**PRECAUTION PHRASES**

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P235	Keep cool.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

**2.3 Other hazards**

No Information

**Results of PBT and vPvB assessment:**

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**3. Composition/Information On Ingredients****3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
13463-67-7	TITANIUM DIOXIDE	25 - <50
123-86-4	N-BUTYL ACETATE	2.5 - <10
78-93-3	METHYL ETHYL KETONE	2.5 - <10
540-88-5	TERT-BUTYL ACETATE	2.5 - <10
PROPRIETARY	ALIPHATIC DIOL	1.0 - <2.5
763-69-9	ETHOXYPROPIONATE	1.0 - <2.5
12239-87-1	C.I. PIGMENT BLUE 15:2	1.0 - <2.5
1333-86-4	CARBON BLACK	1.0 - <2.5
100-41-4	ETHYL BENZENE	0.1 - <1.0
77-58-7	ORGANIC TIN	0.1 - <1.0

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
13463-67-7			0
123-86-4	GHS02-GHS07	H226-336	0
78-93-3	GHS02-GHS07	H225-319-336	0
540-88-5	GHS02-GHS07	H225-332-335-336	0
PROPRIETARY	GHS07	H315-319	0
763-69-9	GHS02	H226	0
12239-87-1			0
1333-86-4			0
100-41-4	GHS02-GHS07-GHS08	H225-304-315-319-332-351-373-412	0
77-58-7	GHS05-GHS07-GHS08-GHS09	H314-317-341-360-370-400	1

Remarks: CASstatement

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

**4. First-aid Measures****4.1 Description of First Aid Measures**

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

**4.3 Indication of any immediate medical attention and special treatment needed**

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

## 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

### 5.2 Special hazards arising from the substance or mixture

No Information

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Heat, flames and sparks.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
TITANIUM DIOXIDE	13463-67-7	10 mg/m <sup>3</sup>	N/E	N/E
N-BUTYL ACETATE	123-86-4	50 PPM	150 PPM	N/E
METHYL ETHYL KETONE	78-93-3	200 PPM	300 PPM	N/E
TERT-BUTYL ACETATE	540-88-5	50 PPM	150 PPM	N/E
ALIPHATIC DIOL	PROPRIETARY	25 PPM	50 PPM	N/E
ETHOXYPROPIONATE	763-69-9	N/E	N/E	N/E
C.I. PIGMENT BLUE 15:2	12239-87-1	N/E	N/E	N/E
CARBON BLACK	1333-86-4	3 MGM3	N/E	N/E
ETHYL BENZENE	100-41-4	20 PPM	125 ppm	
ORGANIC TIN	77-58-7	N/E	N/E	N/E

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E
N-BUTYL ACETATE	123-86-4	710 MGM3, 150 PPM	950 MGM3, 200 PPM
METHYL ETHYL KETONE	78-93-3	590 MGM3, 200 PPM	885 MGM3, 300 PPM
TERT-BUTYL ACETATE	540-88-5	950 MGM3, 200 PPM	N/E
ALIPHATIC DIOL	PROPRIETARY	N/E	N/E
ETHOXYPROPIONATE	763-69-9	N/E	N/E
C.I. PIGMENT BLUE 15:2	12239-87-1	N/E	N/E
CARBON BLACK	1333-86-4	3.5 MGM3	N/E
ETHYL BENZENE	100-41-4	435 MGM3, 100 PPM	545 MGM3, 125 PPM
ORGANIC TIN	77-58-7	0.10 mg/m <sup>3</sup>	N/E

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

**EYE PROTECTION:** Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location.

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	Viscous Liquid, Various Colors
<b>Physical State</b>	Liquid
<b>Odor</b>	Solvent
<b>Odor threshold</b>	N/D
<b>pH</b>	N/D
<b>Melting point / freezing point (°C)</b>	N/D
<b>Boiling point/range</b>	149 F (65 C) - 595 F (313 C)
<b>Flash Point</b>	63F 17C)
<b>Evaporation rate</b>	Slower Than Ether
<b>Flammability (solid, gas)</b>	Not determined
<b>Upper/lower flammability or explosive limits</b>	0.6 - 36.0
<b>Vapour Pressure, mmHg</b>	N/D
<b>Vapour density</b>	Heavier than Air
<b>Relative density</b>	Not determined
<b>Solubility in / Miscibility with water</b>	N/D
<b>Partition coefficient: n-octanol/water</b>	Not determined
<b>Auto-ignition temperature (°C)</b>	Not determined
<b>Decomposition temperature (°C)</b>	Not determined
<b>Viscosity</b>	Unknown
<b>Explosive properties</b>	Not determined
<b>Oxidising properties</b>	Not determined

### 9.2 Other information

<b>VOC Content g/l:</b>	228
<b>Specific Gravity (g/cm<sup>3</sup>)</b>	app. 1.47

## 10. Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

Strong oxidizing agents.

**10.6 Hazardous decomposition products**Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.**11. Toxicological Information****11.1 Information on toxicological effects****Acute Toxicity:**

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

STOT-single exposure: Unknown

STOT-repeated exposure: Unknown

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available	No Information	No Information
123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4h, Inh. rat		
78-93-3	METHYL ETHYL KETONE	2194 mg/kg rat, oral	Not Available	34.5 mg/L/ 4 hour rat, inhalation	0.000	0.000
540-88-5	TERT-BUTYL ACETATE	3160 mg/kg, oral, rat	Not Available	4000 ppm/6 hours, rat inhalation	0.000	0.000
PROPRIETARY	ALIPHATIC DIOL	Not Available		Not Available	0.000	0.000
763-69-9	ETHOXYPROPIONATE	5000 mg/kg, oral, rat	4080 mg/kg, dermal, rat	Not Available	0.000	0.000
1333-86-4	CARBON BLACK	8000 mg/kg oral, rat	Not Available	Not Available		
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	0.000	0.000
77-58-7	ORGANIC TIN	2071 mg/kg, oral, rat	Not Available	Not Available	0.000	0.000

**Additional Information:**

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

## 12. Ecological Information

<b>12.1 Toxicity:</b>	
EC50 48hr (Daphnia):	Unknown
IC50 72hr (Algae):	Unknown
LC50 96hr (fish):	Unknown
<b>12.2 Persistence and degradability:</b>	Unknown
<b>12.3 Bioaccumulative potential:</b>	Unknown
<b>12.4 Mobility in soil:</b>	Unknown
<b>12.5 Results of PBT and vPvB assessment:</b>	The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.
<b>12.6 Other adverse effects:</b>	Unknown

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
123-86-4	N-BUTYL ACETATE	44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)
78-93-3	METHYL ETHYL KETONE	308 mg/l (Daphnia magna)	No information	2993 mg/l (Pimephales promelas)
540-88-5	TERT-BUTYL ACETATE	No information	No information	No information
PROPRIETARY	ALIPHATIC DIOL	No information	No information	No information
763-69-9	ETHOXYPROPIONATE	785 mg/l (daphnia magna)	115 mg/l (algae)	67.65 mg/l (fathead minnow)
12239-87-1	C.I. PIGMENT BLUE 15:2	No information	No information	No information
1333-86-4	CARBON BLACK	No information	No information	No information
100-41-4	ETHYL BENZENE	1.8 mg/l (Daphnia Magna)	4.6 mg/l (Green Algae)	4.2 mg/l (Rainbow Trout)
77-58-7	ORGANIC TIN	No information	No information	No information

## 13. Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

14.1 UN number	UN1263
14.2 UN proper shipping name	Paint
Technical name	N/A
14.3 Transport hazard class(es)	3
Subsidiary shipping hazard	N/A
14.4 Packing group	II
14.5 Environmental hazards	Unknown
14.6 Special precautions for user	Unknown
EmS-No.:	F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

## 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

### U.S. Federal Regulations: As follows -

#### CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids)

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
ETHYL BENZENE	100-41-4

#### Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
----------------------	----------------

No TSCA 12(b) components exist in this product.

### U.S. State Regulations: As follows -

#### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
BARIUM SULFATE	7727-43-7
ACRYLIC COPOLYMER	TRADE SECRET
AZO PIGMENT	82199-12-0

#### Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
BARIUM SULFATE	7727-43-7
ACRYLIC COPOLYMER	TRADE SECRET
AZO PIGMENT	82199-12-0
ACRYLIC POLYOL	TRADE SECRET
CASTOR OIL	8001-79-4
COLOR PIGMENT	5567-15-7



COLOR PIGMENT

15793-73-4

**CALIFORNIA PROPOSITION 65**

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

**International Regulations: As follows -****\* Canadian DSL:**

All chemical ingredients included on inventory (DSL)

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**16. Other Information****Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

**Reasons for revision**

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.