



Safety Data Sheet
prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

- 1.1 Product Identifier** F138A1NL
- Product Name:** CARBOSEAL 745 PART A **Revision Date:** 02/21/2018
- 1.2 Relevant identified uses of the substance or mixture and uses advised against** **Supersedes Date:** New SDS
- Component of multicomponent industrial coatings - Industrial use.
- 1.3 Details of the supplier of the safety data sheet**
- Manufacturer:** Carboline Company
2150 Schuetz Road
St. Louis, MO USA 63146
- Regulatory / Technical Information:
Contact Carboline Technical Services at
1-800-848-4645
- Datasheet Produced by:** Schlereth, Ken - ehs@stoncor.com
- 1.4 Emergency telephone number:** CHEMTREC 1-800-424-9300 (Inside US)
CHEMTREC +1 703 5273887 (Outside US)
HEALTH - Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2
 Eye Irritation, category 2
 STOT, single exposure, category 3, RT1
 Skin Irritation, category 2
 Skin Sensitizer, category 1

2.2 Label elements**Symbol(s) of Product****Signal Word**

warning

Named Chemicals on Label

EPOXY RESIN, ALKYL GLYCIDYL ETHER

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P332+313	If skin irritation occurs: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

Unknown

3. Composition/Information On Ingredients**3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
25068-38-6	EPOXY RESIN	50-75
13463-67-7	TITANIUM DIOXIDE	10-25
68609-97-2	ALKYL GLYCIDYL ETHER	2.5-10
1333-86-4	CARBON BLACK	0.1-1.0

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
25068-38-6	GHS07-GHS09	H315-317-319-335-411	0
13463-67-7			0
68609-97-2	GHS07	H315-317-335	0
1333-86-4	GHS07-GHS08	H319-335-351-372	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Vapors may spread long distances and ignite.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Evacuate personnel to safe areas. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and

contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>%</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>	<u>OEL Note</u>
EPOXY RESIN	50-75	N/E	N/E	N/E	N/E	
TITANIUM DIOXIDE	10-25	10 MGM3	N/E	10 MGM3	N/E	
ALKYL GLYCIDYL ETHER	2.5-10	N/E	N/E	N/E	N/E	
CARBON BLACK	0.1-1.0	3.0 MG/M3	N/E	3.5 MG/M3	N/E	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. Lightweight protective clothing

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Use only in an area equipped with explosion proof exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Viscous Grey Liquid
Physical State	Liquid
Odor	Epoxy
Odor threshold	N/D
pH	N/D
Melting point / freezing point (°C)	N/D

Boiling point/range (°C)	300 F (149 C) - 500 F (260 C)
Flash Point, (°C)	107
Evaporation rate	Slower Than Butyl Acetate
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	1.3 - 7.0
Vapour Pressure, mmHg	N/D
Vapour density	Heavier than Air
Relative density	Not determined
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Unknown
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	0
Specific Gravity (g/cm³)	1.5

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
25068-38-6	EPOXY RESIN	11400 mg/kg, rat, oral	23000 mg/kg, dermal, rabbit	>20 mL/kg skin, sensitizer
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available
68609-97-2	ALKYL GLYCIDYL ETHER	17100 mg/kg, oral, rat		Not Available
1333-86-4	CARBON BLACK	8000 mg/kg oral, rat	Not Available	Not Available

Additional Information:

This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This product may contain Carbon Black, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. The classification(s) is/are relevant when exposed to these respirable substances in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): Unknown

IC50 72hr (Algae): Unknown

LC50 96hr (fish): Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB assessment: Unknown

12.6 Other adverse effects: Unknown

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
25068-38-6	EPOXY RESIN	2.1 mg/l (daphnia)	11 mg/l (algae)	1.3 mg/l (fish)
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
68609-97-2	ALKYL GLYCIDYL ETHER	7.2 mg/L (Daphna)	844 mg/l (Algae)	1.8 g/L (Fish)
1333-86-4	CARBON BLACK	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number	N/A
14.2 UN proper shipping name	Not Regulated
Technical name	N/A
14.3 Transport hazard class(es)	N/A
Subsidiary shipping hazard	N/A
14.4 Packing group	N/A
14.5 Environmental hazards	No Information
14.6 Special precautions for user	Unknown
EmS-No.:	N/A
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -**New Jersey Right-to-Know:**


The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
NEPHELINE SYENITE	37244-96-5
Silicone Additive	TRADE SECRET

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
NEPHELINE SYENITE	37244-96-5

California Proposition 65:
 **Warning**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
TITANIUM DIOXIDE	13463-67-7
CARBON BLACK	1333-86-4

 **Warning**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -*** Canadian DSL:**

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

