

SELECTION & SPECIFICATION DATA

Generic Type	A woven, continuous filament, strand fiberglass mesh ("E" Glass)
Description	FP-Fiberglass Mesh is a high strength fiberglass reinforcing mesh designed for use with Thermo-Lag® intumescent fireproofing products.
Typical Uses	FP-Fiberglass Mesh is used as a reinforcing mesh for Thermo-Lag® intumescent fireproofing products (for specific designs) when applied to structural steel beams and columns which are subjected to ASTM-E119/UL 263 or UL 1709 fire environments. *The product should be applied in accordance with the appropriate design.
Color	Off White

APPLICATION PROCEDURES

General	FP-Fiberglass Mesh is installed into the wet Thermo-Lag® intumescent material. Contact Carboline Technical Service for specific design details. *The product should be applied in accordance with the appropriate design.
----------------	--

TESTING / CERTIFICATION / LISTING

General	Underwriter's Laboratories, Inc. (UL) Intertek Laboratories, Inc. Lloyd's Register of Shipping (LRS) Det Norske Veritas (DNV) American Bureau of Shipping (ABS) Southwest Research Institute (SWRI) FM Global
----------------	---

PACKAGING, HANDLING & STORAGE

Packaging	475 ft ² (44.12 m ²) roll
Shelf Life	N/A (Not affected by environmental changes) *Shelf Life: (actual stated shelf life) when kept at recommended storage conditions and in original unopened containers.
Storage	Store indoors in a dry environment.
Standard Length	150' (45.7 m)
Standard Width	38" (0.96 m)

FP-Fiberglass Mesh

PRODUCT DATA SHEET



WARRANTY

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Carboline Company to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Carboline quality control. We assume no responsibility for coverage, performance, injuries or damages resulting from use. Carbolines sole obligation, if any, is to replace or refund the purchase price of the Carboline product(s) proven to be defective, at Carbolines option. Carboline shall not be liable for any loss or damage. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY CARBOLINE, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. All of the trademarks referenced above are the property of Carboline International Corporation unless otherwise indicated.