



Safety Data Sheet

Prepared in Accordance with HPR
(SOR/2015-17)

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	R335S1NL	Revision Date:	12/05/2022
Product Name:	SP-100 EQUIPMENT WASH	Supersedes Date:	01/29/2021
1.2 Relevant identified uses of the substance or mixture and uses advised against	Monocomponent industrial coating - Industrial use.		
1.3 Details of the supplier of the safety data sheet	<p>Manufacturer : Specialty Polymer Coatings Division Carboline Global Inc. 2150 Schuetz Road St. Louis, Mo. 63146</p> <p>Regulatory / Technical Information: 604-514-9711</p> <p>Datasheet Produced by: Schlereth, Ken - regulatory@carboline.com</p>		
1.4 Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-681-6669		

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
 Carcinogenicity, category 2
 Eye Irritation, category 2
 Flammable Liquid, category 2
 Reproductive Toxicity, category 1A
 STOT, single exposure, category 3, NE
 Skin Irritation, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

METHYL ETHYL KETONE, ORTHO-XYLENE, ETHYL BENZENE, PARA-XYLENE, PROPYLENE GLYCOL MONOMETHYL ETHER, META-XYLENE, ETHYL ACETATE

HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Reproductive Toxicity, category 1A	H360-1A	May damage fertility or the unborn child.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+313	If skin irritation occurs: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>
------------------------------	------------------	----------------	----------	------------------------

PROPYLENE GLYCOL MONOMETHYL ETHER	203-539-1	107-98-2	25 - <50	H226-319-332-336	Acute Tox. 4 Inhalation, Eye Irrit. 2, Flam. Liq. 3, STOT SE 3 NE
META-XYLENE	203-576-3	108-38-3	10 - <25	H312-315-332	
METHYL ETHYL KETONE	201-159-0	78-93-3	10 - <25	H225-319-336	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE
PARA-XYLENE	203-396-5	106-42-3	2.5 - <10	H304-312-315-332-335-371	
ETHYL BENZENE	202-849-4	100-41-4	2.5 - <10	H225-304-315-319-332-351-373-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2
ORTHO-XYLENE	202-422-2	95-47-6	2.5 - <10	H312-315-332	
ETHYL ACETATE	205-500-4	141-78-6	2.5 - <10	H225-319-336	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE
2-METHOXY-1- PROPANOL	216-455-5	1589-47-5	0.1 - <1.0	H226-315-318-335-360	Eye Dam. 1, Flam. Liq. 3, Repr. 1A, Skin Irrit. 2, STOT SE 3 RTI
TOLUENE	203-625-9	108-88-3	0.1 - <1.0	H225-304-315-319-332-335-336-361-370-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 1, STOT SE 3 NE, STOT SE 3 RTI

<u>CAS-No.</u>	<u>M-Factors</u>
107-98-2	0
108-38-3	0
78-93-3	0
106-42-3	0
100-41-4	0
95-47-6	0
141-78-6	0
1589-47-5	0
108-88-3	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if

available, can be found in section 11.
When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	50 PPM	100 PPM	N/E
META-XYLENE	108-38-3	100 PPM	150 PPM	N/E
METHYL ETHYL KETONE	78-93-3	200 PPM	300 PPM	N/E
PARA-XYLENE	106-42-3	100 PPM	150 PPM	N/E
ETHYL BENZENE	100-41-4	20 PPM	125 ppm	
ORTHO-XYLENE	95-47-6	100 PPM	150 PPM	N/E
ETHYL ACETATE	141-78-6	400 PPM	N/E	N/E
2-METHOXY-1-PROPANOL	1589-47-5	N/E	N/E	N/E
TOLUENE	108-88-3	20 PPM	N/E	N/E

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	360 MGM3, 100 PPM	540 MGM3, 150 PPM
META-XYLENE	108-38-3	100.00 PPM	N/E
METHYL ETHYL KETONE	78-93-3	590 MGM3, 200 PPM	885 MGM3, 300 PPM
PARA-XYLENE	106-42-3	100.00 PPM	N/E
ETHYL BENZENE	100-41-4	435 MGM3, 100 PPM	645 MGM3, 125 PPM
ORTHO-XYLENE	95-47-6	100.00 PPM	N/E
ETHYL ACETATE	141-78-6	1400 MGM3, 400 PPM	N/E
2-METHOXY-1-PROPANOL	1589-47-5	N/E	N/E
TOLUENE	108-88-3	200 ppm	560 MGM3, 150 PPM

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight

protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Liquid, Clear
Physical State	Liquid
Odor	Solvent
Odor threshold	Not Determined
pH	Not Determined
Melting point / freezing point (°C)	Unknown
Boiling point/range (°C)	Unknown - 277 F (136 C)
Flash Point (°C)	54°F (12°C)
Evaporation rate	Slower Than Ether
Flammability (solid, gas)	N/D
Upper/lower flammability or explosive limits	1.0 - 10.9
Vapour Pressure, mmHg	Not Determined
Vapour density	Heavier than Air
Relative density	N/D
Solubility in / Miscibility with water	Not Determined
Partition coefficient: n-octanol/water	N/D
Auto-ignition temperature (°C)	N/D
Decomposition temperature (°C)	N/D
Viscosity	Not Determined
Explosive properties	N/D
Oxidising properties	N/D

9.2 Other information

VOC Content g/l:	878.4
Specific Gravity (g/cm³)	0.88

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition productsCarbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.**11. Toxicological Information****11.1 Information on toxicological effects****Acute Toxicity:**

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Skin Irritation, category 2; Eye Irritation, category 2**Corrosivity:** Unknown**Sensitization:** Unknown**Repeated dose toxicity:** Unknown**Carcinogenicity:** Carcinogenicity, category 2**Mutagenicity:** Unknown**Toxicity for reproduction:** Reproductive Toxicity, category 1A**STOT-single exposure:** STOT, single exposure, category 2**STOT-repeated exposure:** STOT, repeated exposure, category 2**Aspiration hazard:** Acute toxicity, Inhalation, category 4

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	4016 mg/kg, oral, rat	13536 mg/kg, dermal, rabbit	10000 ppm/4hrs rat, inhalation	0.000	0.000
108-38-3	META-XYLENE	Not Available	Not Available	Not Available	0.000	0.000
78-93-3	METHYL ETHYL KETONE	2194 mg/kg rat, oral	Not Available	34.5 mg/L/ 4 hour rat, inhalation	0.000	0.000
106-42-3	PARA-XYLENE	Not Available	Not Available	Not Available	0.000	0.000
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	0.000	0.000
95-47-6	ORTHO-XYLENE	Not Available	Not Available	Not Available	0.000	0.000
141-78-6	ETHYL ACETATE	5600 mg/kg oral, rat	Not Available	56000 mg/ l/4h. (rat)	0.000	0.000
1589-47-5	2-METHOXY-1-PROPANOL	5710 mg/kg, oral, rat	5660 mg/kg, dermal, rabbit	1600 ppm / 4h, inh, rat	0.000	0.000

108-88-3	TOLUENE	5000 mg/kg rat oral	12267 mg/kg, dermal, rabbit	8000 ppm/4 hrs, rat, inhalation	0.000	0.000
----------	---------	------------------------	--------------------------------	---------------------------------------	-------	-------

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information available.
IC50 72hr (Algae):	No information available.
LC50 96hr (fish):	No information available.

12.2 Persistence and degradability: No information available.

12.3 Bioaccumulative potential: No information available.

12.4 Mobility in soil: No information available.

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information available.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	23300 mg/l (Water flea)	No information	20800 mg/l (Fish)
108-38-3	META-XYLENE	No information	No information	No information
78-93-3	METHYL ETHYL KETONE	308 mg/l (Daphnia magna)	No information	2993 mg/l (Pimephales promelas)
106-42-3	PARA-XYLENE	No information	No information	No information
100-41-4	ETHYL BENZENE	1.8 mg/l (Daphnia Magna)	4.6 mg/l (Green Algae)	4.2 mg/l (Rainbow Trout)
95-47-6	ORTHO-XYLENE	No information	No information	No information
141-78-6	ETHYL ACETATE	No information	No information	No information
1589-47-5	2-METHOXY-1-PROPANOL	19000 mg/l (Daphnia magna)	No Information	4998 mg/l (Fish)
108-88-3	TOLUENE	6 mg/l (Daphnia magna)	12.5 mg/L (Algae)	5.8 mg/L (Fish)

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1	UN number	UN1993
14.2	UN proper shipping name	Flammable liquid, n.o.s.
	Technical name	(Methyl Ethyl Ketone)
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	II
14.5	Environmental hazards	No information available.
14.6	Special precautions for user	No information available.
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No information available.

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:	No information available.
Danish MAL Code:	No information available.
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	No information available.
Norway Product Registration Number:	No information available.
WGK Class:	Not available

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>%</u>
META-XYLENE	108-38-3	22.586
PARA-XYLENE	106-42-3	9.82
ETHYL BENZENE	100-41-4	9.329
ORTHO-XYLENE	95-47-6	7.1195
TOLUENE	108-88-3	0.24059
BENZENE	71-43-2	0.00491

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

International Regulations: As follows -*** Canadian DSL:**

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H361	Suspected of damaging fertility or the unborn child.
H370	Causes damage to organs.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.