

# Sanitile® 555 VOC



**Sanitile 555 VOC is a high performance, unmodified water-based epoxy with outstanding toughness and durability.**

**PRODUCT DETAILS** Sanitile 555 VOC is a water-based epoxy finish that has wide versatility as both a wall finish or a floor coating. It has an attractive high gloss appearance and very good chemical resistance. Sanitile 555 VOC has minimal odor and is less than 100 g/l VOC. It exhibits significant improvements in film hardness and toughness over straight acrylic or acrylic-epoxy modified coatings and is more chemically resistant and physically durable. It is therefore ideal for more aggressive exposures for walls and structural components than acrylic-modified epoxies. It may also be used for light to moderate duty floors

## APPLICATIONS

DAIRIES  
MEAT AND FISH PROCESSING AREAS  
BAKERIES  
KITCHENS  
WET AND DRY HANDLING AREAS  
COMMERCIAL KITCHENS  
PHARMACEUTICAL FACILITIES  
HOSPITALS  
OPERATING ROOMS  
CLEANROOMS

## FEATURES

- › High gloss, easy to clean finish
- › Wide versatility for walls and floors
- › Very good chemical resistance
- › Tough, durable film
- › Outstanding adhesion
- › Withstands steam cleaning
- › Flexible and impact resistant
- › Low odor and low VOC
- › Available in custom colors through Rapid Tint Service

# Sanitile<sup>®</sup> 555 VOC

## Quality Product Backed by Quality Service

- › Carboline Company has been solving tough corrosion and fireproofing problems since 1947
- › Industrial service centers and sales offices located around the world
- › Over 20 worldwide manufacturing locations with a global network of sales and technical support
- › Industry leading field service and technical engineering support team
- › Certified to ISO 9001

### Sanitile 555 VOC

FEATURE	ADVANTAGE	BENEFIT
Unmodified epoxy formulation	More durable and chemical resistant than acrylics or acrylic-modified epoxies	Longer service life and holds up to repeated chemical cleanings
High solids	VOC of less than 100 g/l	Compliant with very restrictive local, state and Federal regulations
Durable formulation	Withstands impact and abrasion resistance	Single-product use for walls and floors
Fast dry properties	Light foot traffic in three hours	Fast return to service



**Carboline Company**  
Global Headquarters  
2150 Schuetz Road  
St. Louis, MO 63146 USA  
PH: +1-314-644-1000  
[www.carboline.com](http://www.carboline.com)