



# Material Safety Data Sheet

**CHEMTREC Transportation  
Emergency Phone: 800-424-9300**

**Pittsburgh Poison Control  
Center  
Health Emergency No.: 412-681-6669**

•NOTE: The CHEMTREC Transportation  
•Emergency Phone is to be used only in the  
•event of chemical emergencies involving a  
•spill, leak, fire, exposure or accident  
•involving chemicals

## Section 1 - Chemical Product / Company Information

**Product Name:** POLYCLAD 757 PART B  
**Revision Date:** 08/02/2010  
**Identification Number:** PLMSDS 8853B1NL  
**Supercedes :** 01/06/2010  
**Product Use/Class:** FOR INDUSTRIAL USE ONLY  
**Preparer:** Regulatory, Department  
**Manufacturer:** Carboline Company  
2150 Schuetz Road  
St. Louis, MO 63146  
(800) 848-4645

## Section 2 - Composition / Information On Ingredients

| Chemical Name      | CAS Number | Weight % Less Than | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA-CEIL |
|--------------------|------------|--------------------|---------------|----------------|--------------|-----------|
| PROPOXYLATED AMINE | 102-60-3   | 35.0               | N/E           | N/E            | N/E          | N/E       |
| SYNTHETIC ZEOLITE  | 1318-02-1  | 5.0                | N/E           | N/E            | N/E          | N/E       |
| CARBON BLACK       | 1333-86-4  | 5.0                | 3.5 MG/M3     | N/E            | 3.5 MG/M3    | N/E       |
| SILANE             | 2530-85-0  | 5.0                | N/E           | N/E            | N/E          | N/E       |

## Section 3 - Hazards Identification

**Emergency Overview:** Irritating to eyes, respiratory system and skin. May be harmful if swallowed.

**Effects Of Overexposure - Eye Contact:** May cause eye irritation.

**Effects Of Overexposure - Skin Contact:** Direct skin contact may cause irritation.

**Effects Of Overexposure - Inhalation:** May cause nose and throat irritation.

**Effects Of Overexposure - Ingestion:** May be harmful if swallowed.

**Effects Of Overexposure - Chronic Hazards:** Under normal use conditions, this product is not expected to cause adverse health effects.

**Primary Route(s) Of Entry:** Skin Contact, Eye Contact

**Medical Conditions Prone to Aggravation by Exposure:** No Information.

## Section 4 - First Aid Measures

**First Aid - Eye Contact:** If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

**First Aid - Skin Contact:** In case of contact, wash skin immediately with soap and water.

**First Aid - Inhalation:** If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

**First Aid - Ingestion:** If swallowed do not induce vomiting. Seek immediate medical attention.

## Section 5 - Fire Fighting Measures

**Flash Point, F:** 330F (165C)  
(Setaflash)

**Lower Explosive Limit, %:** 0.5  
**Upper Explosive Limit, %:** 36.0

**Extinguishing Media:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**Unusual Fire And Explosion Hazards:** This product contains less than 1% volatile components. The amount of vapors that could accumulate are minimal. However, vapors are heavier than air and could travel long distances, ignite, and flashback. Eliminate all ignition sources. Keep away from sparks, open flames, and heat sources. All electrical equipment and installations should be made and grounded in accordance with the National Electrical Code. In areas where explosion hazards exist, workers should be required to use nonferrous tools and to wear conductive and non-sparking shoes.

**Special Firefighting Procedures:** Evacuate hazard area of unprotected personnel. Use a NIOSH approved self-contained breathing unit and complete body protection. Cool surrounding containers with water in case of fire exposure.

## Section 6 - Accidental Release Measures

**Steps To Be Taken If Material Is Released Or Spilled:** Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Evacuate the area of unprotected personnel. Wear appropriate personal protection clothing and equipment. Follow exposure controls/personal protection guidelines in Section 8. Contain and soak up residual with an absorbent (clay or sand). Take up absorbent material and seal tightly for proper disposal. Dispose of in accordance with local, state and federal regulations. Refer to Section 15 for SARA Title III and CERCLA information.

## Section 7 - Handling And Storage

**Handling:** Avoid breathing vapors or spray mist. Do not get in eyes, on skin, or on clothing. Keep container tightly closed when not in use. Wear personal protection equipment. Do not breathe vapors. Wash thoroughly after handling. If pouring or transferring materials, ground all containers and tools. Do not weld, heat, cut or drill on full or empty containers. Use only in accordance with Carboline application instructions, container label and Product Data Sheet.

**Storage:** Keep away from heat, sparks, open flames and oxidizing agents. Keep containers closed. Store in a cool, dry place with adequate ventilation.

## Section 8 - Exposure Controls / Personal Protection

**Engineering Controls:** Use explosion-proof ventilation when required to keep below health exposure guidelines and Lower Explosion Limit (LEL).

**Respiratory Protection:** Use only with ventilation to keep levels below exposure guidelines listed in Section 2. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use MSHA/NIOSH approved supplied air respirator. Follow all current OSHA requirements for respirator use. For silica containing coatings in a liquid state, and/or if no exposure limits are established in Section 2 above, supplied air respirators are generally not required.

**Skin Protection:** Recommend impervious gloves and clothing to avoid skin contact. If material penetrates to skin, change gloves and clothing. The use of protective creams may be beneficial to certain individuals. Protective creams should be applied before exposure.

**Eye Protection:** Recommend safety glasses with side shields or chemical goggles to avoid eye contact.

**Other protective equipment:** Eye wash and safety showers should be readily available.

**Hygienic Practices:** Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Use of a hand cleaner is recommended. Launder contaminated clothing before reuse. Leather shoes can absorb and allow hazardous materials to pass through. Check shoes carefully after soaking before reuse.

## Section 9 - Physical And Chemical Properties

|                           |                               |                          |                   |
|---------------------------|-------------------------------|--------------------------|-------------------|
| <b>Boiling Range:</b>     | 149 F (65 C) - 595 F (313 C)  | <b>Vapor Density:</b>    | Heavier than Air  |
| <b>Odor:</b>              | Slight                        | <b>Odor Threshold:</b>   | N/D               |
| <b>Appearance:</b>        | Viscous Brown or Black Liquid | <b>Evaporation Rate:</b> | Slower Than Ether |
| <b>Solubility in H2O:</b> | N/D                           |                          |                   |
| <b>Freeze Point:</b>      | N/D                           | <b>Specific Gravity:</b> | app. 1.03         |
| <b>Vapor Pressure:</b>    | N/D                           | <b>PH:</b>               | N/D               |
| <b>Physical State:</b>    | Liquid                        |                          |                   |

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

**Conditions To Avoid:** Heat, sparks and open flames.

**Incompatibility:** Avoid contact with strong oxidizing agents.

**Hazardous Decomposition Products:** Carbon monoxide, nitrogen oxides, and unidentified organic compounds. Consider all smoke and fumes from burning material as very hazardous. Welding, cutting or abrasive grinding can create smoke and fumes. Do not breathe any fumes or smoke from these operations.

**Hazardous Polymerization:** Will not occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

## Section 11 - Toxicological Information

**Product LD50:** N/D

**Product LC50:** N/D

| Chemical Name      | CAS Number | LD50                 | LC50                   |
|--------------------|------------|----------------------|------------------------|
| PROPOXYLATED AMINE | 102-60-3   | 3.28 G/KG, ORAL, RAT | NOT AVAILABLE          |
| SYNTHETIC ZEOLITE  | 1318-02-1  | N/E                  | N/E                    |
| CARBON BLACK       | 1333-86-4  | NOT AVAILABLE        | >8000 MG/KG, ORAL, RAT |
| SILANE             | 2530-85-0  | N/E                  | N/E                    |

## Section 12 - Ecological Information

**Ecological Information:** No data

## Section 13 - Disposal Information

**Disposal Information:** Dispose of in accordance with State, Local, and Federal Environmental regulations. Responsibility for proper waste disposal is with the owner of the waste.

## Section 14 - Transportation Information

|                                  |               |                          |     |
|----------------------------------|---------------|--------------------------|-----|
| <b>DOT Proper Shipping Name:</b> | Not Regulated | <b>Packing Group:</b>    | N/A |
| <b>DOT Technical Name:</b>       | N/A           | <b>Hazard Subclass:</b>  | N/A |
| <b>DOT Hazard Class:</b>         | None          | <b>Resp. Guide Page:</b> | N/A |
| <b>DOT UN/NA Number:</b>         | None          |                          |     |

**Additional Notes:** None.

## Section 15 - Regulatory Information

### CERCLA - SARA HAZARD CATEGORY

This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD

### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Section 313 Substances exist in this product

### TOXIC SUBSTANCES CONTROL ACT

All components of this product are listed on the TSCA inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(B) Substances exist in this product

### U.S. STATE REGULATIONS AS FOLLOWS:

#### NEW JERSEY RIGHT-TO-KNOW

The following materials are non-hazardous, but are among the top five components in this product.

| <u>Chemical Name</u> | <u>CAS Number</u> |
|----------------------|-------------------|
| CASTOR OIL           | 8001-79-4         |
| POLYETHER POLYOL     | 25322-69-4        |
| IRON OXIDE           | 1309-37-1         |

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u> | <u>CAS Number</u> |
|----------------------|-------------------|
| CASTOR OIL           | 8001-79-4         |
| POLYETHER POLYOL     | 25322-69-4        |

#### CALIFORNIA PROPOSITION 65

**Warning: The following ingredients present in the product are known to the state of California to cause Cancer:**

| <u>Chemical Name</u>    | <u>CAS Number</u> |
|-------------------------|-------------------|
| CARBON BLACK            | 1333-86-4         |
| MICROCRYSTALLINE SILICA | 14808-60-7        |
| ETHYL ACRYLATE          | 140-88-5          |

**Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards:**

No California Proposition 65 Reproductive Toxins exist

### INTERNATIONAL REGULATIONS AS FOLLOWS:

## CANADIAN WHMIS

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** D2A, D2B

### Section 16 - Other Information

#### HMIS Ratings

**Health:** 2

**Flammability:** 1

**Reactivity:** 0

**Personal Protection:** X

**VOLATILE ORGANIC COMPOUNDS, GR/LTR MIXED (UNTHINNED):** 0

**REASON FOR REVISION:** Product composition changed. Changes made in Section(s) 2, 5, 9, 11, and 15.

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations