

Safety Data Sheet according to Regulation (EC) 'No. 2020/878

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

P391B **Revision Date:** 04-03-2025 **Product Identifier** 1.1

THERMALINE HEAT SHIELD -Supersedes Date: 07-02-2023 **Product Name:**

PART B

3 **Version Number:**

UFI Code: CP9G-T3PV-F00C-6JGS

No Contain nanoform:

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Please see Technical Data Sheet. Advised against: others than recommended

THERMALINE HEAT SHIELD - PART A Product to be mixed with:

Mixing ratio by volume Part A/

Part B:

10 / 0.35

Details of the supplier of the safety data sheet

Carboline Italia, S.p.a. Supplier:

Via Margherita Viganò De Vizzi, 77 20092 Cinisello Balsamo (MI)

Italy

Regulatory / Technical Information: +32 67493710 Nivelles, Belgium

+39 0294759236 Cinisello Balsamo, Italy

regulatoryeurope@carboline.com

CHEMTREC +1 703 5273887 (Outside US) 1.4 Emergency telephone number:

112 (24/7)

Croatia +3851 2348 342 (24/7 in Croatian and English)

Iceland 112 (24/7) Malta 112 (24/7)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 3	H226
Aspiration Hazard, category 1	H304
Skin Corrosion, category 1B	H314-1B
Skin Sensitizer, category 1	H317
STOT, single exposure, category 3, RTI	H335
STOT, single exposure, category 3, NE	H336
Hazardous to the aquatic environment, Chronic, category 2	H411

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Mesitylene, 3-aminopropyltriethoxysilane, Solvent naphtha (petroleum), light arom.

HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin Corrosion, category 1B	H314-1B	Causes severe skin burns and eye damage.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment,	H411	Toxic to aquatic life with long lasting effects.
Chronic, category 2		

PRECAUTION PHRASES

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P33	IF IN EYES: Rinse cautiously with water for several minutes.
8	Remove contact lenses, if present and easy to do so. Continue rinsing.
	community.

ADDITIONAL INFORMATION

Note P : The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1~% w/w benzene

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Name According to EEC

CAS-No.

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

Endocrine disrupting properties - Ecotoxicity

Name According to EEC

CAS-No.

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

Name According to EEC	<u>%</u>	<u>Classifications</u>	8	SCL Value:
EINEC No.			ļ ,	ATE Value:
CAS-No. REACH Reg No.			ľ	M-Factor:
<u></u>				
Solvent naphtha (petroleum), light arom.	50 - <75	H226-304-315-335-336-411	SCL Value:	-
265-199-0				
64742-95-6		Aquatic Chronic 2, Asp. Tox. 1, Flam. Liq. 3,	ATE \ ()	
01-2119455851-35		Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI	ATE Value:	-
649-356-00-4				
			M-Factor: (acute)	-
			M-Factor: (chronic)	-

3-aminopropyltriethoxysilane 213-048-4 919-30-2	10 - <25	H302-314-317	SCL Value:	-
01-2119480479-24 612-108-00-0		Acute Tox. 4 Oral, Skin Corr. 1B, Skin Sens. 1	ATE Value:	-
			M-Factor: (acute)	-
			M-Factor: (chronic)	-
Mesitylene 203-604-4 108-67-8	2.5 - <10	H226-304-315-319-335-411	SCL Value:	-
01-2119463878-19 601-025-00-5		Aquatic Chronic 2, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2, STOT SE 3 RTI	ATE Value:	-
			M-Factor: (acute)	-
			M-Factor: (chronic)	-
xylene 215-535-7	0.1 - <1.0	H226-304-312-315-319-332-335-373-412	SCL Value:	-
1330-20-7 01-2119488216-32 601-022-00-9		Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2, STOT RE 2, STOT	ATE Value:	-
		SE 3 RTI	M-Factor: (acute)	-
			M-Factor: (chronic)	-

Remarks: Note P

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Move to fresh air. Provide fresh air, rest and warmth. Call a physician immediately. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position. AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin. AFTER EYE CONTACT: Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Irritating to respiratory system. Irritating to skin. May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure. Vapours may cause drowsiness and dizziness. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11. When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Open drum carefully as content may be under pressure. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in upright position only. Storage of flammable liquids. Store away from: oxidising materials, acids, and alkalis.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	CAS-No.	<u>!</u>	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
Solvent naphtha (petroleum), light arom.	64742-95-6					
3-aminopropyltriethoxysilane	919-30-2					
Mesitylene	108-67-8		20			100
xylene	1330-20-7		50	100	442	221
Name	CAS-No.	OEL Note				
Solvent naphtha (petroleum), light arom.	64742-95-6					
3-aminopropyltriethoxysilane	919-30-2					
Mesitylene	108-67-8					
xylene	1330-20-7	Sk				

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

Chemical Name:

Solvent naphtha (petroleum), light arom.

EC No.: CAS-No.: 265-199-0 64742-95-6

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required				11 mg/kg bw/	
							day	
Inhalation	0	0	0	150 mg/m ³	0	0	0	32 mg/m³
Dermal				25 mg/kg bw/day				11 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.635 mg/l
Fresh water sediments	3.29 mg/kg
Marine water	0.0635 mg/l
Marine sediments	0.329 mg/kg
Food chain	
Microorganisms in sewage treatment	100 mg/l
soil (agricultural)	0.29 mg/kg
Air	

Chemical Name:

3-aminopropyltriethoxysilane

EC No.: CAS-No.: 213-048-4 919-30-2

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required				5 mg/kg bw/		5 mg/kg bw/day
						day		
Inhalation		59 mg/m3		59 mg/m3		17.4 mg/m3		17.4 mg/m3
Dermal		8.3 mg/kg bw/		8.3 mg/kg bw/		5 mg/kg bw/		5 mg/kg bw/day
		day		day		day		

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.33 mg/L
Fresh water sediments	
Marine water	0.033 mg/L
Marine sediments	
Food chain	
Microorganisms in sewage treatment	13 mg/L
soil (agricultural)	0.04 mg/kg
Air	

Chemical Name:

xylene

EC No.: CAS-No.: 215-535-7 1330-20-7

DNELs - Derived no effect level

	Workers					Consumers			
Route of Exposure	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	
Oral	Not required							1.6 mg/kg bw/ day	
Inhalation Dermal	289 mg/m³	289 mg/m ³		77 mg/m³ 180 mg/kg bw/	174 mg/m³	174 mg/m³		14.8 mg/m³ 108 mg/kg bw/	
				day				day	

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Wear respiratory protection with combination filter (dust and gas filter, EN 14387:2004 +A1:2008) during spraying operations: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust). When working in confined or poorly ventilated spaces, a battery powered assisted air-fed mask must be used.

EYE PROTECTION: Face-shield. Safety glasses with side-shields conforming to EN 166.

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

Body Protection: Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Colour: Clear
Physical State Liquid
Odor Solvent

Odor threshold

PH

Not determined

Not determined

Melting point / freezing point (°C)

Not determined

Boiling point or initial boiling point and 140 - 200

boiling range (°C)

Flash Point, (°C) 35

Evaporation rate > 1 (air=1)

Flammability (solid, gas) Not determined

Llower and upper explosive limit Not determined

Vapour Pressure Not determined

Relative vapour density Not determined

Density and/or relative density 0.88

Solubility in / Miscibility with water Negligible

Partition coefficient: n-octanol/water Not determined

Auto-ignition temperature (°C) > 400

Decomposition temperature (°C) Not determined

Kinematic viscosity Not determined

Particle characteristics Not applicable to liquids

9.2 Other information

Specific Gravity (g/cm3) 0.88

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No reactivity hazards known under normal storage and use conditions.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Keep away from strong oxidising agents and strongly acid or alkaline materials.

10.6 Hazardous decomposition products

In case of fire or hot work operations, **hazardous decomposition products** may be formed such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), aliphatic amines, aldehydes.

SECTION 11: Toxicological information

11.1 Information on hazard classes as definied in Regulation (EC) No 1272/2008

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Dermal LD50: No Information

Irritation: No information available.

Corrosivity: Corrosive to eyes and skin.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: Vapour/spray mist may irritate respiratory system and lungs.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
64742-95-6	Solvent naphtha (petroleum), light arom.	8400 mg/kg, oral, rat	>2000 mg/kg	3670 ppm/8 hours, rat, inhalation	No information	No information
919-30-2	3-aminopropyltriethoxysilane	1490 mg/kg (oral, rat)	4075 mg/kg (dermal, rabbit)	No information	No information	No information
1330-20-7	xylene	>2000 mg/kg (oral-rat)	1100 mg/kg (ATE dermal-rabbit)	11 mg/L (ATE inh/ vapour)	20001 ppm	>5 mg/l

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Corrosive - causes irreversible eye damage. Chronic exposure causes drying effect on the skin and eczema. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin. Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs.

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Name According to EEC CAS-No.

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

12.7 Other adverse effects: No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
64742-95-6	Solvent naphtha (petroleum), light arom.	3.2 mg/l (EC50, 48h, Daphnia magna)	2.6 mg/l (IC50, 72h Pseudokirchneriella subcapitata)	0
919-30-2	3-aminopropyltriethoxysilane	No information	>1000 mg/L (EC50,72h, Scenedesmus subspicatus)	934 mg/L (CL50 96h, Brachydanio rerio)
108-67-8	Mesitylene	No information	No information	No information
1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrichirus), 21.0 mg/L (Pimephales promelas)

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

European Waste Code: No Information

Packaging Waste Code:

SECTION 14: Transport Information

		ADR/RID	ADN	IMDG	IATA
14.1	UN-number or ID number	UN3470	UN3470	UN3470	UN3470
14.2	UN proper shipping name	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE
14.3	Transport Hazard Class(es)	8,3	8,3	8,3	8,3
14.4	Packing Group	II	II	II	II
14.5	Enviromental Hazards	YES (hydrocarbons, C9, aromatics)	YES (hydrocarbons, C9, aromatics)	Marine Pollutant: YES (hydrocarbons, C9, aromatics)	YES (hydrocarbons, C9, aromatics)

14.6 Special precautions for user Not applicable EmS-No.: F-E, S-C

14.7 Maritime transport in bulk according to IMO

intruments

Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:

Danish MAL Code:

Not available

Danish MAL Code - Mixture:

Not available

Sweden Product Registration Number:

Not available

Norway Product Registration Number:

Not available

Germany WGK Class:

Not available

Directive 2004/42/CE: VOC ready to use 419 g/l (subcat i 500 g/l)

Covered by Directive 2012/18/EC (Seveso III): P5c, E2

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006: Entry 3, 40

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

- 01 Identification
- 02 Hazard Identification
- 03 Composition/Information On Ingredients
 08 Exposure Controls/Personal Protection
- 09 Physical and Chemical Properties
- 11 Toxicological Information
- 14 Transportation Information
- 15 Regulatory Information

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes. .

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million
mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter ≤ 10 µm.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.