

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **Thinner 10**
- Article number: 0510
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU3 Industrial uses: use of substances as such or in preparations in an industrial environment
 - SU22 Professional use: Public domain (administration, education, entertainment, services, craftsmen)
 - SU8 Manufacture of bulk, large scale chemicals (including petroleum products)
 - SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
- Process category
 - PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
 - PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
 - PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
 - PROC4 Chemical production where opportunity for exposure arises
 - PROC7 Industrial spraying
 - PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
 - PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
 - PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
 - PROC11 Non industrial spraying
 - PROC13 Treatment of articles by dipping and pouring
 - PROC15 Use as laboratory reagent
 - PROC17 Lubrication at high energy conditions in metal working operations
 - PROC18 General greasing /lubrication at high kinetic energy conditions
 - PROC20 Use of functional fluids in small devices
 - PROC5 Mixing or blending in batch processes
- Environmental release category
 - ERC1 Manufacture of the substance
 - ERC2 Formulation into mixture
 - ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
 - ERC7 Use of functional fluid at industrial site
 - ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 - ERC9a Widespread use of functional fluid (indoor)
 - ERC9b Widespread use of functional fluid (outdoor)
- Application of the substance / the mixture Thinner, Diluent
- Uses advised against SU21 Consumer use: Private households / general public / consumers
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
 - CARBOLINE NORGE AS
 - Husebysletta 7 P.O. Box 593 - N-3412 Lierstranda
 - Norway
 - Phone: +47 32 85 73 00
 - www.carboline.no
 - Email: Carboline.norge@carboline.com
- Further information obtainable from: ehseurope@stoncor.com
- 1.4 Emergency telephone number:
 - This product does not need to be notified under Article 45.
 - CHEMTREC 1-800-424-9300 (Inside US)
 - CHEMTREC +1 703 5273887 (Outside US)
 - HEALTH - Pittsburgh Poison Control 1-412-681-6669

Trade name: **Thinner 10**

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger
- Hazard-determining components of labelling:
Reaction mass of ethylbenzene and xylene
- Hazard statements
 - H226 Flammable liquid and vapour.
 - H312+H332 Harmful in contact with skin or if inhaled.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H335 May cause respiratory irritation.
 - H373 May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.
 - H304 May be fatal if swallowed and enters airways.
 - H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
 - P280 Wear protective gloves/protective clothing/eye protection/face protection.
 - P284 In case of inadequate ventilation wear respiratory protection.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P314 Get medical advice/attention if you feel unwell.

(Contd. on page 3)




Trade name: **Thinner 10**




(Contd. of page 2)

- Additional information:
Restricted to professional users.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.
- Dangerous components %(m/m):

EC number: 905-588-0	Reaction mass of ethylbenzene and xylene	75-100%
Reg.nr.: 01-2119488216-32	 Flam. Liq. 3, H226;  STOT RE 2, H373; Asp. Tox. 1, H304;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	

CAS: 108-88-3	toluene	≤0.5%
EINECS: 203-625-9	 Flam. Liq. 2, H225;  Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304;  Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 3, H412	
Reg.nr.: 01-2119471310-51		

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:
In case of doubt or if symptoms occur, call medical attention.
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:
Take affected persons into fresh air and keep quiet.
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Remove contaminated clothing, use gloves when removing the clothing.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- After eye contact:
Rinse eyes with open eyelid under running water for 15 minutes and consult a doctor.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Contact lens removal.
- After swallowing:
Do not induce vomiting - aspiration hazard.
Seek immediate medical advice.
Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- Hazards After swallowing the liquid, droplets of product can enter the lungs (aspiration), causing pneumonia.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO₂ or powder. Fight larger fire with alcohol-resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
Carbon dioxide (CO₂)
Carbon monoxide (CO)

(Contd. on page 4)

GB —

Trade name: **Thinner 10**

(Contd. of page 3)

- 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- Additional information
 - Cool endangered receptacles with water spray.
 - Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 - Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to section 13.
 - Ensure adequate ventilation.
 - Collect leaking liquid in sealable waste containers.
- 6.4 Reference to other sections
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
 - Work only in fume cupboard.
 - Ensure good ventilation/exhaustion at the workplace.
- Information about fire - and explosion protection:
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
 - Requirements to be met by storerooms and receptacles:
 - Suitable material for receptacles and pipes: stainless steel.
 - Store only in the original receptacle.
 - Information about storage in one common storage facility: Store away from oxidising agents.
 - Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppmLong-term value: 191 mg/m³, 50 ppm

Sk

- DNELs

Reaction mass of ethylbenzene and xylene

Dermal	Long-term exposure - systemic effects	180 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - systemic effects	289 mg/m ³ (worker)
	Acute - short-term exposure - local effects	289 mg/m ³ (worker)
	Long-term exposure - systemic effects	77 mg/m ³ (worker)
	Long-term exposure - local effects	221 mg/m ³ (worker)

(Contd. on page 5)

— GB —

Trade name: **Thinner 10**

(Contd. of page 4)

108-88-3 toluene

Dermal	Long-term exposure - systemic effects	384 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - systemic effects	384 mg/m ³ (worker)
	Acute - short-term exposure - local effects	384 mg/m ³ (worker)
	Long-term exposure - systemic effects	192 mg/m ³ (worker)
	Long-term exposure - local effects	192 mg/m ³ (worker)

• PNECs

Reaction mass of ethylbenzene and xylene

PNEC	12.64 mg/kg (sediment marine water)
	12.64 mg/kg (sediment freshwater)
	2.31 mg/kg (soil)
PNEC	6.58 mg/l (STP)
	0.327 mg/l (aqua, freshwater)
	0.327 mg/l (aqua, marine water)

108-88-3 toluene

PNEC	16.39 mg/kg (sediment marine water)
PNEC	13.61 mg/l (STP)
	0.68 mg/l (aqua, freshwater)
	0.68 mg/l (aqua, intermittent releases)
	0.68 mg/l (aqua, marine water)

• Ingredients with biological limit values:

• Additional Occupational Exposure Limit Values for possible hazards during processing:

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm
	Long-term value: 441 mg/m ³ , 100 ppm
	Sk

• Additional information: The lists valid during the making were used as basis.

• 8.2 Exposure controls

• Appropriate engineering controls Ensure adequate ventilation.

• Individual protection measures, such as personal protective equipment

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

• Respiratory protection:

Short term filter device:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter type A.

If workers are exposed to concentrations above the exposure limit, they should use a suitable, certified respirator.

• Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Trade name: **Thinner 10**

(Contd. of page 5)

- Material of gloves
Suitable material for safety gloves (EN 374):
Fluorocarbon rubber gloves (Viton)
- Penetration time of glove material
Thickness of gloves ≥ 0.4 mm (xylene)
Value for the permeation ≥ 480 min (xylenes)
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye/face protection



Tightly sealed goggles

- Body protection: Solvent resistant protective clothing
- Environmental exposure controls No additional data. See 6 and 13.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
 - General Information
 - Physical state Fluid
 - Colour: Clear
 - Odour: Aromatic
 - Odour threshold: Not determined.
 - Melting point/freezing point: <-25 °C
 - Boiling point or initial boiling point and boiling range ≥ 136 - ≤ 145 °C (Reaction mass of ethylbenzene and xylene)
 - Flammability Flammable.
 - Lower and upper explosion limit
 - Lower: 1 Vol %
 - Upper: 8 Vol %
 - Flash point: 24 °C
 - Auto-ignition temperature: 460 °C
 - Decomposition temperature: Not determined.
 - pH: Not determined.
 - Viscosity:
 - Kinematic viscosity at 40 °C 0.9 mm²/s
 - Dynamic at 20 °C: 0.61 mPas
 - Solubility
 - water: Slightly soluble.
 - Partition coefficient n-octanol/water (log value) Not determined.
 - Vapour pressure at 20 °C: 8 hPa (Reaction mass of ethylbenzene and xylene)
 - Density and/or relative density
 - Density at 20 °C: 0.87 g/cm³
 - Relative density: Not determined.
 - Vapour density: Not determined.
- 9.2 Other information
 - Appearance:
 - Form: Liquid
 - Important information on protection of health and environment, and on safety.
 - Ignition temperature: Product is not selfigniting.
 - Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
 - Solvent content:
 - Organic solvents: 100.0 %
 - VOC (EC) 870.0 g/l
100.00 %
 - Solids content: 0.0 %
 - Molecular weight 106.17 g/mol

(Contd. on page 7)

Trade name: **Thinner 10**

(Contd. of page 6)

· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions
 - Reacts with oxidising agents.
 - Reacts with strong acids.
 - Reacts with strong oxidizing agents.
- 10.4 Conditions to avoid
 - Heat, fire and sparks.
 - High temperatures
- 10.5 Incompatible materials: Strong oxidising products.
- 10.6 Hazardous decomposition products:
 - During a fire, carbonoxides (CO/CO₂) and smoke release.
 - Aldehyde

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Harmful in contact with skin or if inhaled.
- LD/LC50 values relevant for classification:

108-88-3 toluene

- Oral LD50 5,580 mg/kg (rat)
- Dermal LD50 >5,000 mg/kg (rabbit)
- Inhalative LC50/4h 20 mg/l (rat)
- Primary irritant effect:
 - Skin corrosion/irritation Causes skin irritation.
 - Serious eye damage/irritation Causes serious eye irritation.
 - STOT-single exposure May cause respiratory irritation.
 - STOT-repeated exposure
 - May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure.
 - Route of exposure: Inhalation.
- Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 8)

— GB —

Trade name: **Thinner 10**

(Contd. of page 7)

- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

Reaction mass of ethylbenzene and xylene

ErC50/72h 4.9 mg/l (pseudokirchneriella subcapitata) (OECD 201)

EC50/48h >3.4 mg/l (Ceriodaphnia dubia)

EC50/73h 2.2 mg/l (algae) (OECD 201)

LC50/96h 2.6 mg/l (oncorhynchus mykiss)

13.4 mg/l (pimphales promelas)

LC50/24h 1 mg/l (daphnia magna) (OECD 202)

108-88-3 toluene

NOEC/72h 10 mg/l (Skeletonema costatum)

EC50/3h 134 mg/l (Chlorella vulgaris)

EC50/48h 3.78 mg/l (daphnia magna)

EC50/72h 12.5 mg/l (algae)

LC50/96h 5.5 mg/l (Oncorhynchus kisutch)

5.5 mg/l (fish)

- 12.2 Persistence and degradability No further relevant information available.
- Degree of elimination:

Reaction mass of ethylbenzene and xylene

BOD/28d 90 % (/)

- 12.3 Bioaccumulative potential

Reaction mass of ethylbenzene and xylene

LogPow 3.12-3.2 (/)

108-88-3 toluene

BCF 90 (/)

LogPow 2.73 (/)

- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
 - Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Trade name: **Thinner 10**

(Contd. of page 8)

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR/ADN, IMDG, IATA
- 14.2 UN proper shipping name
- ADR/ADN
- IMDG, IATA
- 14.3 Transport hazard class(es)
- ADR/ADN, IMDG, IATA

UN1307

1307 XYLENES
XYLENES

- Class
- Label
- 14.4 Packing group
- ADR/ADN, IMDG, IATA
- 14.5 Environmental hazards:
- Marine pollutant:
- 14.6 Special precautions for user
- Hazard identification number (Kemler code):
- EMS Number:
- Stowage Category
- 14.7 Maritime transport in bulk according to IMO instruments

3 Flammable liquids.

3

III

No

Warning: Flammable liquids.

30

F-E,S-D

A

Not applicable.

- Transport/Additional information:

- ADR/ADN
- Limited quantities (LQ)
- Excepted quantities (EQ)
- Transport category
- Tunnel restriction code

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

3

D/E

- IMDG
- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- UN "Model Regulation":

UN 1307 XYLENES, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- Regulated explosives precursors
- None of the ingredients is listed.
- Regulated poisons
- None of the ingredients is listed.
- Reportable explosives precursors
- None of the ingredients is listed.

(Contd. on page 10)

Trade name: **Thinner 10**

(Contd. of page 9)

- Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

- National regulations:

- Other regulations, limitations and prohibitive regulations

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Related CAS number = 1330-20-7

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS: Product safety department.

- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3