

**Safety Data Sheet according to Regulation
(EC) 'No. 2020/878****SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking**

1.1	Product Identifier	8320A	Revision Date:	17/10/2024
	Product Name:	CARBOMASTIC 18 FC - A	Supersedes Date:	22/07/2024
			Version Number:	2
	UFI Code:	H3F0-90S7-7006-AKV1		
	Contain nanoform:	Yes		
1.2	Relevant identified uses of the substance or mixture and uses advised against	Base component of 2 components coating - Industrial use. Please see Technical Data Sheet. Advised against: others than recommended		
	Product to be mixed with:	CARBOMASTIC 18 FC PART B / CARBOMASTIC 18 FC CARBO-KIT PART B		
	Mixing ratio by volume Part A/ Part B:	1 / 1		
1.3	Details of the supplier of the safety data sheet			
	Supplier:	Carboline Italia, S.p.a. Via Margherita Viganò De Vizzi, 77 20092 Cinisello Balsamo (MI) Italy		
		Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 0294759236 Cinisello Balsamo, Italy		
	Datasheet Produced by:	Calcagno, Elena - hms@carboline.com		
1.4	Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US) 112 (24/7) Croatia +3851 2348 342 (24/7 in Croatian and English) Iceland 112 (24/7) Malta 112 (24/7)		

SECTION 2: Hazards Identification**2.1 Classification of the substance or mixture**

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 3	H226
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319
Hazardous to the aquatic environment, Chronic, category 2	H411

2.2 Label elements**Symbol(s) of Product****Signal Word**

Warning

Named Chemicals on Label

bis[4-(2,3-epoxypropoxy)phenyl]propane, phenol, styrenated, phenol, methylstyrenated

HAZARD STATEMENTS

Other EU extensions	EUH205	Contains epoxy constituents. May produce an allergic reaction.
Other EU extensions	EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Name According to EEC	CAS-No.
------------------------------	----------------

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

Endocrine disrupting properties - Ecotoxicity

Name According to EEC	CAS-No.
------------------------------	----------------

phenol, styrenated

61788-44-1

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u> <u>EINEC No.</u> <u>CAS-No.</u> <u>REACH Reg No.</u>	<u>%</u>	<u>Classifications</u>	SCL Value: ATE Value: M-Factor:
bis[4-(2,3-epoxypropoxy)phenyl] propane 216-823-5 1675-54-3 01-2119456619-26 603-073-00-2	25 - <50	H315-317-319-411 Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	SCL Value: - ATE Value: - M-Factor: (acute) - M-Factor: (chronic) -
titanium dioxide 236-675-5 13463-67-7 01-2119489379-17	10 - <25		SCL Value: - ATE Value: - M-Factor: (acute) - M-Factor: (chronic) -

talc 238-877-9 14807-96-6 - -	10 - <25		SCL Value: - ATE Value: - M-Factor: (acute) - M-Factor: (chronic) -
quartz (silicon dioxide binded within a mineral structure) 238-878-4 14808-60-7 - Not applicable	2.5 - <10		SCL Value: - ATE Value: - M-Factor: (acute) - M-Factor: (chronic) -
xylene 215-535-7 1330-20-7 01-2119488216-32 601-022-00-9	2.5 - <10	H226-304-312-315-319-332-335-373-412 Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2, STOT RE 2, STOT SE 3 RTI	SCL Value: - ATE Value: - M-Factor: (acute) - M-Factor: (chronic) -
phenol, methylstyrenated 270-966-8 68512-30-1 01-2119555274-38	2.5 - <10	H315-317-332-412 Acute Tox. 4 Inhalation, Aquatic Chronic 3, Skin Irrit. 2, Skin Sens. 1	SCL Value: - ATE Value: - M-Factor: (acute) - M-Factor: (chronic) -

phenol, styrenated 262-975-0 61788-44-1 01-2119980970-27	1.0 - <2.5	H315-317-411 Aquatic Chronic 2, Skin Irrit. 2, Skin Sens. 1	SCL Value:	-
			ATE Value:	-
			M-Factor: (acute)	-
			M-Factor: (chronic)	-
ethylbenzene 202-849-4 100-41-4 01-2119489370-35 601-023-00-4	1.0 - <2.5	H225-304-332-373-412 Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Flam. Liq. 2, STOT RE 2	SCL Value:	-
			ATE Value:	-
			M-Factor: (acute)	-
			M-Factor: (chronic)	-
4-methylpentan-2-one 203-550-1 108-10-1 01-2119473980-30 606-004-00-4	0.1 - <1.0	H225-319-332-336-351 Acute Tox. 4 Inhalation, Carc. 2, Eye Irrit. 2, Flam. Liq. 2, Skin Cracking, STOT SE 3 NE	SCL Value:	-
			ATE Value:	ATE (vapours) = 11 mg/l
			M-Factor: (acute)	-
			M-Factor: (chronic)	-
1,3-bis[12-hydroxy- octadecamide-N-methylene]- benzene 423-300-7 128554-52-9 01-0000016979-49	0.1 - <1.0	H317-413 Aquatic Chronic 4, Skin Sens. 1	SCL Value:	-
			ATE Value:	-
			M-Factor: (acute)	-
			M-Factor: (chronic)	-

quartz (silicon dioxide) 238-878-4 14808-60-7 -	0.1 - <1.0	H372 STOT RE 1	SCL Value: - ATE Value: - M-Factor: (acute) - M-Factor: (chronic) -
--	------------	-----------------------	--

Remarks: Note 10**NANOFORMS**

iron hydroxide oxide yellow
51274-00-1
257-098-5

Distribution

D10 = 40 nm ± 10 nm
D50 = 75 nm ± 25 nm
D90 = 160 nm ± 40 nm

Shape: Rods

Crystallinity: No

Treatment of the surface:

carbon black
1333-86-4
215-609-9

Distribution

D10: 6-30 nm
D50: 10-53 nm
D90: 23-144 nm

Shape: Spheroidal

Crystallinity: No

Treatment of the surface:

Silica, amorphous, fumed,
crystalline free
112945-52-5
231-545-4

Distribution

D10: 7-15 nm
D50: 2-30 nm
D90: 10-35 nm

Shape: Spheroidal

Crystallinity: Amorphous

Treatment of the surface: No

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.**SECTION 4: First-aid Measures****4.1 Description of First Aid Measures****GENERAL NOTES:** Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Move to fresh air. Provide fresh air, rest and warmth. Call a physician immediately. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

May cause sensitization by skin contact. Irritating to eyes and skin.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11. When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

6.2 Environmental precautions

Avoid release to the environment. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Apply technical measures to comply with the occupational exposure limits (see section 8). People handling polyurethane or epoxy products must have received special training according to guidelines from the National Occupational Health and Safety Board. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in upright position only. Storage of flammable liquids.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
bis[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3				
titanium dioxide	13463-67-7				
talc	14807-96-6				
quartz (silicon dioxide binded within a mineral structure)	14808-60-7				
xylene	1330-20-7	50	100	442	221
phenol, methylstyrenated	68512-30-1				
phenol, styrenated	61788-44-1				
ethylbenzene	100-41-4	100	200	884	442
4-methylpentan-2-one	108-10-1	20	50	208	83
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	128554-52-9				
quartz (silicon dioxide)	14808-60-7				

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
bis[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	
titanium dioxide	13463-67-7	
talc	14807-96-6	
quartz (silicon dioxide binded within a mineral structure)	14808-60-7	
xylene	1330-20-7	Sk
phenol, methylstyrenated	68512-30-1	
phenol, styrenated	61788-44-1	
ethylbenzene	100-41-4	Sk
4-methylpentan-2-one	108-10-1	Sk
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	128554-52-9	

quartz (silicon dioxide)

14808-60-7

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

Chemical Name:

bis[4-(2,3-epoxypropoxy)phenyl]propane

EC No.:

216-823-5

CAS-No.:

1675-54-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					0.75 mg/kg bw/day		0.75 mg/kg bw/day
Inhalation		12.25 mg/m3		12.25 mg/m3				
Dermal		8.33 mg/kg bw/day		8.33 mg/kg bw/day		3.571 mg/kg bw/day		3.571 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.006 mg/l
Fresh water sediments	0.996 mg/L
Marine water	0.0006 mg/l
Marine sediments	0.0996 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	0.196 mg/kg
Air	

Chemical Name:

titanium dioxide

EC No.:

236-675-5

CAS-No.:

13463-67-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							700 mg/kg/ bw/day
Inhalation			5 mg/m ³				5 mg/m ³	
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.127 mg/L
Fresh water sediments	1000 mg/kg dw
Marine water	1 mg/L
Marine sediments	100 mg/kg dw
Food chain	1667 mg/kg (oral)
Microorganisms in sewage treatment	100 mg/kg
soil (agricultural)	100 mg/kg dw
Air	

Chemical Name:

xylene

EC No.:

215-535-7

CAS-No.:

1330-20-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/day
Inhalation	289 mg/m ³	289 mg/m ³		77 mg/m ³	174 mg/m ³	174 mg/m ³		14.8 mg/m ³
Dermal				180 mg/kg bw/day				108 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

Chemical Name:

phenol, methylstyrenated

EC No.:

270-966-8

CAS-No.:

68512-30-1

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							0.2 mg/kg bw/day
Inhalation				1.4 mg/m ³				0.35 mg/m ³
Dermal				3.5 mg/kg bw/day				1.7 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	14 µg/L
Fresh water sediments	1064 mg/kg dw
Marine water	1.4 µg/L
Marine sediments	106 mg/kg dw
Food chain	
Microorganisms in sewage treatment	2.4 mg/L
soil (agricultural)	212 mg/kg dw
Air	

Chemical Name:

phenol, styrenated

EC No.:

262-975-0

CAS-No.:

61788-44-1

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation				1.21 mg/m ³				
Dermal				2.87 mg/kg bw/day				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	11.5 µg/L
Fresh water sediments	1.564 mg/kg dw
Marine water	1.15 µg/L
Marine sediments	0.156 mg/kg dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	0.305 mg/kg dw
Air	

Chemical Name:

4-methylpentan-2-one

EC No.:

203-550-1

CAS-No.:

108-10-1

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							4.2 mg/kg bw/day
Inhalation	208 mg/m ³	208 mg/m ³		83 mg/m ³	155.2 mg/m ³	155.2 mg/m ³		14.7 mg/m
Dermal				11.8 mg/kg bw/day				4.2 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.6 mg/L
Fresh water sediments	8.27 mg/kg sediment dw
Marine water	0.06 mg/L
Marine sediments	0.83 mg/kg sediment dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	1.3 mg/kg soil dw
Air	

8.2 Exposure controls**Personal Protection**

RESPIRATORY PROTECTION: Wear a self-contained breathing apparatus or full-face airline respirator during spraying operations and long-term exposure. When working in confined or poorly ventilated spaces, a battery powered assisted air-fed mask must be used. When painting small areas, or when using a roller or brush, respiratory protection with combination filter (dust and gas filter, EN 14387:2004+A1:2008) may be used: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust).

EYE PROTECTION: If splashes are likely to occur, wear: Face-shield, tightly fitting safety goggles (EN 166).

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due

to the numerous outside influences (e.g. temperature). Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Body Protection: Long sleeved clothing.
Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties	
Colour:	Misc. colours
Physical State	Liquid
Odor	Solvent
Odor threshold	Not determined
pH	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point or initial boiling point and boiling range (°C)	114 - 152
Flash Point, (°C)	26
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Lower and upper explosive limit	1 - 8
Vapour Pressure	Not determined
Relative vapour density	>1 (air=1)
Density and/or relative density	Not determined
Solubility in / Miscibility with water	Negligible
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	>432
Decomposition temperature (°C)	Not determined
Kinematic viscosity	115 - 125 KU
Particle characteristics	Not applicable to liquids

Nanoform in mixture

iron hydroxide oxide yellow 51274-00-1 257-098-5	Solubility:	Insoluble
	NoctanoWater:	Not determined
	Partichle Charactheristics:	See sec. 3.2

carbon black 1333-86-4 215-609-9	Solubility: Insoluble NoctanoWater: Not determined Partichle Characteristics: See sec. 3.2
Silica, amorphous, fumed, crystalline free 112945-52-5 231-545-4	Solubility: Not determined NoctanoWater: Not determined Partichle Characteristics: See sec. 3.2

9.2 Other information

VOC Content g/l: 120

Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.

Specific Gravity (g/cm3) 1,68

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No reactivity hazards known under normal storage and use conditions.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Keep away from strong oxidising agents and strongly acid or alkaline materials.

10.6 Hazardous decomposition products

In case of fire or hot work operations, **hazardous decomposition products** may be formed such as: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), aliphatic amines, aldehydes.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute Toxicity:

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Dermal LD50: No information available on the product itself as the product is not tested.

Irritation: Irritating to eyes and skin.

Corrosivity: No information available.

Sensitization: May cause an allergic skin reaction.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	5000 mg/kg (oral-rat)	>2000 mg/kg (dermal, rat M-F)	>20	No information	No information
13463-67-7	titanium dioxide	>5000 mg/kg (oral-rat)	10000 mg/kg	No information	No information	>6.82 mg/L (inh-rat-4h)
1330-20-7	xylene	>2000 mg/kg (oral-rat)	1100 mg/kg (ATE dermal-rabbit)	11 mg/L (ATE inh/vapour)	20001 ppm	>5 mg/l
68512-30-1	phenol, methylstyrenated	>2000 mg/kg (oral, rat)	>2000 mg/kg (dermal, rat)	No information	No information	> 4.92 mg/L (inhalation, aerosol, rat)
61788-44-1	phenol, styrenated	>2000 mg/kg (oral, rat)	>2000 mg/kg (dermal, rat)	No information	No information	No information
100-41-4	ethylbenzene	3500 mg/kg rat, oral	5510 mg/kg, rabbit	4000 ppm, rat, 4h	10000 ppm	1.5 mg/L
108-10-1	4-methylpentan-2-one	2080 mg/kg (oral, rat)	>2000 mg/kg (dermal, rabbit)	11 mg/L	4500 ppm	1.5 mg/L

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Chronic exposure causes drying effect on the skin and eczema. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Repeated skin contact leads to irritation and to sensitisation, possible with cross-sensitisation to other epoxies. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. The product is irritating to the eyes and may cause sensitisation to the respiratory system. Swallowing concentrated chemical may cause severe internal injury. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs.

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Name According to EEC

CAS-No.

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

- 12.2 Persistence and degradability:** No information
- 12.3 Bioaccumulative potential:** No information
- 12.4 Mobility in soil:** No information
- 12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Endocrine disrupting properties**Endocrine disrupting properties - Ecotoxicity**

Name According to EEC	CAS-No.
phenol, styrenated	61788-44-1

- 12.7 Other adverse effects:** No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	1.8 mg/l (Daphnia magna, EC50, 48h,static)	11 mg/l (Scenedesmus capricornutum,EC50r, 72h)	1.5 mg/L (Rainbow trout), 3.6 mg/L (fish)
13463-67-7	titanium dioxide	>1000 mg/L (LC50, statisk, Daphnia magna, OECD202)	>100 mg/L (EC50, statisk, Pseudokirchnerella subcapitata, OECD201)	>1000 mg/L (LC50, statisk, Pimephales promelas, EPA-540/9-85-006)
1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrochirus), 21.0 mg/L (Pimephales promelas)
68512-30-1	phenol, methylstyrenated	14 - 51 mg/L (Daphnia) (OECD TG 202)	15 mg/L (Algae) (OECD TG 201)	25.8 mg/L (Fish) (OECD TG 203)
61788-44-1	phenol, styrenated	1 - 10 mg/L (EL50, Daphnia)	3.14 mg/L (EL50, Algae)	14.8 mg/L (Fish)
100-41-4	ethylbenzene	1.37 mg/l	No information	32 mg/l (Bluegill)
108-10-1	4-methylpentan-2-one	>100 mg/L	>100 mg/L	>179 mg/L (Brachydanio rerio,LD50, 96h)

SECTION 13: Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

European Waste Code: 08 01 11*
Packaging Waste Code: 15 01 10*

SECTION 14: Transport Information

	ADR/RID	ADN	IMDG	IATA
14.1 UN-number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport Hazard Class(es)	3	3	3	3
14.4 Packing Group	III	III	III	III
14.5 Enviromental Hazards	Environmental Hazard: YES (bis[4-(2,3-epoxypropoxy)phenyl]propane)	Environmental Hazard: YES (bis[4-(2,3-epoxypropoxy)phenyl]propane)	Marine Pollutant: YES (bis[4-(2,3-epoxypropoxy)phenyl]propane)	Environmental Hazard: YES (bis[4-(2,3-epoxypropoxy)phenyl]propane)

14.6 Special precautions for user Not applicable

EmS-No.: F-E, S-E

14.7 Maritime transport in bulk according to IMO intruments Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available

Danish MAL Code: 2 - 5

Danish MAL Code - Mixture: 2 - 5

Sweden Product Registration Number: Not available

Norway Product Registration Number: P-92427

Germany WGK Class: Not available

Directive 2004/42/CE: 500 g/l (subcat j)

Covered by Directive 2012/18/EC (Seveso III): P5c, E2
Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006: Entry 3, 40

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

68512-30-1 phenol, methylstyrenated

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Reasons for revision

Revision Description Changed

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

03 - Composition/Information On Ingredients

08 - Exposure Controls/Personal Protection

09 - Physical and Chemical Properties

11 - Toxicological Information

12 - Ecological Information

13 - Disposal Information

15 - Regulatory Information

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes. . . This safety data sheet (SDS) applies to several colours and is based on the colour with the most stringent classification. Thus, for some colours, there may be a different classification than the one given in section 2.2 in this SDS.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road

RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

