

Safety Data Sheet according to Regulation (EC) No. 2020/878

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1	Product Identifier	83200908	Revision Date:	11/10/2023
	Product Name:	CARBOMASTIC 18 FC PART B / CARBOMASTIC 18 FC CARBO- KIT PART B	Supercedes Date:	01/09/2023
			Version Number:	6
	UFI Code:	F5F0-T0FM-H00P-YXF3		
	Contain nanoform:	No		
1.2	Relevant identified uses of the substance or mixture and uses advised against	Hardener for 2 components coatings - Ind Advised against: others than recommende		
	Product to be mixed with: Mixing ratio by volume Part A/ Part B:	CARBOMASTIC 18 FC PART A / CARBO 1:1	MASTIC 18 FC CARBO-KIT PAR	ΤΑ
1.3	Details of the supplier of the safety	data sheet		
	Manufacturer:	Carboline Norge AS Postboks 593 3412 Lierstranda Norway Regulatory / Technical Information: +47 32 85 73 00 +47 32 85 74 00		
	Datasheet Produced by:	Tarka, Malgorzata - hms@carboline.com		
1.4	Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US 112 (24/7) Croatia +3851 2348 342 (24/7 in Croatian Iceland 112 (24/7) Malta 112 (24/7)		

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Corr. Resp.	EUH071
Flam. Liq. 3	H226
Skin Corr. 1B	H314-1B
Skin Sens. 1	H317
STOT RE 2	H373
Aquatic Chronic 2	H411

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

2,4,6-tris(dimethylaminomethyl)phenol, ethylbenzene, xylene, benzene-1,3-dimethanamine, 3-Aminomethyl-3,5,5trimethylcyclohexylamine, quartz (silicon dioxide), 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1chloro-2,3-epoxypropane,, phenol, styrenated, phenol, methylstyrenated, Fatty acids, tall-oil, reaction products with bis-A, epichlorohydrin, glycidyl tolyl ether and TETA

HAZARD STATEMENTS

Corr. Resp.	EUH071	Corrosive to the respiratory tract.
Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Corr. 1B	H314-1B	Causes severe skin burns and eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher. **Endocrine disrupting properties - Ecotoxicity**

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

Name According to EFAECS No. CAS-No. REACH Reg No. Index NUmber	<u>%</u>	<u>Classifications</u>	SCL Value ATE Value M-Factor	
talc 238-877-9	10 - <25		SCL:	-
14807-96-6 - -			ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	

phenol, methylstyrenated 270-966-8 68512-30-1	10 - <25	H315-317-412 Aquatic Chronic 3, Skin Irrit. 2, Skin Sens. 1	SCL:	-
01-2119555274-38 -			ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	
quartz (silicon dioxide binded within a mineral structure) 238-878-4	2.5 - <10		SCL:	-
14808-60-7 - -			ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	
phenol, styrenated 262-975-0 61788-44-1	2.5 - <10	H315-317-411 Aquatic Chronic 2, Skin Irrit. 2, Skin Sens. 1	SCL:	-
01-2119980970-27 -			ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	

benzyl alcohol 202-859-9	2.5 - <10	H302-319-332 Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Eye Irrit. 2	SCL:	-
100-51-6				
01-2119492630-38 603-057-00-5			ATE:	1 620 mg/ kg (oral); >2 000 mg/kg (dermal); 1,5 mg/L
			M-Factor: (acute)	
			M-Factor: (chronic)	
xylene 215-535-7 1330-20-7	2.5 - <10	H226-304-312-315-319-332-335-373-412 Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2,	SCL:	-
01-2119488216-32 601-022-00-9		STOT RE 2, STOT SE 3 RTI	ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	
Fatty acids, tall-oil, reaction products with bis-A, epichlorohydrin, glycidyl tolyl ether and TETA 606-078-8	2.5 - <10	H315-317-318-400-410 Aquatic Acute 1, Aquatic Chronic 1, Eye Dam. 1, Skin Irrit. 2, Skin Sens. 1	SCL:	-
186321-96-0 01-2119983521-35			ATE:	-
-			M-Factor: (acute)	
			M-Factor: (chronic)	

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, 500-101-4	2.5 - <10	H314-317-412 Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1	SCL:	-
38294-64-3 01-2119965165-33 -			ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	
benzene-1,3-dimethanamine 216-032-5 1477-55-0	1.0 - <2.5	H302-314-317-332-412 Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Aquatic Chronic 3, Corr. Resp., Skin Corr. 1B, Skin Sens. 1B	SCL:	-
01-2119480150-50 -			ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	
quartz (silicon dioxide) - 14808-60-7	1.0 - <2.5	H372 STOT RE 1	SCL:	-
-			ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	

Propan-2-ol 200-661-7	1.0 - <2.5	H225-319-336 Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE	SCL:	-
67-63-0				
01-2119457558-25 603-117-00-0			ATE:	5840 mg/kg (oral); 12800 mg/kg (derm.); 10000 ppm 6h (inh.)
			M-Factor: (acute)	
			M-Factor: (chronic)	
ethylbenzene 202-849-4 100-41-4	1.0 - <2.5	H225-304-332-373-412 Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Flam. Liq. 2, STOT RE 2	SCL:	-
01-2119489370-35 601-023-00-4			ATE:	-
			M-Factor: (acute)	
			M-Factor: (chronic)	
Formaldehyde, polymer with N,N- dimethyl-1,3-propanediamine and phenol	1.0 - <2.5	H302-400-410 Acute Tox. 4 Oral, Aquatic Acute 1, Aquatic Chronic 1	SCL:	-
445498-00-0			ATE:	300.03 mg/kg (oral)
-			M-Factor: (acute)	
			M-Factor: (chronic)	

3-Aminomethyl-3,5,5- trimethylcyclohexylamine 220-666-8 2855-13-2	1.0 - <2.5	H302-312-314-317-318 Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A	SCL:	H317 ≥ 0.001 %
01-2119514687-32			ATE:	1030 mg/kg (oral); >5.01 m/ L (inh.); >2000 mg/L (derm.)
			M-Factor: (acute)	
			M-Factor: (chronic)	
2,4,6-tris(dimethylaminomethyl) phenol 202-013-9	1.0 - <2.5	H302-314-318 Acute Tox. 4 Oral, Eye Dam. 1, Skin Corr. 1C	SCL:	-
90-72-2 01-2119560597-27 603-069-00-0			ATE:	2 169 mg/kg (oral)
			M-Factor: (acute)	
			M-Factor: (chronic)	
salicylic acid 200-712-3 69-72-7	0.1 - <1.0	H302-318-361d Acute Tox. 4 Oral, Eye Dam. 1, Repr. 2	SCL:	-
01-2119486984-17 -			ATE:	891 mg/kg (oral); >2 000 kg/ kg (dermal)
			M-Factor: (acute)	
			M-Factor: (chronic)	

Remarks: CAS No. 68512-30-1 identified as EC No. 700-960-7 under REACH Registration

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Move to fresh air. Give oxygen or artificial respiration if needed. When risk of unconsciousness,

place and transport the victim in secured recovery position. Provide fresh air, rest and warmth. Call a physician immediately.

AFTER SKIN CONTACT: Use a mild soap if available. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Do not use solvent or thinners to clean skin.

AFTER EYE CONTACT: Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Causes burns. May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with noncombustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

6.4 Reference to other sections

Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Open drum carefully as content may be under pressure. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

Wash hallus before breaks and at the end of workday. When using, do not eat, unlik of

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in upright position only. Storage of flammable liquids. Store away from: oxidising materials, acids, and alkalis.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(EU)

Name	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
talc	14807-96-6				
phenol, methylstyrenated	68512-30-1				
quartz (silicon dioxide binded within a mineral structure)	14808-60-7				
phenol, styrenated	61788-44-1				
benzyl alcohol	100-51-6				
xylene	1330-20-7	50	100	442	221
Fatty acids, tall-oil, reaction products with bis- A, epichlorohydrin, glycidyl tolyl ether and TETA	186321-96-0				
4,4'-lsopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane,	38294-64-3				
benzene-1,3-dimethanamine	1477-55-0				
quartz (silicon dioxide)	14808-60-7				
Propan-2-ol	67-63-0				
ethylbenzene	100-41-4	100	200	884	442
Formaldehyde, polymer with N,N-dimethyl-1,3 propanediamine and phenol 3-Aminomethyl-3,5,5-trimethylcyclohexylamin					
	90-72-2				
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2 69-72-7				
salicylic acid	09-12-1				

Name	CAS-No.	OEL Note
talc	14807-96-6	
phenol, methylstyrenated	68512-30-1	
quartz (silicon dioxide binded within a minera structure)	l 14808-60-7	
phenol, styrenated	61788-44-1	
benzyl alcohol	100-51-6	
xylene	1330-20-7	Can be absorbed through the skin.
Fatty acids, tall-oil, reaction products with bis A, epichlorohydrin, glycidyl tolyl ether and TETA	- 186321-96-0	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane,	38294-64-3	
benzene-1,3-dimethanamine	1477-55-0	
quartz (silicon dioxide)	14808-60-7	
Propan-2-ol	67-63-0	
ethylbenzene	100-41-4	Can be absorbed through the skin.
Formaldehyde, polymer with N,N-dimethyl-1, propanediamine and phenol	3- 445498-00-0	
3-Aminomethyl-3,5,5-trimethylcyclohexylamir	ne 2855-13-2	
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	
salicylic acid	69-72-7	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

phenol, methylstyrenated	
EC No.:	CAS-No.:
270-966-8	68512-30-1

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							0.2 mg/kg bw/
Inhalation				1.4 mg/m3				day
Dermal				0.35 mg/kg bw/				0.35 mg/m3
				day				1.7 mg/kg bw/
					_			day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	14 μg/L
Fresh water sediments	1064 mg/kg dw
Marine water	1.4 μg/L
Marine sediments	106 mg/kg dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	212 mg/kg dw
Air	

Chemical Name:

phenol, styrenated	
EC No.:	CAS-No.:
262-975-0	61788-44-1

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local systemic effects local sy			systemic	local	systemic	effects local	systemic
Oral		Not required						
Inhalation		1.21 mg/n						
Dermal		2			_			
				day				

Environmental protection target	PNEC
Fresh water	11,5 μg/L
Fresh water sediments	1.564 mg/kg dw
Marine water	1.15 μg/L
Marine sediments	0.156 mg/kg dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	0.305 mg/kg dw
Air	

benzyl alcohol

EC No.: CAS-No.: 202-859-9 100-51-6

DNELs - Derived no effect level

		Wa	orkers		Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects	
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic	
Oral		Not required				20 mg/kg bw/	5 mg/kg bw/	4 mg/kg bw/day	
Inhalation		110 mg/m ³		22 mg/m3		day	day	5.4 mg/m3	
Dermal		40 mg/kg bw/		8 mg/kg bw/day		27 mg/m3		4 mg/kg bw/day	
		day			_	20 mg/kg bw/			
			_			day			

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	1 mg/L
Fresh water sediments	5.27 mg/kg wwt
Marine water	0.1 mg/L
Marine sediments	0.527 mg/kg wwt
Food chain	
Microorganisms in sewage treatment	39 mg/L
soil (agricultural)	0.456 mg/kg wwt
Air	

Chemical Name:

xylene	
EC No.:	CAS-No.:
215-535-7	1330-20-7

DNELs - Derived no effect level

		We	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required				174 mg/m ³	174 mg/m ³		1.6 mg/kg bw/
Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	77 mg/m ³			_	day
Dermal				180 mg/kg bw/				14.8 mg/m ³
				day				108 mg/kg bw/
								day

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

Fatty acids, tall-oil, reaction products with bis-A, epichlorohydrin, glycidyl tolyl ether and TETA

EC No.:	CAS-No.:
606-078-8	186321-96-0

DNELs - Derived no effect level

	-	Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							1.67 mg/kg bw/
Inhalation				23.5 mg/m3				day
Dermal				3.33 mg/kg bw/				5.8 mg/m3
				day				1.67 mg/kg bw/
					-			day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.186 ug/l
Fresh water sediments	0.005 mg/kg
Marine water	0.019 ug/l
Marine sediments	0.005 mg/kg
Food chain	
Microorganisms in sewage treatment	1.58 mg/l
soil (agricultural)	0.00089 mg/kg
Air	

Chemical Name:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane,

EC No.:	CAS-No.:
500-101-4	38294-64-3

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							0.05 mg/m3
Inhalation	0.493			0.493 mg/m3				0.074 mg/m3
Dermal				0.14 mg/kg				0.05 mg/m3

Environmental protection target	PNEC
Fresh water	0.011 mg/L
Fresh water sediments	4320 mg/kg
Marine water	0.001 mg/L
Marine sediments	432 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	864 mg/kg
Air	

benzene-1,3-dimethanamine

EC No.:	CAS-No.:
216-032-5	1477-55-0

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required					
Inhalation		0.2 mg/m ³ 1.2 m						
Dermal	0.3			0.33 mg/kg bw/				
				day				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.094 mg/L
Fresh water sediments	12.4 mg/kg
Marine water	0.0094 mg/L
Marine sediments	1.24 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/L
soil (agricultural)	0.045 mg/kg
Air	

Chemical Name:

Propan-2-ol	
EC No.:	CAS-No.:
200-661-7	67-63-0

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required						26 mg/kg bw/day
Inhalation	500 mg/m3							89 mg/m3
Dermal	888 m			888 mg/kg				319 mg/kg bw/
								day

Environmental protection target	PNEC
Fresh water	140.9 mg/l
Fresh water sediments	552 mg/kg
Marine water	140.9 mg/l
Marine sediments	552 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	28 mg/kg
Air	

ethylbenzene EC No.: 202-849-4

CAS-No.: 100-41-4

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required						1.6 mg/kg bw/
Inhalation	293 mg/m3			77 mg/m3				day
Dermal				180 mg/kg bw/				15 mg/m3
				day				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.1 mg/L
Fresh water sediments	13.7 mg/kg
Marine water	0.01 mg/L
Marine sediments	1.37 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	2.68 mg/kg
Air	

Chemical Name:

3-Aminomethyl-3,5,5-trimethylcyclohexylamine

EC No.:	CAS-No.:
220-666-8	2855-13-2

DNELs - Derived no effect level

	Workers				Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects	
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic	
Oral	Not required							0.526 mg/kg	
Inhalation	0.073 mg/m3		0.073 mg/m3						
Dermal									

Environmental protection target	PNEC
Fresh water	0.06 mg/l
Fresh water sediments	5.784 mg/kg
Marine water	0.006mg/l
Marine sediments	0.578 mg/kg (dry weight)
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	1.121 mg/kg (dry weight)
Air	

2,4,6-tris(dimethylaminomethyl)phenol

EC No.:	CAS-No.:
202-013-9	90-72-2

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect Acute effects Chronic Chronic effects				Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required					0.13 mg/m3		0.075 mg/kg
Inhalation		2.1 mg/m3	4.9 mg/m3	0.53 mg/m3		0.075 mg/kg		0.13 mg/m3
Dermal	0.6 mg/kg 0.150 mg/kg							0.075 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.046 mg/l
Fresh water sediments	
Marine water	0.005 mg/l
Marine sediments	
Food chain	
Microorganisms in sewage treatment	0.2 mg/l
soil (agricultural)	0.025 mg/kg
Air	

Chemical Name:

salicylic acid	
EC No.:	CAS-No.:
200-712-3	69-72-7

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required				4 mg/kg bw/	0.0002 mg/L	1 mg/kg bw/day
Inhalation		5 mg/m3 5 mg/m				day		4 mg/m3
Dermal	2.3 mg/			2.3 mg/kg bw/	_	· · ·	_	1 mg/kg bw/day
				dav				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.20 mg/L
Fresh water sediments	1.42 mg/kg dw
Marine water	0.020 mg/L
Marine sediments	0.142 mg/kg dw
Food chain	
Microorganisms in sewage treatment	162 mg/L
soil (agricultural)	0.166 mg/kg dw
Air	

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Wear respiratory protection with combination filter (dust and gas filter, EN 14387:2004 +A1:2008) during spraying operations: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust). When working in confined or poorly ventilated spaces, a battery powered assisted air-fed mask must be used.

EYE PROTECTION: Face-shield. Safety glasses with side-shields conforming to EN166.

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Use chemical resistant gloves and lotions and barrier creams to prevent

drying of the skin. Protective gloves complying with EN 374: Nitrile rubber. Butyl rubber. Viton®. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Thickness >= 0,5 mm; breakthrough time >=480 min.

BODY PROTECTION: Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

SE	SECTION 9: Physical and Chemical Properties					
9.1	Information on basic physical and chemical Colour	properties Off-white				
	Physical State	Liquid				
	Odor	Solvent				
	Odor threshold	Not determined				
	рН	Not determined				
	Melting point / freezing point (°C)	Not determined				
	Boiling point or initial boiling point and boiling range (°C)	82 - 152				
	Flash Point, (°C)	26				
	Evaporation rate	Not determined				
	Flammability (solid, gas)	Not determined				
	Lower and upper explosive limit	1.0 - 12.0				
	Vapour Pressure	Not determined				
	Relative vapour density	>1 (air = 1)				
	Density and/or relative density	1.47 - 1.57				
	Solubility in / Miscibility with water	Negligible				
	Partition coefficient: n-octanol/water	Not determined				
	Auto-ignition temperature (°C)	425				
	Decomposition temperature (°C)	Not determined				
	Kinematic viscosity	90 - 100 KU				
	Particle characteristics	Not applicable to liquids				
9.2	Other information					
	VOC Content g/I:	110				
	Grams of VOC per liter of coating product a	s applied per ISO 11890-1 and/or ISO 11890-2.				
	Specific Gravity (g/cm3) 1.54					

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under recommended storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No reactivity hazards known under recommended storage and use conditions.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Keep away from strong oxidising agents and strongly acid or alkaline materials.

10.6 Hazardous decomposition products

In case of fire or hot work operations, hazardous decomposition products may be formed such as:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), aliphatic amines, aldehydes, cyanides.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute Toxicity:	
Oral LD50:	No information available on the product itself as the product is not tested.
Inhalation LC50:	No information available on the product itself as the product is not tested.
Dermal LD50:	No information available on the product itself as the product is not tested.
Irritation:	No information available.
Corrosivity:	Corrosive to eyes and skin.
Sensitization:	May cause an allergic skin reaction.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	Central nervous system depression.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
68512-30-1	phenol, methylstyrenated	>2000 mg/kg (oral-rat)	>2000 mg/kg (dermal-rat)	No information	No information	No information
61788-44-1	phenol, styrenated	>2000 mg/kg (Oral-rat)	>2000 mg/kg (Dermal-rat)	No information	No information	No information

Date Printed: 11/10/2023

100-51-6	benzyl alcohol	1620 mg/kg rat	>2000 mg/kg, rabbit	No information	No information	>4.178 mg/L (4h/ rat, mist)
1330-20-7	xylene	>2000 mg/kg (oral-rat)	1100 mg/kg (ATE dermal- rabbit)	11 mg/L (ATE inh/vapour)	4500 ppmV (ATE inh - Gas)	1.5 mg/L (ATE inh/dust/mist)
1477-55-0	benzene-1,3-dimethanamine	980 mg/kg (oral, rat)	>2000 mg/kg (dermal, rabbit)	No information	No information	1.34 mg/L
67-63-0	Propan-2-ol	5840 mg/kg (oral, rat)	12800 mg/kg (dermal, rabbit)	>25 mg/L (inhalation, vapor, rat)	No information	No information
100-41-4	ethylbenzene	3500 mg/kg rat, oral	5001 mg/kg, rabbit	17.2 mg/L. rat, 4h	10000 ppm	1.5 mg/L
445498-00-0	Formaldehyde, polymer with N,N-dimethyl-1,3- propanediamine and phenol	>300 mg/kg (LD50 Oral, rat F)	No information	No information	No information	No information
2855-13-2	3-Aminomethyl-3,5,5- trimethylcyclohexylamine	1030 mg/kg (oral-rat)	2000 mg/kg (dermal-rabbit)	No information	No information	>5.01 mg/L (inhal., dust/mist, rat)
90-72-2	2,4,6-tris (dimethylaminomethyl)phenol	2169 mg/kg (oral, rat)	No information	No information	No information	No information
69-72-7	salicylic acid	891 mg/kg (oral-rat)	>2000 mg/kg (dermal-rat)	900 mg/m3 (1 hr-inh-rat)	No information	No information

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Respiration of solvent vapour may cause dizziness. Corrosive - causes irreversible eye damage. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Chronic exposure causes drying effect on the skin and eczema. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Corrosive to skin. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin. Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs.

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 12: Ecological Information

12.1 Toxicity:

	EC50 48hr (Daphnia): IC50 72hr (Algae): LC50 96hr (fish):	No information No information No information
12.2	Persistence and degradability:	No information
12.3	Bioaccumulative potential:	No information
12.4	Mobility in soil:	No information

12.5 Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Ecotoxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

12.7 Other adverse effects:

No information available on the product itself as the product is not tested.

CAS-No.	Name According to EEC	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
68512-30-1	phenol, methylstyrenated	14 - 51 mg/L (daphnia)	15 mg/L (algae)	25.8 mg/L (fish)
61788-44-1	phenol, styrenated	1-10 mg/L (EL50, daphnia OECD 202)	3.14 mg/L (ErL50, algae, OECD 201)	14.8 mg/L (LL50, OECD 203)
100-51-6	benzyl alcohol	230 mg/L (Daphnia Magna)	770 mg/L (EgC50, Selenastrum capricornutum)	10 mg/L (Lepomis macrochirus)
1330-20-7	xylene	1 - 5 mg/L (Daphnia magna)	3 - 5 mg/L (Selenastrun sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrichirus), 21.0 mg/L (Pimephales promelas)
186321-96-0	Fatty acids, tall-oil, reaction products with bis- A, epichlorohydrin, glycidyl tolyl ether and TETA	0.705 mg/L (Daphnia magna)	0.186 mg/L (Selenastrum capricornutum, ErC50)	1.806 mg/L (Oncorhynchus mykiss)
1477-55-0	benzene-1,3-dimethanamine	15.2 mg/L (Daphnia magna)	32.1 mg/L (EC50, Selenastrum capricornutum)	87.6 mg/L (Oryzias latipes)
67-63-0	Propan-2-ol	9714 mg/L (Daphnia magna, 24h)	>100 mg/L (Scenedesmus subspicatus, EC50)	9640 mg/L (Pimephales promelas)
100-41-4	ethylbenzene	1.8 - 2.4 mg/L (Daphnia magna)	5.4 mg/L (Pseudokirchneriella subcapitata)	4.2 mg/L (Oncorhynchus mykissl)
445498-00-0	Formaldehyde, polymer with N,N- dimethyl-1,3-propanediamine and phenol	24 mg/L (Daphnia, EC50, 48h, static)	>0.219 mg/L (Algae, EC50, 72h, static)	40 mg/L (fish, LC50, 96h, static)
2855-13-2	3-Aminomethyl-3,5,5- trimethylcyclohexylamine	23 mg/L (Daphnia magna)	37 mg/L (EC50, Desmodesmus subspicatus)	110 mg/L (Leuciscus idus)
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	718 mg/L (EC50, 96h, Palaeomonetes vulgaris)	84 mg/L (EC50, 72h, Desmodesmus subspicatus)	175 mg/L (LC50, 96h, Cyprinus carpio)
69-72-7	salicylic acid	870 mg/L (Daphnia magna)	>100 mg/L (EC50, Desmodesmus subspicatus)	1370 mg/L (Pimephales promelas)

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Rags/wiping cloths and the like, moistened with flammable liquids, must be discarded into designated fireproof buckets. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

European Waste Code:	08 01 11*
Packaging Waste Code:	15 01 10*

SECTION 14: Transport Information

		ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1	UN-number or ID number	UN3469	UN3469	UN3469	UN3469
14.2	UN proper shipping name	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE
14.3	Transport Hazard Class(es)	3,8	3,8	3,8	3,8
14.4	Packing Group	111	111	Ш	111
14.5	Enviromental Hazards	Marine pollutant: Yes (Fatty acids, tall-oil, reaction products with bis-A, epichlorohydrin, glycidyl tolyl ether and TETA)	Marine pollutant: Yes (Fatty acids, tall-oil, reaction products with bis-A, epichlorohydrin, glycidyl tolyl ether and TETA)	Marine pollutant: Yes (Fatty acids, tall-oil, reaction products with bis-A, epichlorohydrin, glycidyl tolyl ether and TETA)	Marine pollutant: Yes (Fatty acids, tall-oil, reaction products with bis-A, epichlorohydrin, glycidyl tolyl ether and TETA)

14.6 Special precautions for user No Information EmS-No.: F-E, S-C

14.7 Maritime transport in bulk according to **IMO instruments**

No Information

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:		
Denmark Product Registration Number:	Not available	
Danish MAL Code:	2 - 5	
Danish MAL Code - Mixture:	2 - 5	
Sweden Product Registration Number:	Not available	
Norway Product Registration Number:	P-92428	

WGK Class:

3

Covered by Directive 2012/18/EC (Seveso III): P5c, E2

Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006: Entry 3, 40

Annex XIV - Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

TEXTION OLI	nazaru Otatements snown in Section 5 describing each ingredient.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

Changes have been made to Section 3 of the Safety Data Sheet (SDS). Please refer to the Composition / Information on Ingredients in Section 3 of this SDS. Changes have been made to Section 8 of the Safety Data Sheet (SDS). Please refer to the Exposure Controls / Personal Protection information in Section 8 of the SDS. .

List of References

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark

Date Printed: 11/10/2023

- Joint Research Centre in Ispra, Italy
- Regulation (EC) 1272/2008 with subsequent amendments
- Regulation (EC) 1907/2006 with subsequent amendments
- Commission Regulation (EU) 2020/878
- Eu Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
	Parts per million
ppm ma (m2	Milligrams per cubic meter
mg/m3 TLV	Threshold Limit Value
ACGIH	
OSHA	American Conference of Governmental Industrial Hygienists Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l ma/ka	Grams per liter milligrams per kilogram
mg/kg N/A	
LD50	Not applicable Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal effective concentration Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
VPVB	Very persistent and very bioaccumulative
EEC	
ADR	European Economic Community
RID	International Transport of Dangerous Goods by Road
UN	International Transport of Dangerous Goods by Rail United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified
TDO	by the Protocol of 1978 International Bulk Container
IBC RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	
IMO Note P:	International Maritime Organization The classification as a carcinogen or mutagen need not apply; the substance contains
NOLE F:	less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in powder
	form containing 1 $\%$ or more of titanium dioxide which is in the form of or
	incorporated in particles with aerodynamic diameter \leq 10 µm.

For further information, please contact: Regulatory Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product.

It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.