



Safety Data Sheet
according to Regulation (EC)
No. 2020/878

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Identifier	B034	Revision Date:	28/11/2024
Product Name:	HYDROPLATE 1914 PART A	Supersedes Date:	08/01/2024
		Version Number:	3

UFI Code: N094-90R1-E00M-GDXD

Contain nanoform: No

1.2 Relevant identified uses of the substance or mixture and uses advised against Base component of 2 components coating - Industrial use.
 Advised against: others than recommended

Product to be mixed with: HYDROPLATE 1914 PART B
Mixing ratio by volume Part A/ Part B: 2:1

1.3 Details of the supplier of the safety data sheet

Manufacturer: Carboline Norge AS
 Postboks 593
 3412 Lierstranda
 Norway

Regulatory / Technical Information:
 +47 32 85 73 00
 +47 32 85 74 00

Datasheet Produced by: Tarka, Malgorzata - hms@carboline.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)
 112 (24/7)
 Croatia +3851 2348 342 (24/7 in Croatian and English)
 Iceland 112 (24/7)
 Malta 112 (24/7)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

EU Other	EUH205
EU Other	EUH211
Skin Irrit. 2	H315
Skin Sens. 1	H317
Eye Dam. 1	H318
Acute Tox. 4 Inhalation	H332
Aquatic Chronic 2	H411

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, 1,4-Bis(2,3-epoxypropoxy)butane, [3-(2,3-epoxypropoxy)propyl]trimethoxysilane, Epoxy Phenol Novolac Resin

HAZARD STATEMENTS

EU Other	EUH205	Contains epoxy constituents. May produce an allergic reaction.
EU Other	EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Skin Irrit. 2	H315	Causes skin irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Eye Dam. 1	H318	Causes serious eye damage.
Acute Tox. 4 Inhalation	H332	Harmful if inhaled.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container to waste treatment/disposal facility in accordance with local, state, and federal regulations.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

Endocrine disrupting properties - Ecotoxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 3: Composition/Information On Ingredients**3.1 Substances**

Not applicable

3.2 Mixtures**Hazardous ingredients**

<u>Name According to EEC</u> <u>EINECS No.</u> <u>CAS-No.</u> <u>REACH Reg No.</u> <u>Index Number</u>	<u>%</u>	<u>Classifications</u>	SCL Value ATE Value M-Factor
Epoxy Phenol Novolac Resin 500-006-8 9003-36-5 01-2119454392-40 -	25 - <50	H315-317-411 Aquatic Chronic 2, Skin Irrit. 2, Skin Sens. 1	SCL: - ATE: - M-Factor: (acute) M-Factor: (chronic)

barium sulfate 231-784-4 7727-43-7 01-2119491274-35 -	10 - <25		SCL: ATE: M-Factor: (acute) M-Factor: (chronic)	- -
2,2-bis-[4-(2,3-epoxipropoxy)phenyl]propane 216-823-5 1675-54-3 01-2119456619-26 603-073-00-2	10 - <25	H315-317-319-411 Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	SCL: ATE: M-Factor: (acute) M-Factor: (chronic)	H319 ≥ 5 H315 ≥ 5 -
1,4-Bis(2,3-epoxypropoxy)butane 219-371-7 2425-79-8 01-2119494060-45 -	10 - <25	H302-312-315-317-318-332-412 Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Aquatic Chronic 3, Eye Dam. 1, Skin Irrit. 2, Skin Sens. 1	SCL: ATE: M-Factor: (acute) M-Factor: (chronic)	- 1163 mg/kg (oral); 11 mg/L (inh.); 1100 mg/kg (derm.)

titanium dioxide 236-675-5 13463-67-7 01-2119489379-17 -	2.5 - <10		SCL: ATE: M-Factor: (acute) M-Factor: (chronic)	- -
talc 238-877-9 14807-96-6 - -	2.5 - <10		SCL: ATE: M-Factor: (acute) M-Factor: (chronic)	- -
[3-(2,3-epoxypropoxy)propyl] trimethoxysilane 219-784-2 2530-83-8 01-2119513212-58 -	1.0 - <2.5	H318-412 Aquatic Chronic 3, Eye Dam. 1	SCL: ATE: M-Factor: (acute) M-Factor: (chronic)	- -

Remarks: CAS No. 9003-36-5 identified as EC No. 701-263-0 under REACH Registration
CAS No 13463-67-7: Note 10

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Move to fresh air. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position. Provide fresh air, rest and warmth. Call a physician immediately.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air.

Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment.

6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

6.4 Reference to other sections

Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Apply technical measures to comply with the occupational exposure limits (see section 8). People handling polyurethane or epoxy products must have received special training according to guidelines from the National Occupational Health and Safety Board.

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in upright position only. Store away from: oxidising materials, acids, and alkalis.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
Epoxy Phenol Novolac Resin	9003-36-5				
barium sulfate	7727-43-7				
2,2-bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3				
1,4-Bis(2,3-epoxypropoxy)butane	2425-79-8				
titanium dioxide	13463-67-7				
talc	14807-96-6				
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8				

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
Epoxy Phenol Novolac Resin	9003-36-5	
barium sulfate	7727-43-7	
2,2-bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	
1,4-Bis(2,3-epoxypropoxy)butane	2425-79-8	
titanium dioxide	13463-67-7	
talc	14807-96-6	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

Chemical Name:

Epoxy Phenol Novolac Resin

EC No.:

500-006-8

CAS-No.:

9003-36-5

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							6.25 mg/kg
Inhalation				29.39 mg/m3				8.7 mg/m3
Dermal	0.0083 mg/cm2			104.15 mg/kg				62.5 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.003 mg/L
Fresh water sediments	0.294 mg/kg
Marine water	0.0003 mg/L
Marine sediments	0.0294 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/L
soil (agricultural)	0.237 mg/kg
Air	

Chemical Name:

barium sulfate

EC No.:

231-784-4

CAS-No.:

7727-43-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation								
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	115 µg/L
Fresh water sediments	600.4 mg/kg sediment dw
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	207.7 mg/kg soil dw
Air	

Chemical Name:

2,2-bis-[4-(2,3-epoxipropoxy)phenyl]propane

EC No.:

216-823-5

CAS-No.:

1675-54-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					0.75 mg/kg bw/day		0.75 mg/kg bw/day
Inhalation		12.25 mg/m3		12.25 mg/m3				
Dermal		8.33 mg/kg bw/day		8.33 mg/kg bw/day		3.571 mg/kg bw/day		3.571 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.006 mg/L
Fresh water sediments	0.996 mg/kg
Marine water	0.0006 mg/L
Marine sediments	0.0996 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/L
soil (agricultural)	0.196 mg/kg
Air	

Chemical Name:

1,4-Bis(2,3-epoxypropoxy)butane

EC No.:

219-371-7

CAS-No.:

2425-79-8

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							0.33 mg/kg
Inhalation				4.7 mg/m3				1.16 mg/m3
Dermal				6.66 mg/kg				3.33 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.024 mg/L
Fresh water sediments	0.084 mg/kg
Marine water	0.002 mg/L
Marine sediments	0.008 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	0.003 mg/kg
Air	

Chemical Name:

titanium dioxide

EC No.:

236-675-5

CAS-No.:

13463-67-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required						10 mg/m ³	700 mg/kg/ bw/ day
Inhalation			10 mg/m ³					
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.127 mg/L
Fresh water sediments	1000 mg/kg dw
Marine water	1 mg/L
Marine sediments	100 mg/kg dw
Food chain	1667 mg/kg (oral)
Microorganisms in sewage treatment	100 mg/kg
soil (agricultural)	100 mg/kg dw
Air	

Chemical Name:

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

EC No.:

219-784-2

CAS-No.:

2530-83-8

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					26 400 mg/m ³		5 mg/kg bw/day
Inhalation				70.5 mg/m ³				17 mg/m ³
Dermal				10 mg/kg bw/day				5 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	450 µg/l
Fresh water sediments	1,6 mg/kg sediment dw
Marine water	45 µg/l
Marine sediments	160 µg/kg sediment dw
Food chain	
Microorganisms in sewage treatment	8.2 mg/l
soil (agricultural)	63 µg/kg soil dw
Air	

8.2 Exposure controls**Personal Protection**

RESPIRATORY PROTECTION: Wear a battery powered assisted air-fed mask during spraying operations and long-term exposure. When working in confined or poorly ventilated spaces, a battery powered assisted air-fed mask must be used. When painting small areas, or when using a roller or brush, respiratory protection with combination filter (dust and gas filter, EN 14387:2004+A1:2008) may be used: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust).

EYE PROTECTION: If splashes are likely to occur, wear: Face-shield, tightly fitting safety goggles (EN 166).

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Use chemical resistant gloves and lotions and barrier creams to prevent

drying of the skin. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

BODY PROTECTION: Long sleeved clothing.
Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Colour	Misc. colours
Physical State	LIQUID
Odor	Faint
Odor threshold	Not determined
pH	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point or initial boiling point and boiling range (°C)	>200
Flash Point, (°C)	>200
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Lower and upper explosive limit	Not determined
Vapour Pressure	Not determined
Relative vapour density	>1 (air = 1)
Density and/or relative density	1.55 - 1.65
Solubility in / Miscibility with water	Negligible
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not applicable
Decomposition temperature (°C)	Not determined
Kinematic viscosity	110 - 130 KU
Particle characteristics	Not applicable to liquids

9.2 Other information

VOC Content g/l: 0

Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.

Specific Gravity (g/cm³) 1.57

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No reactivity hazards known under normal storage and use conditions.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Keep away from strong oxidising agents and strongly acid or alkaline materials.

10.6 Hazardous decomposition products

In case of fire or hot work operations, hazardous decomposition products may be formed such as: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), aliphatic amines, aldehydes.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute Toxicity:

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Dermal LD50: No information available on the product itself as the product is not tested.

Irritation: Irritating to skin.

Corrosivity: Causes serious eye damage.

Sensitization: May cause an allergic skin reaction.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
9003-36-5	Epoxy Phenol Novolac Resin	>5000 mg/kg (rat, oral)	>2000 mg/kg (rat, dermal)	No information	No information	No information
7727-43-7	barium sulfate	No Information	>2000 mg/kg bw (rat)	No information	No information	No information

1675-54-3	2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane	>2000 mg/kg (oral-rat)	>2000 mg/kg (dermal-rabbit)	No information	No information	No information
2425-79-8	1,4-Bis(2,3-epoxypropoxy)butane	1410 mg/kg (rat)	1100 mg/kg	11 mg/L	No information	1.5 mg/L
13463-67-7	titanium dioxide	>5000 mg/kg (oral-rat)	10000 mg/kg	No information	No information	>6.82 mg/L (inh-rat-4h)
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	8025 mg/kg (oral-rat)	4250 mg/kg (dermal-rabbit)	>5300 mg/L (inh/4h/aerosols/rat)	No information	No information

Additional Information:

Chronic exposure causes drying effect on the skin and eczema. Repeated skin contact leads to irritation and to sensitisation, possible with cross-sensitisation to other epoxies. The product is irritating to the eyes and may cause sensitisation to the respiratory system. Swallowing concentrated chemical may cause severe internal injury. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs.

11.2 Information on other hazards**Endocrine disrupting properties - Toxicity**

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 12: Ecological Information**12.1 Toxicity:**

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

12.6 Endocrine disrupting properties**Endocrine disrupting properties - Ecotoxicity**

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

12.7 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
9003-36-5	Epoxy Phenol Novolac Resin	2.55 mg/L (Daphnia magna)	1.8 mg/L (Selenastrum capricornutum, EC50, 72hr)	2.54 mg/L (Fish)

1675-54-3	2,2-bis-[4-(2,3-epoxipropoxy)phenyl]propane	2.7 mg/L (Daphnia magna)	9.4 mg/L (EC50, Selenastrum capricornutum)	1.5 mg/L (Oncorhynchus mykiss)
2425-79-8	1,4-Bis(2,3-epoxypropoxy)butane	No information	>160 mg/L (Pseudokirchneriella subcapitata)	19.8 mg/L (Danio rerio)
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)	16 mg/l (EC50, 72h, Pseudokirchnerella subcapitata)	>100 mg/l (EC50, 96h, Oncorhynchus Mykiss OECD203)
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	324 mg/L (Daphnia magna)	No information	55 mg/L (cyprinus carpio)

SECTION 13: Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

European Waste Code: 08 01 11*

Packaging Waste Code: 15 01 10*

SECTION 14: Transport Information

	ADR/RID	ADN	IMDG	IATA
14.1 UN-number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, bisphenol F epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, bisphenol F epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, bisphenol F epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, bisphenol F epoxy resin)
14.3 Transport Hazard Class(es)	9	9	9	9
14.4 Packing Group	III	III	III	III
14.5 Environmental Hazards	Marine Pollutant: Yes (Bisphenol A epoxy resin, Bisphenol F epoxy resin)	Marine Pollutant: Yes (Bisphenol A epoxy resin, Bisphenol F epoxy resin)	Marine Pollutant: Yes (Bisphenol A epoxy resin, Bisphenol F epoxy resin)	Marine Pollutant: Yes (Bisphenol A epoxy resin, Bisphenol F epoxy resin)

14.6 Special precautions for user Not applicable
EmS-No.: F-E, S-E

14.7 Maritime transport in bulk according to IMO instruments Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available
Danish MAL Code: 2 - 5
Danish MAL Code - Mixture: Not available
Sweden Product Registration Number: Not available
Norway Product Registration Number: P-92427
WGK Class: 3

Covered by Directive 2012/18/EC (Seveso III): E2
Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006: Entry 3

Annex XIV - Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information**Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes. . . This safety data sheet (SDS) applies to several colours and is based on the colour with the most stringent classification. Thus, for some colours, there may be a different classification than the one given in section 2.2 in this SDS.

List of References

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark
- Joint Research Centre in Ispra, Italy
- Regulation (EC) 1272/2008 with subsequent amendments
- Regulation (EC) 1907/2006 with subsequent amendments
- Commission Regulation (EU) 2020/878
- Eu Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key

CLP Classification, Labeling & Packaging Regulation

EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

For further information, please contact: Regulatory Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.