

Safety Data Sheet according to Regulation (EC) 'No. 2020/878

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Identifier J178B Revision Date: 19/10/2023

Product Name: SP-2884 HARDENER BLUE - B Supersedes Date: 22/06/2023

Version Number: 3

UFI Code: 599K-P13Y-400X-T2M6

Contain nanoform:

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Hardener for 2 components coatings - Industrial use. Please see Technical Data

Sheet. Advised against: others than recommended

Product to be mixed with: SP-2884 BASE YELLOW - A

Mixing ratio by volume Part A/

Part B:

1/1

1.3 Details of the supplier of the safety data sheet

Supplier: Carboline Italia, S.p.a.

Via Margherita Viganò De Vizzi, 77 20092 Cinisello Balsamo (MI)

Italy

Regulatory / Technical Information: +32 67493710 Nivelles, Belgium

+39 0294759236 Cinisello Balsamo, Italy

Datasheet Produced by: Calcagno, Elena - hms@carboline.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)

112 (24/7)

Croatia +3851 2348 342 (24/7 in Croatian and English)

Iceland 112 (24/7) Malta 112 (24/7)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 3	H226
Acute Toxicity, Oral, category 4	H302
Acute Toxicity, Dermal, category 4	H312
Skin Corrosion, category 1B	H314-1B
Skin Sensitizer, category 1	H317
Acute Toxicity, Inhalation, category 4	H332
STOT, repeated exposure, category 1	H372
Hazardous to the aquatic environment, Chronic, category 2	H411

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

2,4,6-tris(dimethylaminomethyl)phenol, 4-tert-Butylphenol, Benzyl alcohol, 2-piperazin-1-ylethylamine, 1,2-cyclohexanediamine, reaction mass ethylbenzene - xylene, xylene, quartz (silicon dioxide), Propylidynetrimethanol, propoxylated, reaction products with ammonia

H226

HAZARD STATEMENTS

Flammable Liquid, category 3

Acute Toxicity, Oral, category 4	H302	Harmful if swallowed.
Acute Toxicity, Dermal, category 4	H312	Harmful in contact with skin.
Skin Corrosion, category 1B	H314-1B	Causes severe skin burns and eye damage.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

Flammable liquid and vapour.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Name According to EEC CAS-No.

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.

4-tert-Butylphenol 98-54-4

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

Name According to EEC EINEC No. CAS-No. REACH Reg No.	<u>%</u>	<u>Classifications</u>	,	SCL Value: ATE Value: M-Factor:
quartz (silicon dioxide) 238-878-4	50 - <75	H372	SCL Value:	-
14808-60-7			ATE Value:	-
No Information		STOT RE 1	M-Factor: (acute)	-
			M-Factor: (chronic)	-
Propylidynetrimethanol, propoxylated, reaction products with ammonia	10 - <25	H302-312-314-318-411	SCL Value:	-
500-105-6			ATE Value:	-
39423-51-3		Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Aquatic Chronic 2, Skin Corr. 1B		
01-2119556886-20			M-Factor: (acute)	-
			M-Factor: (chronic)	-

 Benzyl alcohol	2.5 - <10	H302-319-332	SCL Value:	-
202-859-9			002 (4,40.	
100-51-6			ATE Value:	-
01-2119492630-38		Acute Tox. 4 Inhalation, Acute Tox. 4 Oral,		
603-057-00-5		Eye Irrit. 2	M-Factor: (acute)	-
			M-Factor: (chronic)	-
glass oxide 266-046-0	2.5 - <10		SCL Value:	-
65997-17-3			ATE Value:	-
No Information			M-Factor: (acute)	-
			M-Factor: (chronic)	-
2,4,6-tris(dimethylaminomethyl) phenol	2.5 - <10	H302-314	SCL Value:	-
202-013-9 90-72-2			ATE Value:	-
No Information		Acute Tox. 4 Oral, Skin Corr. 1C		
603-069-00-0			M-Factor: (acute)	-
			M-Factor: (chronic)	-
1,2-cyclohexanediamine 211-776-7	2.5 - <10	H302-312-314-317-332-335	SCL Value:	-
694-83-7			ATE Value:	-
No Information		Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Skin Corr. 1A, Skin Sens. 1, STOT SE 3 RTI	M-Factor: (acute)	-
			M-Factor: (chronic)	-

4-tert-Butylphenol	2.5 - <10	H315-318-361F-410	SCL Value:	_
202-679-0			002 (4.40.	
98-54-4			ATE Value:	-
01-2119489419-21		Aquatic Chronic 1, Eye Dam. 1, Repr. 2, Skin Irrit. 2	M-Factor: (acute)	1
			M-Factor: (chronic)	-
2-piperazin-1-ylethylamine 205-411-0	1.0 - <2.5	H302-311-314-317-361FD-372-412	SCL Value:	-
140-31-8			ATE Value:	-
01-2119471486-30		Acute Tox. 3 Dermal, Acute Tox. 4 Oral, Aquatic Chronic 3, Repr. 2, Skin Corr. 1B, Skin Sens. 1, STOT RE 1	M-Factor: (acute)	-
			M-Factor: (chronic)	-
reaction mass ethylbenzene - xylene	0.1 - <1.0	H226-304-312-315-319-332-335-373	SCL Value:	-
905-588-0			ATE Value:	-
01-2119539452-40		Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2, STOT RE 2, STOT SE 3 RTI	M-Factor: (acute)	-
			M-Factor: (chronic)	-
xylene 215-535-7	0.1 - <1.0	H226-304-312-315-319-332-335-373-412	SCL Value:	-
1330-20-7			ATE Value:	-
01-2119488216-32 601-022-00-9		Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2, STOT RE 2, STOT SE 3 RTI	M-Factor: (acute)	-
			M-Factor: (chronic)	-

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Move to fresh air. Provide fresh air, rest and warmth. Call a physician immediately. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position. AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin. AFTER EYE CONTACT: Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure. Harmful by inhalation, in contact with skin and if swallowed. Vapours may cause drowsiness and dizziness. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11. When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Open drum carefully as content may be under pressure. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in upright position only. Storage of flammable liquids. Store away from: oxidising materials, acids, and alkalis.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	CAS-No.		LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
quartz (silicon dioxide)	14808-60-7					
Propylidynetrimethanol, propoxylated, reaction products with ammonia	39423-51-3					
Benzyl alcohol	100-51-6					
glass oxide	65997-17-3					
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2					
1,2-cyclohexanediamine	694-83-7					
4-tert-Butylphenol	98-54-4					
2-piperazin-1-ylethylamine	140-31-8					
reaction mass ethylbenzene - xylene						
xylene	1330-20-7		50	100	442	221
<u>Name</u>	CAS-No.	OEL Note				
quartz (silicon dioxide)	14808-60-7					
Propylidynetrimethanol, propoxylated, reaction products with ammonia	39423-51-3					
Benzyl alcohol	100-51-6					
glass oxide	65997-17-3					
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2					

1,2-cyclohexanediamine 694-83-7

4-tert-Butylphenol 98-54-4

2-piperazin-1-ylethylamine 140-31-8

reaction mass ethylbenzene - xylene

xylene 1330-20-7 Sk

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

Chemical Name:

Propylidynetrimethanol, propoxylated, reaction products with ammonia

EC No.: CAS-No.: 500-105-6 39423-51-3

DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required					•		
Inhalation	14 mg			14 mg/m³				0.8 mg/kg bw/
								day
Dermal				1.6 mg/kg bw/				3.48 mg/m ³
				dav				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.0044 mg/l
Fresh water sediments	0.02 mg/kg
Marine water	0.00044 mg/l
Marine sediments	0.002 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/l-sewage treatment
soil (agricultural)	0.002 mg/kg
Air	

Chemical Name:

Benzyl alcohol

EC No.: CAS-No.: 202-859-9 100-51-6

DNELs - Derived no effect level

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required				20 mg/Kg bw/	5 mg/kg bw/	4 mg/kg bw/day
· ·				day	day			
Inhalation		110 mg/m ³		22 mg/m3		27 mg/m3		5.4 mg/m3
Dermal		40 mg/kg bw/		8 mg/kg bw/day		20 mg/kg bw/		4 mg/kg bw/day
		day				day		

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	1 mg/L
Fresh water sediments	5.27 mg/kg wwt
Marine water	0.1 mg/L
Marine sediments	0.527 mg/kg wwt
Food chain	
Microorganisms in sewage treatment	39 mg/L
soil (agricultural)	0.456 mg/kg wwt
Air	

Chemical Name:

glass oxide

EC No.: CAS-No.: 266-046-0 65997-17-3

DNELs - Derived no effect level

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							
Inhalation			•					
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	6.5 μg/L
Fresh water sediments	174 mg/kg sediment dw
Marine water	3.4 μg/L
Marine sediments	164 mg/kg sediment dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	147 mg/kg soil dw
Air	

Chemical Name:

1,2-cyclohexanediamine

EC No.: CAS-No.: 211-776-7 694-83-7

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect Acute effects Chronic Chronic effects			Acute effect	Acute effects	Chronic	Chronic effects	
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							
Inhalation	0,5 mg/m3	0,5 mg/m3	0,25 mg/m3	0,25 mg/m3				
Dermal			1,5 mg/kg	1,5 mg/kg				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.42 mg/l
Fresh water sediments	
Marine water	0.042 mg/l
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

Chemical Name:

4-tert-Butylphenol

EC No.: CAS-No.: 202-679-0 98-54-4

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required						0.026 mg/kg	
Inhalation				0.5 mg/m3				0.09 mg/m3
Dermal				0.071 mg/kg				0.026 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

Chemical Name:

2-piperazin-1-ylethylamine

EC No.: CAS-No.: 205-411-0 140-31-8

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required			0.02 mg/kg	1.5 mg/kg bw/		0.3 mg/kg bw/	
					bw/day	day		day
Inhalation		21.4 mg/m3		3.6 mg/m3		5.3 mg/m3		0.9 mg/m3
Dermal		20 mg/kg bw/	0.006 mg/cm2	3.3 mg/kg bw/		10 mg/kg bw/	0.003 mg/cm2	1.7 mg/cm2
		day		dav		day		<u>-</u>

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.058 mg/l
Fresh water sediments	215 mg/kg dwt
Marine water	0.0058 mg/l
Marine sediments	21.5 mg/kg bwt
Food chain	
Microorganisms in sewage treatment	82.2 mg/l
soil (agricultural)	42.9 mg/kg dwt
Air	

Chemical Name:

reaction mass ethylbenzene - xylene

EC No.: CAS-No.: 905-588-0

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							1.6 mg/kg bw/
								day
Inhalation	289 mg/m ³			77 mg/m³				14.8 mg/m ³
Dermal				180 mg/kg bw/				108 mg/kg bw/
				day				day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0,327 mg/L
Fresh water sediments	12.46 mg/kg sediment dw
Marine water	0,327 mg/L
Marine sediments	12.46 mg/kg sediment dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	2.31 mg/kg soil dw
Air	

Chemical Name:

xylene

EC No.: CAS-No.: 215-535-7 1330-20-7

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required						1.6 mg/kg bw/	
								day
Inhalation	289 mg/m ³	289 mg/m ³		77 mg/m³	174 mg/m ³	174 mg/m ³		14.8 mg/m ³
Dermal				180 mg/kg bw/				108 mg/kg bw/
				day				day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Wear respiratory protection with combination filter (dust and gas filter, EN 14387:2004 +A1:2008) during spraying operations: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust). When working in confined or poorly ventilated spaces, a battery powered assisted air-fed mask must be used.

EYE PROTECTION: Face-shield.

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to

the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

Blue

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties Colour:

> **Physical State** Liquid Odor Amine

Odor threshold Not determined

рΗ Not determined Melting point / freezing point (°C) Not determined

Boiling point or initial boiling point and

boiling range (°C)

Not determined

Flash Point, (°C) 30

Evaporation rate Not determined Flammability (solid, gas) Not determined

Llower and upper explosive limit Not determined

Vapour Pressure Not determined

Relative vapour density >1 (air=1)

Density and/or relative density Not determined

Solubility in / Miscibility with water Negligible

Partition coefficient: n-octanol/water Not determined Auto-ignition temperature (°C) Not determined Decomposition temperature (°C) Not determined Kinematic viscosity Not determined

Particle characteristics Not applicable to liquids

9.2 Other information

VOC Content g/l: 30

Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.

Specific Gravity (g/cm3) 1.25

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under recommended storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No reactivity hazards known under recommended storage and use conditions.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Keep away from strong oxidising agents and strongly acid or alkaline materials.

10.6 Hazardous decomposition products

In case of fire or hot work operations, **hazardous decomposition products** may be formed such as:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), aliphatic amines, aldehydes.

SECTION 11: Toxicological information

11.1 Information on hazard classes as definied in Regulation (EC) No 1272/2008

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Dermal LD50: No Information

Irritation: No information available.

Corrosivity: Skin Corrosion, category 1B

Sensitization: Skin sensitizer, category 1

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: STOT RE 1

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
39423-51-3	Propylidynetrimethanol, propoxylated, reaction products with ammonia	550 mg/kg rat	>1000 mg/kg rat	No information	No information	No information
100-51-6	Benzyl alcohol	1200 mg/kg rat	2980 mg/kg, rabbit	No information	No information	>4.178 mg/L (4h/ rat, mist)
65997-17-3	glass oxide	>2000 - 5000 mg/ kg bw (rat)	No information	No information	No information	No information
90-72-2	2,4,6-tris (dimethylaminomethyl)phenol	2000 mg/kg oral		2169 mg/kg oral	0.000	0.000
694-83-7	1,2-cyclohexanediamine	1170 mg/kg, rat, oral	1870 mg/kg Dermal,rat	No information	No information	1.23 mg/l/4h Inhalation ,rat
98-54-4	4-tert-Butylphenol	>2000 mg/kg	5600 mg/kg	No information	No information	No information
140-31-8	2-piperazin-1-ylethylamine	1999 mg/kg, oral, rat	866 mg/kg, dermal, rabbit	No information	No information	No information
	reaction mass ethylbenzene - xylene	3500 mg/kg oral, rat	1100 mg/kg dermal, rat	29.08 mg/kg/4h inhalation, rat	No information	No information

1330-20-7 xylene >2000 mg/kg (ATE 11 mg/L (ATE inh/ 4500 ppmV (ATE 1.5 mg/L (ATE 1.5 m

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Corrosive - causes irreversible eye damage. Chronic exposure causes drying effect on the skin and eczema. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin. Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs.

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Name According to EEC CAS-No.

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):No informationIC50 72hr (Algae):No informationLC50 96hr (fish):No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB

assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.
4-tert-Butylphenol 98-54-4

12.7 Other adverse effects: No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
39423-51-3	Propylidynetrimethanol, propoxylated, reaction products with ammonia	13 mg/l (daphnla)	No information	>100 mg/l (fish)
100-51-6	Benzyl alcohol	230 mg/L (Daphnia Magna)	770 mg/L (EgC50, Selenastrum capricornutum)	400 mg/L (fish)
65997-17-3	glass oxide	No information	1000 mg/L	1000 mg/L

90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	718 mg/L (EC50, 96h, Palaeomonetes vulgaris)	84 mg/L (EC50, 72h, Desmodesmus subspicatus)	
694-83-7	1,2-cyclohexanediamine	No information	No information	1825 mg/l (Pimephales promelas)
98-54-4	4-tert-Butylphenol	3.4 to 4.5 mg/l	2.4 mg/l	4.71 to 5.62 mg/l
140-31-8	2-piperazin-1-ylethylamine	58 mg/l (Daphnia)	1000 mg/l (EC50, Algae	e)2190 mg/l (EC50, fish)
1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrun sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrichirus), 21.0 mg/l (Pimenhales promelas)

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

European Waste Code:

Packaging Waste Code:

No Information
No Information

SECTION 14: Transport Information

		ADR/RID	ADN	IMDG	IATA
14.1	UN-number or ID number	UN3470	UN3470	UN3470	UN3470
14.2	UN proper shipping name	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE
14.3	Transport Hazard Class(es)	8,(3)	8,(3)	8,(3)	8,(3)
14.4	Packing Group	II	II	II	II
14.5	Enviromental Hazards	Environmental Hazard: YES (Propylidynetrimethanol , propoxylated, reaction products with ammonia)	nol, propoxylated,	Marine Pollutant: YES (Propylidynetrimethan ol, propoxylated, reaction products with ammonia)	Environmental Hazard: YES (Propylidynetrimethanol, propoxylated, reaction products with ammonia)

14.6 Special precautions for user Not applicable EmS-No.: F-E, S-C

14.7 Maritime transport in bulk according to IMO

intruments

Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:Not availableDanish MAL Code:Not availableDanish MAL Code - Mixture:Not availableSweden Product Registration Number:Not availableNorway Product Registration Number:Not availableGermany WGK Class:Not available

Directive 2004/42/CE: 500 g/l (subcat j)

Covered by Directive 2012/18/EC (Seveso III): Not applicable

Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:

Not applicable

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

98-54-4 4-tert-Butylphenol

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H361fd	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

02 - Hazard Identification

11 - Toxicological Information

14 - Transportation Information

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes. .

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.

- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter \leq 10 μm .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.