

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 1 of 16  
Print date: 18/12/2024

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: CARBOCOAT 1422 Blanco RAL 9010  
Product Code: J29388250  
UFI: 343N-E0Y2-5008-WX33

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

ESMALTE DE TERMINACION USO PROFESIONAL

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

##### Company's identification:

Company: **Carboline**  
Address: C/Numancia, 185 Entresuelo 1ª  
City: 08034 Barcelona  
Province: Barcelona  
Telephone: +34 932 09 60 19  
E-mail: iboter@carboline.com

#### 1.4 Emergency telephone number: (Available 24 hours)

Toxicological Information Service (National Institute of Toxicology and Forensic Sciences) Telephone: +34 91 5620420.  
Information in Spanish (24 hours/365 days). Solely for the purpose of providing a health response in case of emergency.

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Flam. Liq. 3 : Flammable liquid and vapour.  
Skin Irrit. 2 : Causes skin irritation.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

**Warning**

Hazard statements:

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 2 of 16  
Print date: 18/12/2024

### Precautionary statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P262 Do not get in eyes, on skin, or on clothing.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/&  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...  
P331 Do NOT induce vomiting.  
P370+P378 In case of fire: Use... to extinguish.  
P403+P235 Store in a well-ventilated place. Keep cool.

### 2.3 Other hazards.

The mixture does not contain substances classified as PBT.  
The mixture does not contain substances classified as vPvB.  
The mixture does not contain any endocrine disrupting properties substances.

The product may have the following additional risks:  
May form explosible dust-air mixture if dispersed.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene	10 - 49.99 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 7727-43-7 EC No: 231-784-4 Registration No: 01-2119491274-35-XXXX	[1] barium sulfate	2.5 - 9.99 %	-	-
Index No: 649-356-00-4 CAS No: 128601-23-0 EC No: 918-668-5 Registration No: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics	1 - 2.49 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT SE 3, H335 - STOT SE 3, H336	-
Index No: 601-023-00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01-2119489370-35-XXXX	[1] ethylbenzene	1 - 9.99 %	Acute Tox. 4 *, H332 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT RE 2, H373(órganos de audición)	-

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 3 of 16  
Print date: 18/12/2024

EC No: 919-857-5 Registration No: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	0 - 9.99 %	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT SE 3, H336	-
CAS No: 34590-94-8 EC No: 252-104-2 Registration No: 01-2119450011-60-XXXX	[1] (2-methoxymethylethoxy)propanol	0 - 2.49 %	-	-
Index No: 607-025-00-1 CAS No: 123-86-4 EC No: 204-658-1 Registration No: 01-2119485493-29-XXXX	n-butyl acetate	0 - 19.99 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
EC No: 905-588-0 Registration No: 01-2119539452-40-0051	reaction mass of ethylbenzene and xylene	0 - 9.99 %	Acute Tox. 4, H312 - Acute Tox. 4, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 607-195-00-7 CAS No: 108-65-6 EC No: 203-603-9 Registration No: 01-2119475791-29-XXXX	[1] 2-methoxy-1-methylethyl acetate	0 - 19.99 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
EC No: 919-446-0 Registration No: 01-2119458049-33-XXXX	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	0 - 0.99 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT RE 1, H372 - STOT SE 3, H336	-
Index No: 603-002-00-5 CAS No: 64-17-5 EC No: 200-578-6 Registration No: 01-2119457610-43-XXXX	ethanol, ethyl alcohol	0 - 9.99 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225	-
Index No: 613-088-00-6 CAS No: 2634-33-5 EC No: 220-120-9 Registration No: 01-2120761540-60-XXXX	1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one	0 - 0.0499 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 (M=1) - Eye Dam. 1, H318 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Skin Sens. 1, H317: C g 0,05 %
Index No: 601-043-00-3 CAS No: 95-63-6 EC No: 202-436-9 Registration No: 01-2119472135-42-XXXX	[1] 1,2,4-trimethylbenzene	0 - 2.49 %	Acute Tox. 4 *, H332 - Aquatic Chronic 2, H411 - Eye Irrit. 2, H319 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - STOT SE 3, H335	-

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 4 of 16  
Print date: 18/12/2024

Index No: 601-009-00-8 CAS No: 111-65-9 EC No: 203-892-1 Registration No: 01-2119463939-19-XXXX	octane, n-octane	0 - 0.249 %	Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 1, H410 (M=1) - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Skin Irrit. 2, H315 - STOT SE 3, H336	-
--	------------------	-------------	---	---

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

### SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

### SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

#### 5.1 Extinguishing media.

##### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

##### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 5 of 16  
Print date: 18/12/2024

### 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Carbon monoxide, carbon dioxide.
- Flammable vapors or gases.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

### 6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 6 of 16  
Print date: 18/12/2024

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5.000	50.000

### 7.3 Specific end use(s).

PINTURA

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
xylene	1330-20-7	European Union [1]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
barium sulfate	7727-43-7	European Union [1]	Eight hours		0,5
			Short term		
ethylbenzene	100-41-4	European Union [1]	Eight hours	100 (skin)	442 (skin)
			Short term	200 (skin)	884 (skin)
(2-methoxymethylethoxy)propanol	34590-94-8	European Union [1]	Eight hours	50 (skin)	308 (skin)
			Short term		
2-methoxy-1-methylethyl acetate	108-65-6	European Union [1]	Eight hours	50 (skin)	275 (skin)
			Short term	100 (skin)	550 (skin)
1,2,4-trimethylbenzene	95-63-6	European Union [1]	Eight hours	20	100
			Short term		

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
xylene CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m <sup>3</sup> )
barium sulfate CAS No: 7727-43-7 EC No: 231-784-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	10 (mg/m <sup>3</sup> )
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m <sup>3</sup> )
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	DNEL (Workers)	Inhalation, Chronic, Systemic effects	480 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Short term, Systemic effects	960 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Inhalation, Short term, Systemic effects	859,7 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Chronic, Local effects	480 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Inhalation, Chronic, Local effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Short term, Local effects	960 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Short term, Local effects	960 (mg/m <sup>3</sup> )

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 7 of 16  
Print date: 18/12/2024

	DNEL (Consumers)	Inhalation, Short term, Local effects	859,7 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Oral, Chronic, Systemic effects	3,4 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	3,4 (mg/kg bw/day)
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	DNEL (Workers)	Inhalation, Chronic, Systemic effects	275 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	33 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Chronic, Systemic effects	153,5 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	54,8 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	1,67 (mg/kg bw/day)
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	DNEL (Workers)	Inhalation, Chronic, Systemic effects	950 (mg/m <sup>3</sup> )
1,2,4-trimethylbenzene CAS No: 95-63-6 EC No: 202-436-9	DNEL (Workers)	Inhalation, Chronic, Local effects	100 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	100 (mg/m <sup>3</sup> )
octane, n-octane CAS No: 111-65-9 EC No: 203-892-1	DNEL (Workers)	Inhalation, Chronic, Systemic effects	2035 (mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
	aqua (intermittent releases)	0,36 (mg/l)
	STP	35,6 (mg/l)
	sediment (freshwater)	0,981 (mg/kg sediment dw)
	sediment (marine water)	0,0981 (mg/kg sediment dw)
	soil	0,0903 (mg/kg soil dw)
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	aqua (freshwater)	0,635 (mg/L)
	aqua (marine water)	0,0635 (mg/L)
	aqua (intermittent releases)	6,35 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	3,29 (mg/kg sediment dw)
	sediment (marine water)	0,329 (mg/kg sediment dw)
	soil	0,29 (mg/kg soil dw)
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	Fresh water	0,96 (mg/L)
	Marine water	0,79 (mg/L)
	aqua (intermittent releases)	2,75 (mg/L)

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 8 of 16  
Print date: 18/12/2024




	Soil	0,63 (mg/kg soil dw)
	sediment (freshwater)	3,6 (mg/kg sediment dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>	
<b>Uses:</b>	<b>ESMALTE DE TERMINACION USO PROFESIONAL</b>	
<b>Breathing protection:</b>		
If the recommended technical measures are observed, no individual protection equipment is necessary.		
<b>Hand protection:</b>		
If the product is handled correctly, no individual protection equipment is necessary.		
<b>Eye protection:</b>		
PPE:	Face shield.	
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.	
CEN standards:	EN 165, EN 166, EN 167, EN 168	
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.	
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.	
<b>Skin protection:</b>		
PPE:	Anti-static protective clothing.	
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.	
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.	
PPE:	Anti-static safety footwear.	
Characteristics:	«CE» marking, category II.	
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346	
Maintenance:	The footwear should be checked regularly	
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.	

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: BLANCO

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: 115 °C (Estimation based on the indication of the Regulation (CE) N°1272/2008.)

Flammability: Not applicable/Not available due to the nature/properties of the product

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 9 of 16  
Print date: 18/12/2024

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product  
Upper explosion limit: Not applicable/Not available due to the nature/properties of the product  
Flash point: 30 °C (Estimation based on the indication of the Regulation (CE) N°1272/2008.)  
Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product  
Decomposition temperature: Not applicable/Not available due to the nature/properties of the product  
pH: Not applicable (Substance/mixture is non-soluble (in water)).  
Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product  
Solubility: Not applicable/Not available due to the nature/properties of the product  
Hydrosolubility: Not applicable/Not available due to the nature/properties of the product  
Liposolubility: Not applicable/Not available due to the nature/properties of the product  
Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product  
Vapour pressure: 10,171 (Estimation based on the indication of the Regulation (CE) N°1272/2008.)  
Absolute density: Not applicable/Not available due to the nature/properties of the product  
Relative density: 1,147  
Relative vapour density: Not applicable/Not available due to the nature/properties of the product  
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

### 9.2 Other information

#### Information with regard to physical hazard classes

Flammable liquids:

Sustained combustibility: Yes.

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

### 10.4 Conditions to avoid.

Avoid any improper handling.

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

## SECTION 11: TOXICOLOGICAL INFORMATION.

**IRRITANT MIXTURE.** Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

#### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
xylene	Oral	LD50	Rat	4300 mg/kg bw [1]
		LD50	rat (male)	3523 mg/kg bw [2]
		[1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956		
		[2] Study report, 1986, similar to EU Method B.1 (Acute Toxicity (Oral))		

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 10 of 16  
Print date: 18/12/2024

CAS No: 1330-20-7 EC No: 215-535-7	Dermal	LD50 Rabbit > 1700 mg/kg bw [1] LD50 rabbit 12126 mg/kg bw [2] (male) [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974 [2] Publication, 1962, unnamed
	Inhalation	LC50 Rat 21,7 mg/l/4 h [1] LC50 Rat 6350 ppm (4 h) [2] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974 [2] The toxicological properties of hydrocarbon solvents, Hine CH, Zuidema HH (1970), Industrial Medicine 39, 215-200
ethylbenzene  CAS No: 100-41-4 EC No: 202-849-4	Oral	LD50 Rat 3500 mg/kg bw [1] [1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956
	Dermal	LD50 Rabbit 15400 mg/kg bw [1] [1] Food and Cosmetics Toxicology. Vol. 13, Pg. 803, 1975
	Inhalation	
1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one  CAS No: 2634-33-5 EC No: 220-120-9	Oral	LD50 Rat 1020 mg/kg bw [1] LD50 rat 490 mg/kg bw (act. ingr.) [2] [1] Pharmacological Research Communications. Vol. 3, Pg. 385, 1971 [2] Study report according to OECD Guideline 401 (Acute Oral Toxicity)
	Dermal	
	Inhalation	
1,2,4-trimethylbenzene  CAS No: 95-63-6 EC No: 202-436-9	Oral	LD50 Rat (male) 6000 mg/kg bw [1] [1] Study report, 1980. EU Method B.1 (Acute Toxicity (Oral))
	Dermal	
	Inhalation	

a) acute toxicity;  
Not conclusive data for classification.

Acute Toxicity Estimate (ATE):  
Mixtures:  
ATE (Dermal) = 3.638 mg/kg

b) skin corrosion/irritation;  
Product classified:  
Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;  
Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;  
Based on available data, the classification criteria are not met.

e) germ cell mutagenicity;  
Not conclusive data for classification.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 11 of 16  
Print date: 18/12/2024

f) carcinogenicity;  
Not conclusive data for classification.

g) reproductive toxicity;  
Not conclusive data for classification.

h) STOT-single exposure;  
Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;  
Based on available data, the classification criteria are not met.

j) aspiration hazard;  
Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards.

#### Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

#### Other information

There is no information available on other adverse health effects.

## SECTION 12: ECOLOGICAL INFORMATION.

### 12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
xylene	Fish	LC50	Fish	15,7 mg/l (96 h) [1]
		[1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212		
	Aquatic invertebrates	LC50	Crustacean	8,5 mg/l (48 h) [1]
ethylbenzene		[1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p		
	Aquatic plants			
		LC50	Fish	80 mg/l (96 h) [1]
		[1] Mayer, F.L.Jr., and M.R. Ellersieck 1986. Manual of Acute Toxicity: Interpretation and Data Base for 410 Chemicals and 66 Species of Freshwater Animals. Resour.Publ.No.160, U.S.Dep.Interior, Fish Wildl.Serv., Washington, DC :505 p. (USGS Data File)		
	Aquatic invertebrates	LC50	Crustacean	16,2 mg/l (48 h) [1]
		[1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p		
	Aquatic plants	EC50	Algae	5 mg/l (72 h) [1]

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 12 of 16  
Print date: 18/12/2024

CAS No: 100-41-4	EC No: 202-849-4	[1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L. Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169. Masten, L.W., R.L. Boeri, and J.D. Walker 1994. Strategies Employed to Determine the Acute Aquatic Toxicity of Ethyl Benzene, a Highly Volatile, Poorly Water-Soluble Chemical. Ecotoxicol.Environ.Saf. 27(3):335-348
------------------	------------------	---

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	3,15	-	-	Moderate
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	1,78	-	-	Very low
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	-0,3	-	-	Very low

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

### 12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 13 of 16  
Print date: 18/12/2024

### SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

#### 14.1 UN number or ID number.

UN No: UN1263

#### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 1263, PAINT, 3, PG III, (D/E)

IMDG: UN 1263, PAINT, 3, PG III

ICAO/IATA: UN 1263, PAINT, 3, PG III

#### 14.3 Transport hazard class(es).

Class(es): 3

#### 14.4 Packing group.

Packing group: III

#### 14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEM 3 Emergency sheets (F 3 Fire, S - Spills): F-E,S-E

#### 14.6 Special precautions for user.

Labels: 3



Hazard number: 30

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

#### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

### SECTION 15: REGULATORY INFORMATION.

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): i - One-pack performance coatings, solvent-borne

Phase I\* (from 01/01/2007): 600 g/l

Phase II\* (from 01/01/2010): 500 g/l

(\*) g/l ready to use

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1      Date of compilation: 18/12/2024

Page 14 of 16  
Print date: 18/12/2024

VOC content (p/p): 35,563 %  
VOC content: 407,902 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 2: Hazardous to water. (Autoclassified according to the AwSV Regulations)

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.(órganos de audición)
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4  
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4  
Acute Tox. 4 : Acute toxicity (Oral), Category 4  
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1  
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1  
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2  
Asp. Tox. 1 : Aspiration toxicity, Category 1  
Eye Dam. 1 : Serious eye damage, Category 1  
Eye Irrit. 2 : Eye irritation, Category 2  
Flam. Liq. 2 : Flammable liquid, Category 2  
Flam. Liq. 3 : Flammable liquid, Category 3  
Skin Irrit. 2 : Skin irritant, Category 2  
Skin Sens. 1 : Skin sensitizer, Category 1  
STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1  
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1 Date of compilation: 18/12/2024

Page 15 of 16  
Print date: 18/12/2024

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

### Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
1330-20-7	xylene	Registered
7727-43-7	barium sulfate	Registered
128601-23-0	Hydrocarbons, C9, aromatics	
100-41-4	ethylbenzene	Registered
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
34590-94-8	(2-methoxymethylethoxy)propanol	Registered
123-86-4	n-butyl acetate	Registered
	reaction mass of ethylbenzene and xylene	
108-65-6	2-methoxy-1-methylethyl acetate	Registered
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
64-17-5	ethanol, ethyl alcohol	Registered
2634-33-5	1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one	Registered
95-63-6	1,2,4-trimethylbenzene	Registered
111-65-9	octane, n-octane	Registered

### Canada DSL/NDSL Inventory Registration Status

CAS No	Name	State DSL	State NDSL
1330-20-7	xylene	Registered	Not
7727-43-7	barium sulfate	Registered	Not
128601-23-0	Hydrocarbons, C9, aromatics	Not	Not
100-41-4	ethylbenzene	Registered	Not
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not	Not
34590-94-8	(2-methoxymethylethoxy)propanol	Registered	Not
123-86-4	n-butyl acetate	Registered	Not
	reaction mass of ethylbenzene and xylene	Not	Not
108-65-6	2-methoxy-1-methylethyl acetate	Registered	Not
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Not	Not
64-17-5	ethanol, ethyl alcohol	Registered	Not
2634-33-5	1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one	Registered	Not
95-63-6	1,2,4-trimethylbenzene	Registered	Not
111-65-9	octane, n-octane	Registered	Not

Risk classification system NFPA 704:

-Continued on next page.-

# SAFETY DATA SHEET


(in accordance with Regulation (EU) 2020/878)



## CARBOCOAT 1422 Blanco RAL 9010

Version 1      Date of compilation: 18/12/2024

Page 16 of 16  
Print date: 18/12/2024



Health hazard: 2 (Hazardous)

Flammability: 3 (Below 100°F)

Reactivity: 0 (Stable)

### Abbreviations and acronyms used:

ADR/RID: Agreement concerning the International Carriage of Dangerous Goods by Road.

AwSV: Facility Regulations for handling substances that are hazardous for the water.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

WGK: Water hazard classes.

### Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.