



**Safety Data Sheet**  
**according to Regulation (EC)**  
**No. 2015/830**



### SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

<b>1.1 Product Identifier</b>	10EU0021	<b>Revision Date:</b>	25/03/2020
<b>Product Name:</b>	THINNER N° 21 (EU)	<b>Supersedes Date:</b>	26/07/2019
		<b>Version Number:</b>	3
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>	Thinner for industrial coatings - Industrial use.		
<b>Product to be mixed with:</b>	Not applicable		
<b>Mixing ratio by volume Part A/ Part B:</b>	Not applicable		
<b>1.3 Details of the supplier of the safety data sheet</b>			
<b>Manufacturer:</b>	Carboline Italia, S.p.a. Via Margherita Vigano' De Vizzi . n 77 20092 Cinisello Balsamo (MI) Italy		
	Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cinisello Balsamo, Italy		
<b>Datasheet Produced by:</b>	Chen, Shi - ehs@stoncor.com		
<b>1.4 Emergency telephone number:</b>	CHEMTREC +1 703 5273887 (Outside US) PPC +1 412 6816669 (Outside US) Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)(24h/24h) Emergenza ambientale +39 335-601 32 88 / +39 347-949 84 88 / +39 348-246 90 99		

### SECTION 2: Hazard Identification

#### 2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

#### HAZARD STATEMENTS

Flammable Liquid, category 2	H225
Eye Irritation, category 2	H319
STOT, single exposure, category 3, NE	H336

## 2.2 Label elements

### Symbol(s) of Product



### Signal Word

Danger

### Named Chemicals on Label

Propan-2-ol, 1-methoxypropan-2-ol

#### HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.

#### PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P337+313	If eye irritation persists: Get medical advice/attention.
P403+235	Store in a well-ventilated place. Keep cool.

## 2.3 Other hazards

Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## SECTION 3: Composition/Information On Ingredients

### 3.2 Mixtures

#### Hazardous Ingredients

<u>CAS-No.</u>	<u>EINEC No.</u>	<u>Name According to EEC</u>	<u>%</u>
67-63-0	200-661-7	Propan-2-ol	75-100
107-98-2	203-539-1	1-methoxypropan-2-ol	2.5 - <10

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
67-63-0	01-2119457558-25	GHS02-GHS07	H225-319-336	
107-98-2	01-2119457435-35	GHS02-GHS07	H226-336	

**Additional Information:** The text for CLP Hazard Statements shown above (if any) is given in Section 16.

## SECTION 4: First-aid Measures

### 4.1 Description of First Aid Measures

**GENERAL NOTES:** Show this safety data sheet to the doctor in attendance.

**AFTER INHALATION:** Move to fresh air. Provide fresh air, rest and warmth. Call a physician immediately. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position.

**AFTER SKIN CONTACT:** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

#### **Self protection of the first aider:**

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### **4.2 Most important symptoms and effects, both acute and delayed**

Irritating to eyes. Vapours may cause drowsiness and dizziness.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11. When symptoms persist or in all cases of doubt seek medical advice.

### **SECTION 5: Fire-fighting Measures**

#### **5.1 Extinguishing Media:**

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

#### **5.2 Special hazards arising from the substance or mixture**

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). May explode in fire. Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

#### **5.3 Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

### **SECTION 6: Accidental Release Measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment.

#### **6.2 Environmental precautions**

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

#### **6.3 Methods and material for containment and cleaning up**

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). After cleaning, flush away traces with water.

#### **6.4 Reference to other sections**

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

### **SECTION 7: Handling and Storage**

#### **7.1 Precautions for safe handling**

Keep containers dry and tightly closed to avoid moisture absorption and contamination. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment.

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

**7.2 Conditions for safe storage, including any incompatibilities**

**CONDITIONS TO AVOID:** Avoid moisture. Avoid heat, sparks, flames and other ignition sources.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store away from: oxidising materials, acids, and alkalis. Keep away from heat and flame. Keep away from combustible materials. Store in upright position only. Storage of flammable liquids.

**7.3 Specific end use(s)**

No specific advice for **end use** available.

**SECTION 8: Exposure Controls/Personal Protection****8.1 Control parameters****Ingredients with Occupational Exposure Limits  
(UK WELS)**

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
Propan-2-ol	67-63-0	400	500	1250	999
1-methoxypropan-2-ol	107-98-2	100	150	560	375

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
Propan-2-ol	67-63-0	
1-methoxypropan-2-ol	107-98-2	Sk

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

**8.2 Exposure controls****Personal Protection**

**RESPIRATORY PROTECTION:** When working in confined or poorly ventilated spaces, a self-contained breathing apparatus or full-face airline respirator must be used. Respirator with a vapour filter: gas filter type A2 (organic substances).

**EYE PROTECTION:** If splashes are likely to occur, wear: Face-shield, tightly fitting safety goggles (EN 166).

**HAND PROTECTION:** Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Use chemical resistant gloves (EN 374): Butyl rubber. Viton®.

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location.

**ENGINEERING CONTROLS:** Ensure adequate ventilation, especially in confined areas.

**Chemical Name:**

Propan-2-ol

**EC No.:**

200-661-7

**CAS-No.:**

67-63-0

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required						26 mg/kg	
Inhalation				500 mg/m <sup>3</sup>				89 mg/m <sup>3</sup>
Dermal				888 mg/kg				319 mg/kg

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	140.9 mg/l
Fresh water sediments	552 mg/kg
Marine water	140.9 mg/l
Marine sediments	552 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	28 mg/kg
Air	

**Chemical Name:**

1-methoxypropan-2-ol

**EC No.:**

203-539-1

**CAS-No.:**

107-98-2

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required						3.3 mg/kg	
Inhalation	553.5 mg/m <sup>3</sup>	553.5 mg/m <sup>3</sup>		369 mg/m <sup>3</sup>				43.9 mg/m <sup>3</sup>
Dermal				183 mg/kg bw/day				18.1 mg/kg

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	10 mg/l
Fresh water sediments	100 mg/l
Marine water	1 mg/l
Marine sediments	5.2 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	5.49 mg/kg
Air	

**SECTION 9: Physical and Chemical Properties****9.1 Information on basic physical and chemical properties**

<b>Appearance:</b>	Clear
<b>Physical State</b>	LIQUID
<b>Odor</b>	SOLVENT
<b>Odor threshold</b>	Not determined
<b>pH</b>	Not determined
<b>Melting point / freezing point (°C)</b>	Not determined
<b>Boiling point/range (°C)</b>	83 - 122

Flash Point, (°C)	12
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	1.5 - 13.7
Vapour Pressure	Not determined
Vapour density	>1 (air = 1)
Relative density	Not determined
Solubility in / Miscibility with water	Miscible
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	287
Decomposition temperature (°C)	Not determined
Viscosity	Not determined
Explosive properties	Not determined
Oxidising properties	Not determined

## 9.2 Other information

VOC Content g/l:	800.0
Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.	
Specific Gravity (g/cm <sup>3</sup> )	0.80

## SECTION 10: Stability and Reactivity

### 10.1 Reactivity

No **reactivity** hazards known under recommended storage and use conditions.

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

No Information

### 10.4 Conditions to avoid

Avoid moisture. Avoid heat, sparks, flames and other ignition sources.

### 10.5 Incompatible materials

Keep away from oxidising agents and strongly acid or alkaline materials.

### 10.6 Hazardous decomposition products

Carbon dioxide, carbon monoxide.

## SECTION 11: Toxicological Information

### 11.1 Information on toxicological effects

#### Acute Toxicity:

**Oral LD50:** No information available on the product itself as the product is not tested.

**Inhalation LC50:** No information available on the product itself as the product is not tested.

**Irritation:** Causes serious eye irritation.

**Corrosivity:** No information available.

**Sensitization:** No information available.

<b>Repeated dose toxicity:</b>	No information available.
<b>Carcinogenicity:</b>	No information available.
<b>Mutagenicity:</b>	No information available.
<b>Toxicity for reproduction:</b>	No information available.
<b>STOT-single exposure:</b>	Central nervous system depression.
<b>STOT-repeated exposure:</b>	No information available.
<b>Aspiration hazard:</b>	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.  
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
67-63-0	Propan-2-ol	4720 mg/kg (oral-rat)	No information	22500 ppm/8hrs rat, inhalation	No information	No information
107-98-2	1-methoxypropan-2-ol	4016 mg/kg (oral-rat)	>13000 mg/kg (dermal-rabbit)	10000 ppm/4hrs rat, inhalation	No information	No information

#### Additional Information:

Repeated and prolonged exposure to solvents may cause brain and nervous system damage. Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Chronic exposure causes drying effect on the skin and eczema. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin.

## SECTION 12: Ecological Information

### 12.1 Toxicity:

<b>EC50 48hr (Daphnia):</b>	No information
<b>IC50 72hr (Algae):</b>	No information
<b>LC50 96hr (fish):</b>	No information

**12.2 Persistence and degradability:** No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

**12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**12.6 Other adverse effects:** No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
67-63-0	Propan-2-ol	No information	No information	4200 mg/L (fish)
107-98-2	1-methoxypropan-2-ol	>21000 mg/L (Daphnia)	No information	6812 mg/L (Leuciscus idus)

## SECTION 13: Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems. Rags/wiping cloths and the like, moistened with flammable liquids, must be discarded into designated fireproof buckets.

European Waste Code: 14 06 03\*  
Packaging Waste Code: 15 01 10

## SECTION 14: Transport Information

14.1 UN number	UN1263
14.2 UN proper shipping name	PAINT RELATED MATERIAL
Technical name	Not applicable
14.3 Transport hazard class(es)	3
Subsidiary shipping hazard	Not applicable
14.4 Packing group	II
14.5 Environmental hazards	Marine Pollutant: NO
14.6 Special precautions for user	Not applicable
EmS-No.:	F-E, <u>S-E</u>
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

## SECTION 15: Regulatory Information

**15.1 Safety, health and environmental regulations/legislation for the substance or mixture:**

### National Regulations:

Denmark Product Registration Number:	Not available
Danish MAL Code:	Not available
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	Not available
Norway Product Registration Number:	Not available
Germany WGK Class:	1
Directive 2004/42/CE :	Not applicable
Covered by Directive 2012/18/EC (Seveso III):	P5c
Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:	Entry 3, 40

### Annex XIV - Authorisation List:

CAS-No.      Name According to EEC

Not Applicable

### SVHC - Substances of very high concern (Candidate List):

CAS-No.      Name According to EEC

Not Applicable



**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**SECTION 16: Other Information****Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Reasons for revision**

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes. .

## List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;  
European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;  
European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);  
EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

## Acronym &amp; Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code

IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

