

Safety Data Sheet

prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

| 1.1 | Product Identifier | 504-0003 | Revision Date: | 26/08/2023 |
|-----|---|---|---------------------------------------|------------|
| | Product Name: | Carbocoat GP-55 - Primer | Supersedes Date: | 22/06/2018 |
| 1.2 | Relevant identified uses of the substance or mixture and uses advised against | Monocomponent industrial coating - Ir recommended | ndustrial use. Advised against: other | s than |
| 1.3 | Details of the supplier of the safety | data sheet | | |
| | Importer: | Importer | | |
| | Manufacturer: | StonCor Africa (Pty.) Ltd. 8 Cresset Road Midrand Industrial Park, Chloorkop P.O. Box 2205 2001, Johannesburg South Africa Regulatory / Technical Information: +27 11 254 5500 | | |
| | Datasheet Produced by: | Hensberg, Joshua - ehs@stoncor.con | n | |
| 1.4 | Emergency telephone number: | CHEMTREC 1-800-424-9300 (Inside CHEMTREC +1 703 5273887 (Outsid Giftinformasjonen: +47 22 59 13 00 | | |

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 2 Carcinogenicity, category 2 Flammable Liquid, category 2 Skin Irritation, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Ethylbenzene, Xylene, titanium dioxide

HAZARD STATEMENTS

| Flammable Liquid, category 2 | H225 | Highly flammable liquid and vapour. |
|--|------|--|
| Skin Irritation, category 2 | H315 | Causes skin irritation. |
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled. |
| Carcinogenicity, category 2 | H351 | Suspected of causing cancer. |
| Hazardous to the aquatic environment, | H411 | Toxic to aquatic life with long lasting effects. |
| Chronic, category 2 | | |
| PRECAUTION PHRASES | | |

Keep away from heat, hot surfaces, sparks, open flames and P210 other ignition sources. No smoking. P235 Keep cool. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment. P273 P280 Wear protective gloves/protective clothing/eye protection/ face protection. P284 Wear respiratory protection. IF INHALED: Remove victim to fresh air and keep at rest in a P304+340 position comfortable for breathing. P308+313 IF exposed or concerned: Get medical advice/attention. P332+313 If skin irritation occurs: Get medical advice/attention. P391 Collect spillage. Store in a well-ventilated place. Keep container tightly P403+233 closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

| Hazardous ingredients Name According to EEC Xylene | <u>EINEC No.</u> 215-535-7 | <u>CAS-No.</u> 1330-20-7 | <u>%</u> 10 - <25 | <u>Classifications</u> H226-315-332 | Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2 |
|--|-------------------------------|-----------------------------|----------------------|--|--|
| trizinc bis (orthophosphate) | 231-944-3 | 7779-90-0 | 2.5 - <10 | H302-400-410 | Acute Tox. 4 Oral, Aquatic Acute 1, Aquatic Chronic 1 |
| Ethylbenzene | 202-849-4 | 100-41-4 | 2.5 - <10 | H225-304-315-319-3 32-373 | Acute Tox. 4 Inhalation, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2 |

Product: 504-0003

| titanium dioxide | 236-675-5 | 13463-67-7 | 2.5 - <10 | H351 | Carc. 2 |
|--|-----------|------------|------------|----------|----------------------------------|
| magnesium carbonate | | 546-93-0 | 1.0 - <2.5 | H319 | Eye Irrit. 2 |
| calcium bis(2- ethylhexanoate) | 205-249-0 | 136-51-6 | 0.1 - <1.0 | H361 | |
| Solvent naphtha (petroleum), medium aliph. | 265-191-7 | 64742-88-7 | 0.1 - <1.0 | H304 | Asp. Tox. 1 |
| cobalt 2-ethylhexanoate | 205-250-6 | 136-52-7 | <0.1 | H317-400 | Aquatic Acute 1, Skin Sens. 1 |
| Zirconium Octoate | | 15104-99-1 | <0.1 | | |
| Bis(2-ethylhexyl) phthalate | 204-211-0 | 117-81-7 | <0.1 | H360 | Repr. 1A |

| CAS-No. | M-Factors |
|------------|-----------|
| 1330-20-7 | 0 |
| 7779-90-0 | 0 |
| 100-41-4 | 0 |
| 13463-67-7 | 0 |
| 546-93-0 | 0 |
| 136-51-6 | 0 |
| 64742-88-7 | 0 |
| 136-52-7 | 1 |
| 15104-99-1 | 0 |
| 117-81-7 | 0 |

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(EU)

| Name | CAS-No. | LTEL ppm | STEL ppm | STEL mg/m3 | LTEL mg/m3 |
|-------------------------------|------------|----------|----------|------------|------------|
| Xylene | 1330-20-7 | 50 | 100 | 442 | 221 |
| trizinc bis(orthophosphate) | 7779-90-0 | | | | |
| Ethylbenzene | 100-41-4 | 100 | 200 | 884 | 442 |
| titanium dioxide | 13463-67-7 | | | | |
| magnesium carbonate | 546-93-0 | | | | |
| calcium bis(2-ethylhexanoate) | 136-51-6 | | | | |

| Solvent naphtha (petroleum), medium aliph. | 64742-88-7 |
|--|------------|
| cobalt 2-ethylhexanoate | 136-52-7 |
| Zirconium Octoate | 15104-99-1 |
| Bis(2-ethylhexyl) phthalate | 117-81-7 |

| <u>Name</u> | CAS-No. | OEL Note |
|--|------------|----------|
| Xylene | 1330-20-7 | SK |
| trizinc bis(orthophosphate) | 7779-90-0 | |
| Ethylbenzene | 100-41-4 | SKIN |
| titanium dioxide | 13463-67-7 | |
| magnesium carbonate | 546-93-0 | |
| calcium bis(2-ethylhexanoate) | 136-51-6 | |
| Solvent naphtha (petroleum), medium aliph. | 64742-88-7 | |
| cobalt 2-ethylhexanoate | 136-52-7 | |
| Zirconium Octoate | 15104-99-1 | |
| Bis(2-ethylhexyl) phthalate | 117-81-7 | |

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties Appearance: Viscous Liquid

| Liquid |
|-------------------|
| Solvent |
| Not determined |
| Not determined |
| Not determined |
| 77 - 385 |
| 19 |
| Slower than ether |
| Not determined |
| 1 - 13.1 |
| |

| ١ | Vapour Pressure | Not determined |
|----|---|------------------|
| ١ | Vapour density | Heavier than air |
| I | Relative density | 1.45 - 1.49 |
| \$ | Solubility in / Miscibility with water | Insoluble |
| I | Partition coefficient: n-octanol/water | Not determined |
| / | Auto-ignition temperature (°C) | Not determined |
| I | Decomposition temperature (°C) | Not determined |
| ١ | /iscosity | 80 - 95 kU |
| I | Explosive properties | Not determined |
| (| Oxidising properties | Not determined |
| (| Other information | |
| ١ | VOC Content g/I: | 445 |
| C | Calculated grams of VOC per liter of coating product as | s applied. |
| (| Specific Gravity (g/cm3) | 1.444 |
| | | |

10. Stability and Reactivity

10.1 Reactivity

9.2

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid Direct sources of heat.

10.5 Incompatible materials Strong oxidizing agents.

10.6 Hazardous decomposition products Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

Information on toxicological effects 11.1 Acute Toxicity: Oral LD50: No information Inhalation LC50: No information No information available. Irritation: No information available. Corrosivity: Sensitization: No information available. No information available. Repeated dose toxicity: Carcinogenicity: This product contains one or more carcinogenic substances. See hazard classification and precautionary statements in Section 2 for further information. **Mutagenicity:** No information available. No information available. Toxicity for reproduction: No information available. STOT-single exposure: No information available. STOT-repeated exposure: No information available. Aspiration hazard:

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 | Gas LC50 | Dust/Mist LC50 |
|------------|--|----------------------------|-------------------------|--------------------------------|----------|----------------|
| 1330-20-7 | Xylene | 3523 mg/kg, rat, oral | 12126 mg/kg, rabbitt | 5000 ppm/4 hrs rat, inhalation | 0.000 | 0.000 |
| 7779-90-0 | trizinc bis(orthophosphate) | 552 mg/kg, oral rat | | | 0.000 | 0.000 |
| 100-41-4 | Ethylbenzene | 3500 mg/kg rat, oral | 5510 mg/kg, rabbit | 4000 ppm, rat, 4h | 0.000 | 0.000 |
| 13463-67-7 | titanium dioxide | 10000 mg/m3, oral (rat) | | | 0.000 | 0.000 |
| 64742-88-7 | Solvent naphtha (petroleum), medium aliph. | >2000 mg/kg, oral, rat | | | 0.000 | 0.000 |
| 117-81-7 | Bis(2-ethylhexyl) phthalate | 30,600 mg/kg, oral, rat | | | 0.000 | 0.000 |

Additional Information:

This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

546-93-0

136-51-6

136-52-7

117-81-7

64742-88-7

15104-99-1

magnesium carbonate

cobalt 2-ethylhexanoate

Bis(2-ethylhexyl) phthalate

Zirconium Octoate

calcium bis(2-ethylhexanoate)

Solvent naphtha (petroleum), medium aliph.

12. Ecological Information

| | • | | | | | | |
|--|-----------------------------|--|--|--------------------|--|--|--|
| 12.1 Toxic | city: | | | | | | |
| EC | C50 48hr (Daphnia): | No information | | | | | |
| IC | 50 72hr (Algae): | No information | | | | | |
| LC | C50 96hr (fish): | No information | | | | | |
| 12.2 Persistence and degradability: | | No information | | | | | |
| 12.3 Bioaccumulative potential: | | No information | | | | | |
| 12.4 Mobi | lity in soil: | No information | No information | | | | |
| 12.5 Results of PBT and vPvB assessment: | | The product does not meet the | The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII. | | | | |
| 12.6 Othe | r adverse effects: | No information | | | | | |
| CAS-No. | Chemical Name | <u>EC50 48hr</u> | <u>IC50 72hr</u> | <u>LC50 96hr</u> | | | |
| 1330-20-7 | Xylene | 3.82 mg/l | No information | 24-30 mg/l, minnow | | | |
| 7779-90-0 | trizinc bis(orthophosphate) | No information | No information | | | | |
| 100-41-4 | Ethylbenzene | 1.37 mg/l | No information | 32 mg/l (Bluegill) | | | |
| 13463-67-7 | titanium dioxide | >100 mg/l (EC50, 48h, Daphnia magna | No information | >1000 mg/l | | | |

OECD202)ation

No information

13. Disposal Considerations
13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

| | , , , , | |
|------|---|----------------|
| 14. | Transport Information | |
| 14.1 | UN number | UN 1263 |
| 14.2 | UN proper shipping name | Paint |
| | Technical name | Not applicable |
| 14.3 | Transport hazard class(es) | 3 |
| | Subsidiary shipping hazard | Not applicable |
| 14.4 | Packing group | PG II |
| 14.5 | Environmental hazards | Not applicable |
| 14.6 | Special precautions for user | Not applicable |
| | EmS-No.: | Not applicable |
| 14.7 | Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code | Not applicable |

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

| National Regulations: | | |
|--------------------------------------|---------------|--|
| Denmark Product Registration Number: | Not available | |
| Danish MAL Code: | Not available | |
| Danish MAL Code - Mixture: | Not available | |
| Sweden Product Registration Number: | Not available | |
| Norway Product Registration Number: | Not available | |
| WGK Class: | Not available | |

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| | č |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H351 | Suspected of causing cancer. |
| H360 | May damage fertility or the unborn child. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| | |

Reasons for revision

Revision Description Changed Composition Information Changed Substance and/or Product Properties Changed in Section(s): 01 - Identification 09 - Physical and Chemical Properties 11 - Toxicological Information 14 - Transportation Information

- 15 Regulatory Information
- Revision Statement(s) Changed
- nevibion beacement(b) onange

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

| CLP | Classification, Labeling & Packaging Regulation |
|--------|--|
| EC | European Commission |
| EU | European Union |
| US | United States |
| CAS | Chemical Abstract Service |
| EINECS | European Inventory of Existing Chemical Substances |
| REACH | Registration, Evaluation, Authorization of Chemicals Regulation |
| GHS | Globally Harmonized System of Classification and Labeling of Chemicals |
| LTEL | Long term exposure limit |
| STEL | Short term exposure limit |
| OEL | Occupational exposure limit |
| ppm | Parts per million |
| mg/m3 | Milligrams per cubic meter |
| TLV | Threshold Limit Value |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| OSHA | Occupational Safety & Health Administration |
| PEL | Permissible Exposure Limits |
| VOC | Volatile organic compounds |
| g/l | Grams per liter |
| mg/kg | Milligrams per kilogram |
| N/A | Not applicable |
| LD50 | Lethal dose at 50% |
| LC50 | Lethal concentration at 50% |
| EC50 | Half maximal effective concentration |
| IC50 | Half maximal inhibitory concentration |
| PBT | Persistent bioaccumulative toxic chemical |
| vPvB | Very persistent and very bioaccumulative |
| EEC | European Economic Community |
| ADR | International Transport of Dangerous Goods by Road |
| RID | International Transport of Dangerous Goods by Rail |
| UN | United Nations |
| IMDG | International Maritime Dangerous Goods Code |
| IATA | International Air Transport Association |
| MARPOL | International Convention for the Prevention of Pollution From Ships, 1973 as |
| | modified by the Protocol of 1978 |
| IBC | International Bulk Container |
| | |

| RTI | Respiratory Tract Irritation |
|----------|---|
| NE | Narcotic Effects |
| IMO | International Maritime Organization |
| Note P: | The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene |
| Note 10: | The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 $\%$ or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 µm. |

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.