## Safety Data Sheet according to Regulation (EC) 'No. 2020/878



## SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1	Product Identifier Product Name:	1205A5742A PHENOLINE 1205 PART A	Revision Date: Supersedes Date:	06/06/2024 23/09/2020
1.2	UFI Code: Contain nanoform: Relevant identified uses of the substance or mixture and uses advised against	No Information No Component of multicomponent industr others than recommended	rial coatings - Industrial use. Advised	l against:
1.3	Details of the supplier of the safety	r data sheet		
	Importer:	None		
	Manufacturer:	StonCor Middle East L.L.C. Plot # B518, Al Quoz Industrial Area 3 P.O. Box: 3034 Dubai, U.A.E.		
		Regulatory / Technical Information: +971 4 347 0460 +971 4 347 0242 (fax)		
	Datasheet Produced by:	Rivero, Melody - ehs@stoncor.com		

1.4	Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US) 112 (24/7) Croatia +3851 2348 342 (24/7 in Croatian and English) Iceland 112 (24/7)
		Malta 112 (24/7)

## **SECTION 2: Hazards Identification**

#### 2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

#### HAZARD STATEMENTS

Flammable Liquid, category 2	H225
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319
Acute Toxicity, Inhalation, category 4	H332
Carcinogenicity, category 2	H351
Hazardous to the aquatic environment, Chronic, category 2	H411

## 2.2 Label elements

#### Symbol(s) of Product



#### Signal Word

Danger

#### Named Chemicals on Label

Ethylbenzene, Xylene, titanium dioxide, phenol, polymer with formaldehyde, glycidyl ether, glass oxide

#### HAZARD STATEMENTS

Flammable Liquid, category 2 Skin Irritation, category 2 Skin Sensitizer, category 1 Eye Irritation, category 2 Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 2 Hazardous to the aquatic environment, Chronic, category 2 <b>PRECAUTION PHRASES</b>	H225 H315 H317 H319 H332 H351 H411	Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.
	P210 P235 P261 P273 P280 P284 P302+352 P304+340 P305+351+338 P308+313 P333+313 P391 P403+233	<ul> <li>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>Keep cool.</li> <li>Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>Avoid release to the environment.</li> <li>Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>Wear respiratory protection.</li> <li>IF ON SKIN: Wash with plenty of soap and water.</li> <li>IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</li> <li>IF IN EYES: Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses, if present and easy to do so.</li> <li>Continue rinsing.</li> <li>IF exposed or concerned: Get medical advice/attention.</li> <li>If skin irritation or rash occurs: Get medical advice/attention.</li> <li>Collect spillage.</li> <li>Store in a well-ventilated place. Keep container tightly</li> </ul>

## 2.3 Other hazards

No Information

## Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity						
Name According to EEC CAS-No.						
No Information						
Endocrine disrupting properties - Ecotoxicity						
Name According to EEC	CAS-No.					

No Information

## SECTION 3: Composition/Information On Ingredients

#### 3.1 Substances

Not applicable

3.2 Mixtures

### Hazardous ingredients

Name According to EEC EINEC No. CAS-No. REACH Reg No.	<u>%</u>	<u>Classifications</u>		SCL Value: ATE Value: M-Factor:
phenol, polymer with formaldehyde, glycidyl ether 608-164-0 28064-14-4 No Information	25 - <50	H315-317-319-411 Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	SCL Value: ATE Value: M-Factor: (acute)	-
			M-Factor: (chronic)	-

		I	I	
glass oxide	25 - <50	H351	SCL Value:	-
266-046-0				
65997-17-3			ATE Value:	-
No Information		Carc. 2		
			M-Factor:	-
			(acute)	
			M-Factor: (chronic)	-
Xylene	10 - <25	H226-315-332	SCL Value:	-
215-535-7				
1330-20-7			ATE Value:	-
No Information		Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit.		
		2	M-Factor:	-
			(acute)	
			M-Factor:	-
			(chronic)	
Butanone	10 - <25	H225-319-336	SCL Value:	-
201-159-0			JOL Value.	
78-93-3				
No Information			ATE Value:	-
		Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE		
			M-Factor: (acute)	-
			()	
			M-Factor:	-
			(chronic)	

titanium dioxide	2.5 - <10	H351	SCL Value:	-
236-675-5 13463-67-7			ATE Value:	-
No Information		Carc. 2	M-Factor: (acute)	-
			M-Factor: (chronic)	-
Ethylbenzene 202-849-4	1.0 - <2.5	H225-304-315-319-332-373	SCL Value:	-
100-41-4			ATE Value:	-
No Information		Acute Tox. 4 Inhalation, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2	M-Factor: (acute)	-
			M-Factor: (chronic)	-

#### Additional Information:

The text for CLP Hazard Statements shown above (if any) is given in Section 16.

## SECTION 4: First-aid Measures

#### 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

#### AFTER INHALATION: Move to fresh air.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### No Information

#### 4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required. No information available on clinical testing and medical monitoring. Specific

#### toxicological information on substances, if available, can be found in section 11.

#### SECTION 5: Firefighting Measures

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

# 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water spray Dry powder Alcohol-resistant foam Carbon dioxide (CO2). Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

#### **SECTION 6: Accidental Release Measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

#### 6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

#### SECTION 7: Handling and Storage

#### 7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### CONDITIONS TO AVOID: Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

No specific advice for end use available.

## **SECTION 8: Exposure Controls/Personal Protection**

## 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits

(EU)

Name	CAS-No.	LTE	<u>EL ppm</u>	STEL ppm	STEL mg/m3	LTEL mg/m3
phenol, polymer with formaldehyde, glycid ether	yl 28064-14-4					
glass oxide	65997-17-3					
Xylene	1330-20-7		50	100	442	221
Butanone	78-93-3	2	200	300	900	600
titanium dioxide	13463-67-7					
Ethylbenzene	100-41-4		100	200	884	442
Name	CAS-No.	OEL Note				
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4					
glass oxide	65997-17-3					
Xylene	1330-20-7	SK				
Butanone	78-93-3					
titanium dioxide	13463-67-7					
Ethylbenzene	100-41-4	SKIN				

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

## Chemical Name: EC No.:

CAS-No.:

## **DNELs - Derived no effect level**

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required					
Inhalation								
Dermal								

#### PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

#### 8.2 Exposure controls

#### **Personal Protection**

#### **RESPIRATORY PROTECTION:** Respirator with a vapor filter.

**EYE PROTECTION:** Tightly fitting safety goggles.

**HAND PROTECTION:** Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

#### SECTION 9: Physical and Chemical Properties 9.1 Information on basic physical and chemical properties Colour: Viscous Liquid **Physical State** Liquid Odor Epoxy Odor threshold Not determined pН Not determined Melting point / freezing point (°C) Not determined Boiling point or initial boiling point and 65 - 204 boiling range (°C) Flash Point, (°C) 12 Evaporation rate Slower Than Ether Flammability (solid, gas) Not determined Llower and upper explosive limit 1 - 10.1 Vapour Pressure Not determined Relative vapour density Heavier Than Air Density and/or relative density Not determined Solubility in / Miscibility with water Not determined Partition coefficient: n-octanol/water Not determined Auto-ignition temperature (°C) Not determined Decomposition temperature (°C) Not determined Kinematic viscosity Unknown Particle characteristics Not applicable to liquids 9.2 Other information VOC Content g/l: 250

## **SECTION 10: Stability and Reactivity**

Specific Gravity (g/cm3)

1.362

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

- **10.3 Possibility of hazardous reactions** Hazardous polymerisation does not occur.
- **10.4 Conditions to avoid** Direct sources of heat.
- **10.5 Incompatible materials** Strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as definied in Regulation (EC) No 1272/2008

Acute Toxicity: Oral LD50: Inhalation LC50: Dermal LD50:	No information available. No information available. No Information
Irritation:	No information available.
Corrosivity:	No information available.
Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	5000 mg/kg. oral, rat	>2000 mg/kg, rabbit		0.000	0.000
1330-20-7	Xylene	3523 mg/kg, rat, oral	12126 mg/kg, rabbitt	5000 ppm/4 hrs rat, inhalation	0.000	0.000
78-93-3	Butanone	2737 mg/kg rat, oral		5000 ppm / 1 hour rat, inhalation	0.000	0.000

Date Printed: 06/06/2024

13463-67-7	titanium dioxide	10000 mg/m3, oral (rat)			0.000	0.000
100-41-4	Ethylbenzene	3500 mg/kg rat, oral	5510 mg/kg, rabbit	4000 ppm, rat, 4h	0.000	0.000

## Additional Information:

No Information

## 11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Name According to EEC

CAS-No.

No Information

SE	SECTION 12: Ecological Information					
12.1	Toxici	ty:				
	EC	50 48hr (Daphnia):	No info	ormation		
	IC5	0 72hr (Algae):	No infe	ormation		
	LC	50 96hr (fish):	No infe	ormation		
12.2	12.2 Persistence and degradability:		No inf	ormation		
12.3	Bioac	cumulative potential:	No infe	ormation		
12.4	Mobili	ty in soil:	No infe	ormation		
12.5	12.5 Results of PBT and vPvB		The pro	oduct does not meet the	e criteria for PBT/VP	VB in accordance with Annex XIII.
12.6	Endo	rine disrupting properties				
	Endo	ocrine disrupting properties - Ecotoxicity				
	Name According to EEC CAS-No.					
	No I	nformation				
12.7	12.7 Other adverse effects: No information					
<u>CAS-</u>	<u>No.</u>	Name According to EEC		<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
28064	4-14-4	phenol, polymer with formaldehyde, glyc ether	cidyl	No information	No information	
65997	7-17-3	glass oxide		No information	No information	
1330-	-20-7	Xylene		3.82 mg/l	No information	24-30 mg/l, minnow
78-93	3-3	Butanone		No information	No information	
13463	3-67-7	titanium dioxide		>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l

# 100-41-4Ethylbenzene1.37 mg/lNo information32 mg/l (Bluegill)

## **SECTION 13: Disposal Considerations**

**13.1** WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code:	080111
Packaging Waste Code:	150110

## SECTION 14: Transport Information

		ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1	UN-number or ID number	UN 1263	UN 1263	UN 1263	UN 1263
14.2	UN proper shipping name	Paint	Paint	Paint	Paint
14.3	Transport Hazard Class(es)	3	3	3	3
14.4	Packing Group	П	II	II	Ш
14.5	Enviromental Hazards	No Information	No Information	No Information	No Information

14.6	Special precautions for user	Unknown	
	EmS-No.:	F-E, S-E	
14.7	Maritime transport in bulk according to IMO	Unknown	

## SECTION 15: Regulatory Information

intruments

15.1 Safety, health and environmental regulations/legislation for the substance or mixture: National Regulations:

Denmark Product Registration Number:	Not available
Danish MAL Code:	Not available
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	Not available
Norway Product Registration Number:	Not available
Germany WGK Class:	Not available
Covered by Directive 2012/18/EC (Seveso III):	Not applicable
Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:	Not applicable

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## **SECTION 16: Other Information**

## Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

#### Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

- 01 Identification
- 02 Hazard Identification
- 03 Composition/Information On Ingredients
- 08 Exposure Controls/Personal Protection
- 09 Physical and Chemical Properties
- 11 Toxicological Information
- 14 Transportation Information
- 15 Regulatory Information

Revision Statement(s) Changed

#### List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%

#### Date Printed: 06/06/2024

EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as
	modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance
	contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in
	powder form containing 1 $\%$ or more of titanium dioxide which is in the form of
	or incorporated in particles with aerodynamic diameter $\leq$ 10 µm.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.