

Safety Data Sheet

prepared to UN GHS Revision 7



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	1205A5742A	Revision Date:	09/02/2026
Product Name:	PHENOLINE 1205 PART A	Supersedes Date:	New SDS
1.2 Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use. Advised against: others than recommended		
1.3 Details of the supplier of the safety data sheet			
Manufacturer:	StonCor Middle East L.L.C. Plot # B518, Al Quoz Industrial Area 3 P.O. Box: 3034 Dubai, U.A.E.		
	Regulatory / Technical Information: +971 4 347 0460 +971 4 347 0242 (fax)		
Datasheet Produced by:	Rivero, Melody - ehs@stoncor.com		
1.4 Emergency telephone number:	+1 703-741-5970 - North America +1 800-424-9300 - North America +55 11 4349 1359 - South America +52 55 8526 4930 - Central America +44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa +65 3163 8374 - Asia, South Asia, And Oceania		

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
 Hazardous to the aquatic environment, Chronic, category 2
 Carcinogenicity, category 2
 Eye Irritation, category 2A
 Flammable Liquid, category 2
 Skin Irritation, category 2
 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Ethylbenzene, Xylene, titanium dioxide, phenol, polymer with formaldehyde, glycidyl ether, glass oxide

HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P337+313	If eye irritation persists: Get medical advice/attention.
P362+364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
phenol, polymer with formaldehyde, glycidyl ether	608-164-0	28064-14-4	30 - <60	H315-317-319-411	Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1
glass oxide	266-046-0	65997-17-3	30 - <60	H351	Carc. 2
Xylene	215-535-7	1330-20-7	10 - <30	H226-315-332	Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2
Butanone	201-159-0	78-93-3	5.0 - <10	H225-319-336	Eye Irrit. 2, Flam. Liq. 2, Skin Cracking, STOT SE 3 NE
Ethylbenzene	202-849-4	100-41-4	1.0 - <5.0	H225-304-332-373	Acute Tox. 4 Inhalation, Asp. Tox. 1, Flam. Liq. 2, STOT RE 2
titanium dioxide	236-675-5 236-675-5	13463-67-7	1.0 - <5.0	H351	Carc. 2

CAS-No.

28064-14-4
65997-17-3
1330-20-7
78-93-3
100-41-4
13463-67-7

M-Factors

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water spray Dry powder Alcohol-resistant foam Carbon dioxide (CO₂). Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (Middle East)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4				
glass oxide	65997-17-3				
Xylene	1330-20-7	50	100	442	221
Butanone	78-93-3	200	300	900	600
Ethylbenzene	100-41-4	100	200	884	442
titanium dioxide	13463-67-7				

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	
glass oxide	65997-17-3	
Xylene	1330-20-7	SK
Butanone	78-93-3	
Ethylbenzene	100-41-4	SKIN
titanium dioxide	13463-67-7	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Rubber or plastic apron.

Body Protection: Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Viscous Liquid
Physical State	Liquid
Odor	Epoxy
Odor threshold	Not determined
pH	

	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	65 - 204
Flash Point, (°C)	12
Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	1 - 10.1
Vapour Pressure	Not determined
Vapour density	Heavier Than Air
Relative density	Not determined
Solubility in / Miscibility with water	Not determined
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Unknown
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	250.00
Specific Gravity (g/cm³)	1.356

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	5000 mg/kg, oral, rat	>2000 mg/kg, rabbit		0.000	0.000
1330-20-7	Xylene	3523 mg/kg, rat, oral	12126 mg/kg, rabbit	5000 ppm/4 hrs rat, inhalation	0.000	0.000
78-93-3	Butanone	2737 mg/kg rat, oral		5000 ppm / 1 hour rat, inhalation	0.000	0.000
100-41-4	Ethylbenzene	3500 mg/kg rat, oral	5510 mg/kg, rabbit	4000 ppm, rat, 4h	0.000	0.000
13463-67-7	titanium dioxide	10000 mg/m3, oral (rat)			0.000	0.000

Additional Information:

No Information

12. Ecological Information

- 12.1 Toxicity:**
- | | |
|----------------------|----------------|
| EC50 48hr (Daphnia): | No information |
| IC50 72hr (Algae): | No information |
| LC50 96hr (fish): | No information |
- 12.2 Persistence and degradability:** No information
- 12.3 Bioaccumulative potential:** No information
- 12.4 Mobility in soil:** No information
- 12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.
- 12.6 Other adverse effects:** No information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	No information	No information	
65997-17-3	glass oxide	No information	No information	
1330-20-7	Xylene	3.82 mg/l	No information	24-30 mg/l, minnow
78-93-3	Butanone	No information	No information	
100-41-4	Ethylbenzene	1.37 mg/l	No information	32 mg/l (Bluegill)
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l

13. Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

- | | |
|--|-------------------------------------|
| 14.1 UN number | UN 1263 |
| 14.2 UN proper shipping name | Paint |
| Technical name | Not applicable |
| 14.3 Transport hazard class(es) | 3 |
| Subsidiary shipping hazard | Not applicable |
| 14.4 Packing group | II |
| 14.5 Environmental hazards | Marine Pollutant: Yes (Epoxy Resin) |
| 14.6 Special precautions for user | Unknown |
| EmS-No.: | F-E, S-E |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code | Unknown |

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS:



WARNING

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects and other reproductive harm.

No Proposition 65 Reproductive Toxins exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS:



WARNING

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

No Proposition 65 Carcinogens exist in this product.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m ³	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.