

**Safety Data Sheet according to Regulation
(EC) 'No. 2020/878**



SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Identifier	0890A0000B	Revision Date:	20/03/2024
Product Name:	CARBOGUARD 890 PART B	Supersedes Date:	08/07/2020
UFI Code:	No Information		
Contain nanoform:	No		
1.2 Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use. Advised against: others than recommended		
1.3 Details of the supplier of the safety data sheet			
Importer:	None		
Manufacturer:	StonCor Middle East L.L.C. Plot # B518, Al Quoz Industrial Area 3 P.O. Box: 3034 Dubai, U.A.E.		
	Regulatory / Technical Information: +971 4 347 0460 +971 4 347 0242 (fax)		
Datasheet Produced by:	Rivero, Melody - ehs@stoncor.com		
1.4 Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US) 112 (24/7) Croatia +3851 2348 342 (24/7 in Croatian and English) Iceland 112 (24/7) Malta 112 (24/7)		

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 1	H224
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319
Acute Toxicity, Inhalation, category 4	H332
Carcinogenicity, category 1A	H350-1A
STOT, single exposure, category 1	H370
Hazardous to the aquatic environment, Chronic, category 3	H412

2.2 Label elements**Symbol(s) of Product****Signal Word**

Danger

Named Chemicals on Label

Ethylbenzene, Benzyl alcohol, Xylene, 3-Aminomethyl-3,5,5-trimethylcyclohexylamine, quartz (silicon dioxide)

HAZARD STATEMENTS

Flammable Liquid, category 1	H224	Extremely flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
STOT, single exposure, category 1	H370	Causes damage to organs.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

P307+311
 P308+313
 P314
 P333+313
 P403+233

IF exposed, call a POISON CENTER or doctor/physician.
 IF exposed or concerned: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 If skin irritation or rash occurs: Get medical advice/attention.
 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards
 No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Name According to EEC	CAS-No.
No Information	

Endocrine disrupting properties - Ecotoxicity

Name According to EEC	CAS-No.
No Information	

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u> <u>EINEC No.</u> <u>CAS-No.</u> <u>REACH Reg No.</u>	%	<u>Classifications</u>	SCL Value: ATE Value: M-Factor:
quartz (silicon dioxide) 238-878-4 14808-60-7 No Information	50 - <75	H350-370 Carc. 1A, STOT SE 1	SCL Value: - ATE Value: - M-Factor: (acute) - M-Factor: (chronic) -

<p>Xylene 215-535-7 1330-20-7 No Information</p>	2.5 - <10	<p>H226-315-332</p> <p>Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2</p>	<p>SCL Value: -</p> <p>ATE Value: -</p> <p>M-Factor: (acute) -</p> <p>M-Factor: (chronic) -</p>	
<p>Benzyl alcohol 202-859-9 100-51-6 No Information</p>	2.5 - <10	<p>H302-312-319-332</p> <p>Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Eye Irrit. 2</p>	<p>SCL Value: -</p> <p>ATE Value: -</p> <p>M-Factor: (acute) -</p> <p>M-Factor: (chronic) -</p>	
<p>cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol a diglycidyl ether homopolymer 614-657-1 68609-08-5 No Information</p>	2.5 - <10	<p>H411</p> <p>Aquatic Chronic 2</p>	<p>SCL Value: -</p> <p>ATE Value: -</p> <p>M-Factor: (acute) -</p> <p>M-Factor: (chronic) -</p>	

<p>3-Aminomethyl-3,5,5-trimethylcyclohexylamine 220-666-8 2855-13-2 No Information</p>	2.5 - <10	<p>H302-314-317</p> <p>Acute Tox. 4 Oral, Skin Corr. 1B, Skin Sens. 1A</p>	<p>SCL Value: -</p> <p>ATE Value: -</p> <p>M-Factor: (acute) -</p> <p>M-Factor: (chronic) -</p>	
<p>Solvent naphtha (petroleum), light arom. 265-199-0 64742-95-6 No Information</p>	2.5 - <10	<p>H304-411</p> <p>Aquatic Chronic 2, Asp. Tox. 1</p>	<p>SCL Value: -</p> <p>ATE Value: -</p> <p>M-Factor: (acute) -</p> <p>M-Factor: (chronic) -</p>	
<p>Propan-2-ol 200-661-7 67-63-0 No Information</p>	2.5 - <10	<p>H225-319-336</p> <p>Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE</p>	<p>SCL Value: -</p> <p>ATE Value: -</p> <p>M-Factor: (acute) -</p> <p>M-Factor: (chronic) -</p>	

Ethylbenzene 202-849-4 100-41-4 No Information	2.5 - <10	H225-304-315-319-332-373 Acute Tox. 4 Inhalation, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2	SCL Value: ATE Value: M-Factor: (acute) M-Factor: (chronic)	- - - -
urea formaldehyde butilated 614-202-7 68002-19-7 No Information	1.0 - <2.5	H411 Aquatic Chronic 2	SCL Value: ATE Value: M-Factor: (acute) M-Factor: (chronic)	- - - -
Solvent naphtha (petroleum), medium aliph. 265-191-7 64742-88-7 No Information	<0.1	H304 Asp. Tox. 1	SCL Value: ATE Value: M-Factor: (acute) M-Factor: (chronic)	- - - -

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form

explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
quartz (silicon dioxide)	14808-60-7				
Xylene	1330-20-7	50	100	442	221
Benzyl alcohol	100-51-6				
cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol a diglycidyl ether homopolymer	68609-08-5				
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2				
Solvent naphtha (petroleum), light arom.	64742-95-6				
Propan-2-ol	67-63-0				
Ethylbenzene	100-41-4	100	200	884	442
urea formaldehyde butilated	68002-19-7				
Solvent naphtha (petroleum), medium aliph.	64742-88-7				

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
quartz (silicon dioxide)	14808-60-7	
Xylene	1330-20-7	SK
Benzyl alcohol	100-51-6	
cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol a diglycidyl ether homopolymer	68609-08-5	
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	
Solvent naphtha (petroleum), light arom.	64742-95-6	
Propan-2-ol	67-63-0	
Ethylbenzene	100-41-4	SKIN
urea formaldehyde butilated	68002-19-7	

Solvent naphtha (petroleum), medium aliph. 64742-88-7

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

Chemical Name:

EC No.:

CAS-No.:

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation								
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment soil (agricultural)	
Air	

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Colour:	Viscous Liquid
Physical State	Liquid
Odor	Solvent
Odor threshold	Not determined
pH	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point or initial boiling point and boiling range (°C)	65 - 260
Flash Point, (°C)	21

Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined
Lower and upper explosive limit	0.5 - 36
Vapour Pressure	Not determined
Relative vapour density	Heavier Than Air
Density and/or relative density	Not determined
Solubility in / Miscibility with water	Not determined
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Kinematic viscosity	Unknown
Particle characteristics	Not applicable to liquids

9.2 Other information

VOC Content g/l:	217
Specific Gravity (g/cm³)	1.600

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

No Information

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute Toxicity:**

Oral LD50:	No information available.
Inhalation LC50:	No information available.
Dermal LD50:	No Information

Irritation: No information available.

Corrosivity: No information available.

Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
1330-20-7	Xylene	3523 mg/kg, rat, oral	12126 mg/kg, rabbit	5000 ppm/4 hrs rat, inhalation	0.000	0.000
100-51-6	Benzyl alcohol	1230 mg/kg, rat	2000 mg/kg, rabbit	1000 ppm, rat	0.000	0.000
2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine	500 mg/kg oral			0.000	0.000
64742-95-6	Solvent naphtha (petroleum), light arom.	4700 mg/kg, oral, rat	>2000 mg/kg	3670 ppm/8 hours, rat, inhalation	0.000	0.000
67-63-0	Propan-2-ol	4720 mg/kg rat, oral		22500 ppm/8hrs rat, inhalation	0.000	0.000
100-41-4	Ethylbenzene	3500 mg/kg rat, oral	5510 mg/kg, rabbit	4000 ppm, rat, 4h	0.000	0.000
64742-88-7	Solvent naphtha (petroleum), medium aliph.	>2000 mg/kg, oral, rat			0.000	0.000

Additional Information:

No Information

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Name According to EEC	CAS-No.
-----------------------	---------

No Information

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

- 12.2 Persistence and degradability:** No information
- 12.3 Bioaccumulative potential:** No information
- 12.4 Mobility in soil:** No information
- 12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Endocrine disrupting properties**Endocrine disrupting properties - Ecotoxicity**

Name According to EEC	CAS-No.
No Information	

- 12.7 Other adverse effects:** No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
14808-60-7	quartz (silicon dioxide)	No information	No information	
1330-20-7	Xylene	3.82 mg/l	No information	24-30 mg/l, minnow
100-51-6	Benzyl alcohol	230 mg/l	700 mg/l	460 mg/l
68609-08-5	cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol a diglycidyl ether homopolymer	No information	No information	
2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine	No information	No information	
64742-95-6	Solvent naphtha (petroleum), light arom.	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l
67-63-0	Propan-2-ol	No information	No information	
100-41-4	Ethylbenzene	1.37 mg/l	No information	32 mg/l (Bluegill)
68002-19-7	urea formaldehyde butilated	No information	No information	
64742-88-7	Solvent naphtha (petroleum), medium aliph.	No information	No information	

SECTION 13: Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111
Packaging Waste Code: 150110

SECTION 14: Transport Information

	ADR/RID	ADN	IMDG	IATA
14.1 UN-number or ID number	UN 1263	UN 1263	UN 1263	UN 1263
14.2 UN proper shipping name	Paint	Paint	Paint	Paint
14.3 Transport Hazard Class(es)	3	3	3	3
14.4 Packing Group	II	II	II	II
14.5 Enviromental Hazards	No Information	No Information	No Information	No Information

- 14.6 Special precautions for user** Unknown
EmS-No.: F-E, S-E
- 14.7 Maritime transport in bulk according to IMO intruments** Unknown

SECTION 15: Regulatory Information**15.1 Safety, health and environmental regulations/legislation for the substance or mixture:****National Regulations:**

- Denmark Product Registration Number:** Not available
- Danish MAL Code:** Not available
- Danish MAL Code - Mixture:** Not available
- Sweden Product Registration Number:** Not available
- Norway Product Registration Number:** Not available
- Germany WGK Class:** Not available

Covered by Directive 2012/18/EC (Seveso III): Not applicable

Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006: Not applicable

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

Revision Description Changed
 Composition Information Changed
 Substance and/or Product Properties Changed in Section(s):
 01 - Identification
 02 - Hazard Identification
 03 - Composition/Information On Ingredients
 08 - Exposure Controls/Personal Protection
 09 - Physical and Chemical Properties
 11 - Toxicological Information
 14 - Transportation Information
 15 - Regulatory Information
 Revision Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m ³	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail

UN United Nations
IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association
MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC International Bulk Container
RTI Respiratory Tract Irritation
NE Narcotic Effects
IMO International Maritime Organization
Note P: The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.