# **Safety Data Sheet**

# prepared to UN GHS Revision 7



# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 8084A0000A Revision Date: 22/10/2025

Product Name: SEMSTONE 8084 PART A Supersedes Date: New SDS

1.2 Relevant identified uses of the

substance or mixture and uses advised against

Component of multicomponent industrial coatings - Industrial use. Advised against:

others than recommended

1.3 Details of the supplier of the safety data sheet

Manufacturer: StonCor Middle East L.L.C.

Plot # B518, Al Quoz Industrial Area 3

P.O. Box: 3034 Dubai, U.A.E.

Regulatory / Technical Information:

+971 4 347 0460 +971 4 347 0242 (fax)

Datasheet Produced by: Rivero, Melody - ehs@stoncor.com

**1.4 Emergency telephone number:** +1 703-741-5970 - North America

+1 800-424-9300 - North America +55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa

+65 3163 8374 - Asia, South Asia, And Oceania

# 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
Carcinogenicity, category 1B
Eye Irritation, category 2A
Flammable Liquid, category 3
Germ Cell Mutagenicity, category 1B
Reproductive\_ToxicityD\_category\_2
Skin Irritation, category 2
STOT, repeated exposure, category 1

### 2.2 Label elements

# Symbol(s) of Product



# Signal Word

Danger

### Named Chemicals on Label

Styrene

### **HAZARD STATEMENTS**

| Flammable Liquid, category 3           | H226    | Flammable liquid and vapour.                                    |
|--|---------|---|
| Skin Irritation, category 2            | H315    | Causes skin irritation.   |
| Eye Irritation, category 2A            | H319    | Causes serious eye irritation.                                  |
| Acute Toxicity, Inhalation, category 4 | H332    | Harmful if inhaled.   |
| Germ Cell Mutagenicity, category 1B    | H340-1B | May cause genetic defects.                                      |
| Carcinogenicity, category 1B           | H350-1B | May cause cancer.   |
| Reproductive_ToxicityD_category_2      | H361d   | Suspected of damaging the unborn child.                         |
| STOT, repeated exposure, category 1    | H372    | Causes damage to organs through prolonged or repeated exposure. |

### **PRECAUTION PHRASES**

| P201         | Obtain special instructions before use.  |
|--------------|--|
| P202         | Do not handle until all safety precautions have been read and understood.                        |
| D010         |  |
| P210         | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.   |
| P260         | Do not breathe dust/fume/gas/mist/vapours/spray.   |
| P264         | Wash hands thoroughly after handling.  |
| P280         | Wear protective gloves/protective clothing/eye protection/                                       |
|              | face protection.   |
| P284         | Wear respiratory protection.   |
| P304+340     | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes.                                     |
| 1 303 1 330  | Remove contact lenses, if present and easy to do so.   |
|              | Continue rinsing.  |
| P308+313     | IF exposed or concerned: Get medical advice/attention.   |
| P312         | Call a POISON CENTER or doctor/physician if you feel   |
|              | unwell.  |
| P314         | Get medical advice/attention if you feel unwell.   |
| P332+313     | If skin irritation occurs: Get medical advice/attention.   |
| P337+313     | If eye irritation persists: Get medical advice/attention.  |
| P403+233     | Store in a well-ventilated place. Keep container tightly   |
|              |  |

# 2.3 Other hazards

No Information

### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

closed.

# 3. Composition/Information On Ingredients

#### 3.2 Mixtures

| Hazard | lous i | inared | ients |
|--------|--------|--------|-------|
|        |        |        |       |

| Name According to EEC Styrene              | EINEC No.<br>202-851-5 | <u>CAS-No.</u><br>100-42-5 | <u>%</u><br>30 - <60 | Classifications<br>H226-315-319-332-3<br>61d-372 | Acute Tox. 4 Inhalation, Eye<br>Irrit. 2, Flam. Liq. 3, Repr. 2,<br>Skin Irrit. 2, STOT RE 1 |
|--|------------------------|----------------------------|----------------------|--|--|
| silane, 3-(glycidyloxy)<br>propyl          | 219-784-2              | 2530-83-8                  | 1.0 - <5.0           | H318   | Eye Dam. 1   |
| Solvent naphtha (petroleum), medium aliph. | 265-191-7              | 64742-88-7                 | 0.1 - <1.0           | H304-372   | Asp. Tox. 1, STOT RE 1   |
| cobalt 2-ethylhexanoate                    | 205-250-6              | 136-52-7                   | 0.1 - <1.0           | H317-400   | Aquatic Acute 1, Skin Sens.  |

CAS-No.

M-Factors

100-42-5 2530-83-8 64742-88-7 136-52-7

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

### 4. First-aid Measures

#### 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

No Information

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# 5. Fire-fighting Measures

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

#### 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

# 7. Handling and Storage

### 7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

No specific advice for end use available.

# 8. Exposure Controls/Personal Protection

#### 8.1 Control parameters

Ingredients with Occupational Exposure Limits (Middle East)

| <u>Name</u> | <u>CAS-No.</u> | LTEL ppm | STEL ppm | STEL mg/m3 | LTEL mg/m3 |
|-------------|----------------|----------|----------|------------|------------|
| Styrene     | 100-43         | 2-5      |          |            |            |

silane, 3-(glycidyloxy) propyl 2530-83-8

Solvent naphtha (petroleum), medium 64742-88-7

aliph.

cobalt 2-ethylhexanoate 136-52-7

Name CAS-No. OEL Note

Styrene 100-42-5

silane, 3-(glycidyloxy) propyl 2530-83-8

Solvent naphtha (petroleum), medium 64742-88-7

aliph.

cobalt 2-ethylhexanoate 136-52-7

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

#### 8.2 Exposure controls

**Personal Protection** 

**RESPIRATORY PROTECTION:** Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Impervious gloves. Take note of the information given by the producer concerning permeability and

break through times, and of special workplace conditions (mechanical strain, duration of contact).

Body Protection: Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined

areas.

# 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Viscous Liquid

Physical State Liquid
Odor Solvent

Odor threshold Not determined

pH Not determined

Melting point / freezing point (°C)

Not determined

Boiling point/range (°C) 80 - 285

Flash Point, (°C) 23

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive limits

Vapour Pressure Not determined
Vapour density Not determined

Relative density Not determined

Solubility in / Miscibility with water Not determined

Partition coefficient: n-octanol/water Not determined

Auto-ignition temperature (°C) Not determined

Not determined

Decomposition temperature (°C) Not determined

**Viscosity** Unknown

Explosive properties Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/l: 3.00
Specific Gravity (g/cm3) 1.030

# 10. Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

# 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Direct sources of heat.

### 10.5 Incompatible materials

Strong oxidizing agents.

### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

### 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No information available.

Inhalation LC50: No information available.

Irritation: No information available.

Corrosivity: No information available.

**Sensitization:** No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.    | Chemical Name                              | Oral LD50                 | Dermal LD50 | Vapor LC50    | Gas LC50 | Dust/Mist LC50 |
|------------|--|---------------------------|-------------|---------------|----------|----------------|
| 100-42-5   | Styrene                                    | 2650 mg/kg                | >2000 mg/kg | 2800 ppm, 4 h | 0.000    | 0.000          |
| 64742-88-7 | Solvent naphtha (petroleum), medium aliph. | >2000 mg/kg,<br>oral, rat |             |               | 0.000    | 0.000          |

#### Additional Information:

No Information

# 12. Ecological Information

# 12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

12.5 Results of PBT and vPvB

assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects:

No information

| CAS-No.    | <u>Chemical Name</u>                       | EC50 48hr      | IC50 72hr      | LC50 96hr |
|------------|--|----------------|----------------|-----------|
| 100-42-5   | Styrene                                    | 4.7 mg/l       | No information | 4.08 mg/l |
| 2530-83-8  | silane, 3-(glycidyloxy) propyl             | No information | No information |           |
| 64742-88-7 | Solvent naphtha (petroleum), medium aliph. | No information | No information |           |
| 136-52-7   | cobalt 2-ethylhexanoate                    | No information | No information |           |

# 13. Disposal Considerations

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

UN 1263 14.1 UN number 14.2 UN proper shipping name Paint

> Not applicable **Technical name**

14.3 Transport hazard class(es)

Subsidiary shipping hazard Not applicable

14.4 Packing group PG II 14.5 Environmental hazards Unknown 14.6 Special precautions for user Unknown EmS-No.: F-E. S-E Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Unknown

# 15. Regulatory Information

Safety, health and environmental regulations/legislation for the substance or mixture:

**National Regulations:** 

Not available **Denmark Product Registration Number:** Danish MAL Code: Not available Danish MAL Code - Mixture: Not available Not available **Sweden Product Registration Number:** 

**Norway Product Registration Number:** Not available

Not available WGK Class:

#### 15.2 **Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# Other Information

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

#### Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

#### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission ΕU European Union United States IIS

Chemical Abstract Service CAS

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu m$ .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.