

Safety Data Sheet
according to Regulation (EC)
No. 453/2010



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	EP87010700	Revision Date:	04/08/2015
Product Name:	Carbozinc 8701	Supersedes Date:	New SDS

1.2 Relevant identified uses of the substance or mixture and uses advised against Base component of 2 components coatings - Industrial use.

1.3 Details of the supplier of the safety data sheet

Importer: None

Manufacturer: StonCor Middle East L.L.C.
Plot # B518, Al Quoz Industrial Area 3
P.O. Box: 3034
Dubai, U.A.E.

Regulatory / Technical Information:
+971 4 347 0460
+971 4 347 0242 (fax)

Datasheet Produced by: Valderrama, Maja - ehs@stoncor.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)
+ 971 50 455 7641 (Richard D'Souza - Technical Director)
+ 971 50 657 81 21 (N. Kumaresh - Operations Manager)

2. Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 1	H224
Skin Sensitizer, category 1	H317
Acute Toxicity, Inhalation, category 4	H332

Reproductive Toxicity, category 1A
 Hazardous to the aquatic environment, Acute, category 1
 Hazardous to the aquatic environment, Chronic, category 1

H360-1A
 H400
 H410

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

m-xylene, reaction product: bisphenol-a-(epichlorohydrin) epoxy resin (number average molecularweight <= 700)

HAZARD STATEMENTS

Flammable Liquid, category 1	H224	Extremely flammable liquid and vapour.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Reproductive Toxicity, category 1A	H360-1A	May damage fertility or the unborn child.
Hazardous to the aquatic environment, Acute, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, Chronic, category 1	H410	Very toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Not applicable

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

<u>CAS-No.</u>	<u>EINEC No.</u>	<u>Name According to EEC</u>	<u>%</u>
7440-66-6	231-175-3	zinc powder (stabilized)	50-75
108-38-3	203-576-3	m-xylene	2.5-10
117-81-7	204-211-0	bis(2-ethylhexyl) phthalate	1.0-2.5
14807-96-6		talca	1.0-2.5
25068-38-6	500-033-5	reaction product: bisphenol-a-(epichlorohydrin) epoxy resin (number average molecularweight <= 700)	1.0-2.5
1314-13-2	215-222-5	zinc oxide	1.0-2.5
64742-94-5	265-198-5	solvent naphtha (petroleum), heavy aromatic	1.0-2.5
12001-26-2	601-648-2	mica	1.0-2.5
78-83-1	201-148-0	2-methylpropan-1-ol	0.1-1.0
50-00-0	200-001-8	formaldehyde	<0.1

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
7440-66-6		GHS02-GHS09	H250-260-400-410	
108-38-3		GHS02-GHS07	H226-312-315-332	
117-81-7		GHS08	H360	
14807-96-6				
25068-38-6	01-2119456619-26-0029	GHS07-GHS09	H315-317-319-335-411	
1314-13-2		GHS09	H400-410	
64742-94-5		GHS08	H304	
12001-26-2		GHS07	H319-335	
78-83-1		GHS02-GHS05-GHS07	H226-315-318-335-336	
50-00-0		GHS02-GHS05-GHS06-GHS08-GHS09	H226-301-311-314-317-331-334-335-341-350-400	

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Toxic if swallowed. Irritating to eyes, respiratory system and skin.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage**7.1 Precautions for safe handling**

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection**8.1 Control parameters**

Ingredients with Occupational Exposure Limits (EU)

Name	%	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3	OEL Note
zinc powder (stabilized)	50-75					
m-xylene	2.5-10	50	100	442	221	SKIN
bis(2-ethylhexyl) phthalate	1.0-2.5					
talc	1.0-2.5					
reaction product: bisphenol-a-(epichlorohydrin epoxy resin (number average molecularweight <= 700)	1.0-2.5					

zinc oxide	1.0-2.5
solvent naphtha (petroleum), heavy aromatic	1.0-2.5
mica	1.0-2.5
2-methylpropan-1-ol	0.1-1.0
formaldehyde	<0.1

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified at the EU level under the dangerous substances and preparations regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

reaction product: bisphenol-a-(epichlorohydrin) epoxy resin (number average molecularweight <= 700)

EC No.:
500-033-5

CAS-No.:
25068-38-6

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					0.75 mg/kg		0.75 mg/kg
Inhalation		12.25 mg/m ³		12.25 mg/m ³				
Dermal		8.33 mg/kg		8.33 mg/kg		3.571 mg/kg		3.571 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.006 mg/l
Fresh water sediments	0.996 mg/l
Marine water	0.0006 mg/l
Marine sediments	0.0996 mg/l
Food chain	
Microorganisms in sewage treatment	10 mg/l
soil (agricultural)	0.196 mg/kg
Air	

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Viscous Green Liquid
Physical State	Liquid
Odor	Solvent
Odor threshold	Not determined
pH	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	78 - 260
Flash Point, (°C)	18

Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	1 - 11.2
Vapour Pressure	Not determined
Vapour density	Heavier than Air
Relative density	Not determined
Solubility in / Miscibility with water	
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Unknown
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	350
Specific Gravity (g/cm³)	3.000

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50:

Inhalation LC50:

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
117-81-7	bis(2-ethylhexyl) phthalate	30,600 mg/kg, oral, rat		
25068-38-6	reaction product: bisphenol-a-(epichlorohydrin) epoxy resin (number average molecularweight <= 700)	>2000 mg/kg, rat, oral	>2000 mg/kg, rat	
1314-13-2	zinc oxide	>2000 mg/kg		
12001-26-2	mica	>16000 mg/kg		
50-00-0	formaldehyde	100 mg/kg, oral, rat		250 - 590 mg/cu m

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
7440-66-6	zinc powder (stabilized)	No information	No information	
108-38-3	m-xylene	No information	No information	
117-81-7	bis(2-ethylhexyl) phthalate	No information	No information	
14807-96-6	talc	No information	No information	

25068-38-6	reaction product: bisphenol-a-(epichlorohydrin) epoxy resin (number average molecularweight <= 700)	1.8 mg/l	No information	1.5-7.7 mg/L
1314-13-2	zinc oxide	No information	No information	
64742-94-5	solvent naphtha (petroleum), heavy aromatic	No information	No information	
12001-26-2	mica	No information	No information	
78-83-1	2-methylpropan-1-ol	No information	No information	
50-00-0	formaldehyde	No information	No information	

Further Ecological Information

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

CAS-No.	Name According to EEC
25068-38-6	reaction product: bisphenol-a-(epichlorohydrin) epoxy resin (number average molecularweight <= 700)

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: No Information
Packaging Waste Code: 150110

14. Transport Information

14.1	UN number	UN 1263
14.2	UN proper shipping name	Paint
	Technical name	
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	
14.4	Packing group	II
14.5	Environmental hazards	
14.6	Special precautions for user	Not applicable
	EmS-No.:	
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:

Danish MAL Code:

Sweden Product Registration Number:

Norway Product Registration Number:

WGK Class:

Chemical Safety Assessment:

15.2 No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H250	Catches fire spontaneously if exposed to air.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

This is a new Safety Data Sheet (SDS).

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark
 ESIS (The European Chemical Substances Information System), provided by the European Commission
 Joint Research Centre in Ispra, Italy
 Annex VI of the EU Council Directive 67/548/EEC
 Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC
 European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of
 substances and mixtures (CLP Regulation)
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit

OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.