Safety Data Sheet according to Regulation (EC) 'No. 2020/878



SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 **Product Identifier** 0893O7035A **Revision Date**: 05/08/2024

Product Name: CARBOGUARD 893 MIO PART A Supersedes Date: 09/06/2014

UFI Code: No Information

Contain nanoform:

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Component of multicomponent industrial coatings - Industrial use. Advised against:

others than recommended

1.3 Details of the supplier of the safety data sheet

Importer: None

Manufacturer: StonCor Middle East L.L.C.

Plot # B518, Al Quoz Industrial Area 3

P.O. Box: 3034 Dubai, U.A.E.

Regulatory / Technical Information:

+971 4 347 0460 +971 4 347 0242 (fax)

Datasheet Produced by: Rivero, Melody - ehs@stoncor.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)

112 (24/7)

Croatia +3851 2348 342 (24/7 in Croatian and English)

Iceland 112 (24/7) Malta 112 (24/7)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 1	H224
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319
Carcinogenicity, category 1A	H350-1A
Reproductive Toxicity, category 1A	H360-1A
STOT, single exposure, category 1	H370
Hazardous to the aquatic environment, Chronic, category 2	H411

2.2 Label elements

Symbol(s) of Product









Signal Word

Danger

Named Chemicals on Label

quartz (silicon dioxide), Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

HAZARD STATEMENTS

Flammable Liquid, category 1	H224	Extremely flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
Reproductive Toxicity, category 1A	H360-1A	May damage fertility or the unborn child.
STOT, single exposure, category 1	H370	Causes damage to organs.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do so.
	Continue rinsing.
P307+311	IF exposed, call a POISON CENTER or doctor/physician.
P308+313	IF exposed or concerned: Get medical advice/attention.

P308+P313 IF exposed or concerned: Get medical advice/attention

P314 Get medical advice/attention if you feel unwell.

P333+313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

P403+233 Store in a well-ventilated place. Keep container tightly

closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Name According to EEC CAS-No.

No Information

Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.

No Information

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

Name According to EEC EINEC No. CAS-No. REACH Reg No.	<u>%</u>	<u>Classifications</u>	SCL Value: ATE Value: M-Factor:	
quartz (silicon dioxide) 238-878-4	25 - <50	H350-370	SCL Value:	-
14808-60-7 No Information		0 44 0707 05 4	ATE Value:	-
NO IIIIOIIIIauoii		Carc. 1A, STOT SE 1	M-Factor: (acute)	-
			M-Factor: (chronic)	-

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) 500-033-5 25068-38-6 01-2119456619-26-0029	10 - <25	H315-317-319-411 Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	SCL Value: ATE Value: M-Factor: (acute)	-
			M-Factor: (chronic)	-
titanium dioxide 236-675-5	10 - <25	H351	SCL Value:	-
13463-67-7			ATE Value:	-
No Information		Carc. 2		
			M-Factor: (acute)	-
			M-Factor: (chronic)	-
Bis(2-ethylhexyl) phthalate 204-211-0	2.5 - <10	H360	SCL Value:	-
117-81-7			ATE Value:	-
No Information		Repr. 1A		
			M-Factor: (acute)	-
			M-Factor: (chronic)	-

Xylene 215-535-7 1330-20-7 No Information	2.5 - <10	H226-315-332 Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2	SCL Value: ATE Value: M-Factor: (acute)	-
			M-Factor: (chronic)	-
trizinc bis(orthophosphate)	2.5 - <10	H302-400-410	SCL Value:	-
231-944-3 7779-90-0 No Information		Acute Tox. 4 Oral, Aquatic Acute 1, Aquatic	ATE Value:	-
		Chronic 1	M-Factor: (acute)	-
			M-Factor: (chronic)	-
Butanone 201-159-0	1.0 - <2.5	H225-319-336	SCL Value:	-
78-93-3			ATE Value:	-
No Information		Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE	M-Factor: (acute)	-
			M-Factor: (chronic)	-

silicon dioxide (amorphous) 231-545-4	1.0 - <2.5	H372	SCL Value:	-
7631-86-9			ATE Value:	-
No Information		STOT RE 1		
			M-Factor: (acute)	-
			M-Factor:	_
			(chronic)	
Propan-2-ol	1.0 - <2.5	H225-319-336	SCL Value:	-
200-661-7				
67-63-0			ATE Value:	-
No Information		Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE	M-Factor:	_
			(acute)	-
			M-Factor:	_
			(chronic)	
alumina trihydrate	1.0 - <2.5		SCL Value:	-
21645-51-2				
No Information			ATE Value:	-
			M-Factor:	_
			(acute)	
			M-Factor:	-
			(chronic)	

Solvent naphtha (petroleum), medium aliph.	0.1 - <1.0	H304	SCL Value:	-
265-191-7 64742-88-7			ATE Value:	-
No Information		Asp. Tox. 1	M-Factor: (acute)	-
			M-Factor: (chronic)	-

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Dry powder Foam Carbon dioxide (CO2).

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment.

6.1.2 For emergency responders

No Information

6.2 Environmental precautions

No Information

6.3 Methods and material for containment and cleaning up

Pick up and transfer to properly labelled containers. No special environmental precautions required. After cleaning, flush away traces with water.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Avoid prolonged contact with eyes, skin and clothing.

When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid dust accumulation in enclosed space.

STORAGE CONDITIONS: Keep tightly closed in a dry and cool place.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
quartz (silicon dioxide)	14808-60-7				
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6				
titanium dioxide	13463-67-7				
Bis(2-ethylhexyl) phthalate	117-81-7				
Xylene	1330-20-7	50	100	442	221
trizinc bis(orthophosphate)	7779-90-0				
Butanone	78-93-3	200	300	900	600
silicon dioxide (amorphous)	7631-86-9				
Propan-2-ol	67-63-0				
alumina trihydrate	21645-51-2				
Solvent naphtha (petroleum), medium ali	oh. 64742-88-7				

Name	CAS-No.	OEL Note
quartz (silicon dioxide)	14808-60-7	
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	
titanium dioxide	13463-67-7	
Bis(2-ethylhexyl) phthalate	117-81-7	
Xylene	1330-20-7	SK
trizinc bis(orthophosphate)	7779-90-0	
Butanone	78-93-3	
silicon dioxide (amorphous)	7631-86-9	
Propan-2-ol	67-63-0	
alumina trihydrate	21645-51-2	
Solvent naphtha (petroleum), medium aliph.	64742-88-7	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

Chemical Name:

EC No.: CAS-No.:

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required	<u> </u>		<u> </u>		
Inhalation								
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In case of insufficient ventilation wear suitable respiratory equipment.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Colour: Viscous Liquid, Red or Grey Colour

Physical State Liquid
Odor Epoxy

Odor threshold

PH

Not determined

Not determined

Melting point / freezing point (°C)

Not determined

Not determined

79 - 241

boiling range (°C)

0

Flash Point, (°C) 8

Evaporation rate Slower Than Ether
Flammability (solid, gas) Not determined
Llower and upper explosive limit Not determined

Vapour Pressure

Relative vapour density

Density and/or relative density

Solubility in / Miscibility with water

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Not determined

Not determined

Not determined

Not determined

Kinematic viscosity Unknown

Particle characteristics Not applicable to liquids

9.2 Other information

VOC Content g/l: 195

Specific Gravity (g/cm3) 1.610

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Avoid dust accumulation in enclosed space.

10.5 Incompatible materials

No Information

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as definied in Regulation (EC) No 1272/2008

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Dermal LD50: No Information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25068-38-6	Reaction product: bisphenol- A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	>2000 mg/kg, rat, oral	>2000 mg/kg, rat		0.000	0.000
13463-67-7	titanium dioxide	10000 mg/m3, oral (rat)			0.000	0.000
117-81-7	Bis(2-ethylhexyl) phthalate	30,600 mg/kg, oral, rat			0.000	0.000
1330-20-7	Xylene	3523 mg/kg, rat, oral	12126 mg/kg, rabbitt	5000 ppm/4 hrs rat, inhalation	0.000	0.000
7779-90-0	trizinc bis(orthophosphate)	552 mg/kg, oral rat			0.000	0.000
78-93-3	Butanone	2737 mg/kg rat, oral		5000 ppm / 1 hour rat, inhalation	0.000	0.000
7631-86-9	silicon dioxide (amorphous)	3,160 mg/kg, rat			0.000	0.000

67-63-0 Propan-2-ol 4720 mg/kg rat, 22500 ppm/8hrs rat, inhalation 0.000 0.000

64742-88-7 Solvent naphtha (petroleum), >2000 mg/kg, oral, rat 0.000 0.000

Additional Information:

No Information

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Name According to EEC CAS-No.

No Information

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.

No Information

12.7 Other adverse effects: No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
14808-60-7	quartz (silicon dioxide)	No information	No information	
25068-38-6	Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
117-81-7	Bis(2-ethylhexyl) phthalate	No information	No information	

1330-20-7	Xylene	3.82 mg/l	No information	24-30 mg/l, minnow
7779-90-0	trizinc bis(orthophosphate)	No information	No information	
78-93-3	Butanone	No information	No information	
7631-86-9	silicon dioxide (amorphous)	No information	No information	
67-63-0	Propan-2-ol	No information	No information	
21645-51-2	alumina trihydrate	No information	No information	
64742-88-7	Solvent naphtha (petroleum), medium aliph.	No information	No information	

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111 **Packaging Waste Code:** 150110

SECTION 14: Transport Information

		ADR/RID	ADN	IMDG	IATA
14.1	UN-number or ID number	UN 1263	UN 1263	UN 1263	UN 1263
14.2	UN proper shipping name	Paint	Paint	Paint	Paint
14.3	Transport Hazard Class(es)	3	3	3	3
14.4	Packing Group	II	II	II	II
14.5	Enviromental Hazards	No Information	No Information	No Information	No Information

14.6 Special precautions for user Unknown

EmS-No.: F-E, S-E

14.7 Maritime transport in bulk according to IMO Unknown

intruments

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

Germany WGK Class: Not available

Covered by Directive 2012/18/EC (Seveso III): Not applicable

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006: Not applicable

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments. Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit

STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million
mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10:

The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μm .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.