# Safety Data Sheet according to Regulation (EC) 'No. 2020/878



# SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 **Product Identifier** 0134A0000B **Revision Date**: 03/05/2024

Product Name: CARBOTHANE 134 PART B Supersedes Date: 26/08/2020

UFI Code: No Information

Contain nanoform:

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Component of multicomponent industrial coatings - Industrial use. Advised against:

others than recommended

1.3 Details of the supplier of the safety data sheet

Importer: None

Manufacturer: StonCor Middle East L.L.C.

Plot # B518, Al Quoz Industrial Area 3

P.O. Box: 3034 Dubai, U.A.E.

Regulatory / Technical Information:

+971 4 347 0460 +971 4 347 0242 (fax)

Datasheet Produced by: Rivero, Melody - ehs@stoncor.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)

112 (24/7)

Croatia +3851 2348 342 (24/7 in Croatian and English)

Iceland 112 (24/7) Malta 112 (24/7)

# **SECTION 2: Hazards Identification**

## 2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

## **HAZARD STATEMENTS**

Flammable Liquid, category 3	H226
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Acute Toxicity, Inhalation, category 4	H332
STOT, single exposure, category 3, RTI	H335

#### 2.2 Label elements

# Symbol(s) of Product





## Signal Word

Warning

## Named Chemicals on Label

Ethylbenzene, Xylene, homopolymer of hdi

## **HAZARD STATEMENTS**

Flammable Liquid, category 3 Skin Irritation, category 2	H226 H315	Flammable liquid and vapour. Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
PRECAUTION PHRASES		
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.

## 2.3 Other hazards

No Information

# Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# **Endocrine disrupting properties - Toxicity**

Name According to EEC CAS-No.

No Information

# Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.

No Information

# **SECTION 3: Composition/Information On Ingredients**

## 3.1 Substances

Not applicable

# 3.2 Mixtures

# Hazardous ingredients

Name According to EEC EINEC No. CAS-No. REACH Reg No.	<u>%</u>	<u>Classifications</u>	,	CCL Value: ATE Value: M-Factor:
homopolymer of hdi 500-060-2	50 - <75	H317-332-335	SCL Value:	-
28182-81-2 No Information		Acute Tox. 4 Inhalation, Skin Sens. 1, STOT	ATE Value:	-
		SE 3 RTI	M-Factor: (acute)	-
			M-Factor: (chronic)	-
2-methoxy-1-methylethyl- acetate	10 - <25	H226	SCL Value:	-
203-603-9 108-65-6 No Information		Flam. Liq. 3	ATE Value:	-
INO IIIOIIIIauoii			M-Factor: (acute)	-
			M-Factor: (chronic)	-

Xylene 215-535-7	10 - <25	H226-315-332	SCL Value:	-
1330-20-7			ATE Value:	-
No Information		Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2	M-Factor: (acute)	-
			M-Factor: (chronic)	-
Ethylbenzene 202-849-4	2.5 - <10	H225-304-315-319-332-373	SCL Value:	-
100-41-4			ATE Value:	-
No Information		Acute Tox. 4 Inhalation, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2	M-Factor: (acute)	-
			M-Factor: (chronic)	-

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

#### **SECTION 4: First-aid Measures**

## 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

No Information

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if

available, can be found in section 11.

# **SECTION 5: Firefighting Measures**

## 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

# 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# **SECTION 6: Accidental Release Measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

## 6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

## **SECTION 7: Handling and Storage**

#### 7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

No specific advice for end use available.

# **SECTION 8: Exposure Controls/Personal Protection**

# 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
homopolymer of hdi	28182-81-2				
2-methoxy-1-methylethyl-acetate	108-65-6	50	100	550	275
Xylene	1330-20-7	50	100	442	221
Ethylbenzene	100-41-4	100	200	884	442

Name CAS-No. OEL Note

homopolymer of hdi 28182-81-2

2-methoxy-1-methylethyl-acetate 108-65-6 SKIN

Xylene 1330-20-7 SK

Ethylbenzene 100-41-4 SKIN

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

**Chemical Name:** 

EC No.: CAS-No.:

#### **DNELs - Derived no effect level**

		Wo	orkers			Con	sumers	
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required					
Inhalation								
Dermal								

#### PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

## 8.2 Exposure controls

## **Personal Protection**

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

**HAND PROTECTION:** Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

#### **OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# **SECTION 9: Physical and Chemical Properties**

9.1 Information on basic physical and chemical properties

Colour: Colorless, Mobil Liquid

Physical State Liquid

Odor Slight Odor

Odor threshold Not determined

**pH** Not determined

Melting point / freezing point (°C) Not determined

Boiling point or initial boiling point and

boiling range (°C)

128 - N.D.

Flash Point, (°C) 33

Evaporation rate Not determined Flammability (solid, gas) Not determined

Llower and upper explosive limit 0.9 - 7.6

Vapour Pressure

Relative vapour density

Not determined

Density and/or relative density

Not determined

Solubility in / Miscibility with water

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Not determined

Not determined

Not determined

Kinematic viscosity Unknown

Particle characteristics Not applicable to liquids

9.2 Other information

VOC Content g/l: 408

Specific Gravity (g/cm3) 1.065

# **SECTION 10: Stability and Reactivity**

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

# 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Direct sources of heat.

## 10.5 Incompatible materials

Strong oxidizing agents.

## 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as definied in Regulation (EC) No 1272/2008

**Acute Toxicity:** 

Oral LD50: No information available.

Inhalation LC50: No information available.

Dermal LD50: No Information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

**STOT-repeated exposure:** No information available.

**Aspiration hazard:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

9	CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
	28182-81-2	homopolymer of hdi	5000 mg/kg, oral, rat		18500 mg/m3/1H inhalation, rat	0.000	0.000
	108-65-6	2-methoxy-1-methylethyl- acetate	8532 mg/kg, oral (rat)	>5000 mg/kg	1105 mg/m3/4H	0.000	0.000
	1330-20-7	Xylene	3523 mg/kg, rat, oral	12126 mg/kg, rabbitt	5000 ppm/4 hrs rat, inhalation	0.000	0.000
	100-41-4	Ethylbenzene	3500 mg/kg rat, oral	5510 mg/kg, rabbit	4000 ppm, rat, 4h	0.000	0.000

#### Additional Information:

No Information

11.2 Information on other hazards

**Endocrine disrupting properties - Toxicity** 

Name According to EEC CAS-No.

No Information

# **SECTION 12: Ecological Information**

12.1 Toxicity:

EC50 48hr (Daphnia):No informationIC50 72hr (Algae):No informationLC50 96hr (fish):No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

**12.4 Mobility in soil:**No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.

No Information

12.7 Other adverse effects: No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
28182-81-2	homopolymer of hdi	No information	No information	
108-65-6	2-methoxy-1-methylethyl-acetate	No information	No information	
1330-20-7	Xylene	3.82 mg/l	No information	24-30 mg/l, minnow
100-41-4	Ethylbenzene	1.37 mg/l	No information	32 mg/l (Bluegill)

# **SECTION 13: Disposal Considerations**

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111 Packaging Waste Code: 150110

# **SECTION 14: Transport Information**

		ADR/RID	ADN	IMDG	IATA
14.1	UN-number or ID number	UN 1263	UN 1263	UN 1263	UN 1263
14.2	UN proper shipping name	Paint	Paint	Paint	Paint
14.3	Transport Hazard Class(es)	3	3	3	3
14.4	Packing Group	III	III	III	III
14.5	Enviromental Hazards	No Information	No Information	No Information	No Information

14.6 Special precautions for user Unknwon

**EmS-No.:** F-E, S-E

14.7 Maritime transport in bulk according to IMO Unknown

intruments

# **SECTION 15: Regulatory Information**

**Denmark Product Registration Number:** 

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

**National Regulations:** 

Danish MAL Code:Not availableDanish MAL Code - Mixture:Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

Germany WGK Class: Not available

Not available

Covered by Directive 2012/18/EC (Seveso III): Not applicable

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006: Not applicable

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

# 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# SECTION 16: Other Information

# Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

#### Reasons for revision

Revision Description Changed Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

02 - Hazard Identification

03 - Composition/Information On Ingredients
08 - Exposure Controls/Personal Protection

09 - Physical and Chemical Properties

11 - Toxicological Information14 - Transportation Information15 - Regulatory Information

Revision Statement(s) Changed

#### List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

#### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million
mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter
mg/kg Milligrams per kilogram
N/A Not applicable

LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu m$ .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.