# Safety Data Sheet

prepared to UN GHS Revision 7

## 1. Identification of the Substance/Mixture and the Company/Undertaking

**1.1 Product Identifier** 3000PZ700A

**Revision Date:** 28/11/2025

**Supersedes Date:** New SDS

**Product Name:** THERMO-LAG 3000-P GREY
Z700 PART A

**1.2 Relevant identified uses of the substance or mixture and uses advised against** Component of multicomponent industrial coatings - Industrial use. Advised against: others than recommended

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer:**

StonCor Middle East L.L.C.
Plot # B518, Al Quoz Industrial Area 3
P.O. Box: 3034
Dubai, U.A.E.

Regulatory / Technical Information:
+971 4 347 0460
+971 4 347 0242 (fax)

**Datasheet Produced by:** Rivero, Melody - ehs@stoncor.com

**1.4 Emergency telephone number:**

+1 703-741-5970 - North America
+1 800-424-9300 - North America
+55 11 4349 1359 - South America
+52 55 8526 4930 - Central America
+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa
+65 3163 8374 - Asia, South Asia, And Oceania

## 2. Hazard Identification

**2.1 Classification of the substance or mixture**

Hazardous to the aquatic environment, Chronic, category 2
Carcinogenicity, category 2
Eye Irritation, category 2A
Skin Irritation, category 2
Skin Sensitizer, category 1
STOT, repeated exposure, category 2

### 2.2 Label elements

**Symbol(s) of Product**

**Signal Word**

Warning

**Named Chemicals on Label**

melamine, titanium dioxide, Trimethylolpropane triacrylate, Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

**HAZARD STATEMENTS**

| | | |
|---|---|---|
| Skin Irritation, category 2 | H315 | Causes skin irritation. |
| Skin Sensitizer, category 1 | H317 | May cause an allergic skin reaction. |
| Eye Irritation, category 2A | H319 | Causes serious eye irritation. |
| Carcinogenicity, category 2 | H351 | Suspected of causing cancer. |
| STOT, repeated exposure, category 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| Hazardous to the aquatic environment, Chronic, category 2 | H411 | Toxic to aquatic life with long lasting effects. |

**PRECAUTION PHRASES**

| | |
|---|---|
| P201 | Obtain special instructions before use. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P264 | Wash hands thoroughly after handling. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/ face protection. |
| P284 | Wear respiratory protection. |
| P302+352 | IF ON SKIN: Wash with plenty of soap and water. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. |
| P308+313 | IF exposed or concerned: Get medical advice/attention. |
| P314 | Get medical advice/attention if you feel unwell. |
| P333+313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P337+313 | If eye irritation persists: Get medical advice/attention. |
| P362+364 | Take off contaminated clothing and wash it before reuse. |
| P391 | Collect spillage. |
| P501 | Dispose of contents and container in accordance with all local, regional, national and international regulations. |

### 2.3 Other hazards

No Information

**Results of PBT and vPvB assessment:**

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## 3. Composition/Information On Ingredients

### 3.2 Mixtures

**Hazardous ingredients**

| Name According to EEC | EINEC No. | CAS-No. | % | Classifications |
|---|---|---|---|---|

| | | | | | |
|---|---|---|---|---|---|
| Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 500-033-5 | 25068-38-6 | 30 - <60 | H315-317-319-411 | Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1 |
| melamine pyrophosphate | 239-590-1 | 15541-60-3 | 10 - <30 | | |
| melamine | 203-615-4 | 108-78-1 | 10 - <30 | H351-373 | Carc. 2, STOT RE 2 |
| pentaerythritol | | 115-77-5 | 10 - <30 | | |
| titanium dioxide | 236-675-5 236-675-5 | 13463-67-7 | 5.0 - <10 | H351 | Carc. 2 |
| Trimethylolpropane triacrylate | 239-701-3 | 15625-89-5 | 5.0 - <10 | H315-317-319-351-400-410 | Aquatic Acute 1, Aquatic Chronic 1, Carc. 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1 |
| alumina oxide | 215-691-6 | 1344-28-1 | 1.0 - <5.0 | | |
| fly ash | 268-627-4 | 68131-74-8 | 0.1 - <1.0 | | |

| CAS-No. | M-Factors |
|---|---|
| 25068-38-6 | |
| 15541-60-3 | |
| 108-78-1 | |
| 115-77-5 | |
| 13463-67-7 | |
| 15625-89-5 | |
| 1344-28-1 | |
| 68131-74-8 | |

**Additional Information:** The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

### 4.1 Description of First Aid Measures

**GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice.
**AFTER INHALATION:** Move to fresh air. Consult a physician after significant exposure.
**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.
**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

**Self protection of the first aider:**

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

No Information

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

## 5. Fire-fighting Measures

**5.1 Extinguishing Media:**

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above.

**5.2 Special hazards arising from the substance or mixture**

No Information

**5.3 Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

## 6. Accidental Release Measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment.

**6.2 Environmental precautions**

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

**6.3 Methods and material for containment and cleaning up**

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

**6.4 Reference to other sections**

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

## 7. Handling and Storage

**7.1 Precautions for safe handling**

**INSTRUCTIONS FOR SAFE HANDLING:** Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.
**PROTECTION AND HYGIENE MEASURES:** Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

**7.2 Conditions for safe storage, including any incompatibilities**

**CONDITIONS TO AVOID:** No Information
**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

**7.3 Specific end use(s)**

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

**8.1 Control parameters**

**Ingredients with Occupational Exposure Limits**
**(Middle East)**

| Name | CAS-No. | LTEL ppm | STEL ppm | STEL mg/m3 | LTEL mg/m3 |
|---|---|---|---|---|---|
| Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 25068-38-6 | | | | |

| | |
|---|---|
| melamine pyrophosphate | 15541-60-3 |
| melamine | 108-78-1 |
| pentaerythritol | 115-77-5 |
| titanium dioxide | 13463-67-7 |
| Trimethylolpropane triacrylate | 15625-89-5 |
| alumina oxide | 1344-28-1 |
| fly ash | 68131-74-8 |

| Name | CAS-No. | OEL Note |
|---|---|---|
| Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 25068-38-6 | |
| melamine pyrophosphate | 15541-60-3 | |
| melamine | 108-78-1 | |
| pentaerythritol | 115-77-5 | |
| titanium dioxide | 13463-67-7 | |
| Trimethylolpropane triacrylate | 15625-89-5 | |
| alumina oxide | 1344-28-1 | |
| fly ash | 68131-74-8 | |

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

**Personal Protection**

**RESPIRATORY PROTECTION:** Respirator with a vapor filter.
**EYE PROTECTION:** Safety glasses.
**HAND PROTECTION:** Impervious gloves.
**Body Protection:** Long sleeved clothing.
Remove and wash contaminated clothing before re-use.
**OTHER PROTECTIVE EQUIPMENT:** No Information
**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

| | |
|---|---|
| **Appearance:** | Viscous Grey Liquid |
| **Physical State** | Liquid |
| **Odor** | Sweet |
| **Odor threshold** | Not determined |
| **pH** | Not determined |
| **Melting point / freezing point (°C)** | Not determined |
| **Boiling point/range (°C)** | 94 - 316 |

| | |
|---|---|
| **Flash Point, (°C)** | 85 |
| **Evaporation rate** | Slower Than Ether |
| **Flammability (solid, gas)** | Not determined |
| **Upper/lower flammability or explosive limits** | 1.1 - 12.7 |
| **Vapour Pressure** | Not determined |
| **Vapour density** | Heavier Than Air |
| **Relative density** | Not determined |
| **Solubility in / Miscibility with water** | Very Low |
| **Partition coefficient: n-octanol/water** | Not determined |
| **Auto-ignition temperature (°C)** | Not determined |
| **Decomposition temperature (°C)** | Not determined |
| **Viscosity** | Unknown |
| **Explosive properties** | Not determined |
| **Oxidising properties** | Not determined |

**9.2 Other information**

| | |
|---|---|
| **VOC Content g/l:** | 13.00 |
| **Specific Gravity (g/cm3)** | 1.230 |

## 10. Stability and Reactivity

**10.1 Reactivity**
No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability**
No decomposition if stored and applied as directed. Stable under normal conditions.

**10.3 Possibility of hazardous reactions**
Hazardous polymerisation does not occur.

**10.4 Conditions to avoid**
No Information

**10.5 Incompatible materials**
Strong oxidizing agents. Acids and bases. Amines.

**10.6 Hazardous decomposition products**
Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

## 11. Toxicological Information

**11.1 Information on toxicological effects**

**Acute Toxicity:**

**Oral LD50:** No information available.

**Inhalation LC50:** No information available.

**Irritation:** No information available.

**Corrosivity:** No information available.

**Sensitization:** No information available.

**Repeated dose toxicity:** No information available.

**Carcinogenicity:** No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

**STOT-single exposure:** No information available.

**STOT-repeated exposure:** No information available.

**Aspiration hazard:** No information available.

**If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:**

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 | Gas LC50 | Dust/Mist LC50 |
|---|---|---|---|---|---|---|
| 25068-38-6 | Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | >2000 mg/kg, rat, oral | >2000 mg/kg, rat | | 0.000 | 0.000 |
| 108-78-1 | melamine | 3161 mg/kg, oral, rat | | 3248 mg/m3 8 Hr, Inh, Rat | 0.000 | 0.000 |
| 13463-67-7 | titanium dioxide | 10000 mg/m3, oral (rat) | | | 0.000 | 0.000 |
| 15625-89-5 | Trimethylolpropane triacrylate | 5000 mg/kg, oral, rat | | | 0.000 | 0.000 |

**Additional Information:**

No Information

## 12. Ecological Information

**12.1 Toxicity:**

**EC50 48hr (Daphnia):** No information

**IC50 72hr (Algae):** No information

**LC50 96hr (fish):** No information

**12.2 Persistence and degradability:** No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

**12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**12.6 Other adverse effects:** No information

| CAS-No. | Chemical Name | EC50 48hr | IC50 72hr | LC50 96hr |
|---|---|---|---|---|
| 25068-38-6 | Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | No information | No information | |
| 15541-60-3 | melamine pyrophosphate | No information | No information | |
| 108-78-1 | melamine | No information | No information | |
| 115-77-5 | pentaerythritol | No information | No information | No information |
| 13463-67-7 | titanium dioxide | >100 mg/l (EC50, 48h, Daphnia magna OECD202)ation | No information | >1000 mg/l |
| 15625-89-5 | Trimethylolpropane triacrylate | 19.9 mg/l | No information | >1-<2.2 mg/l |
| 1344-28-1 | alumina oxide | No information | No information | |
| 68131-74-8 | fly ash | No information | No information | |

## 13. Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

**14.1 UN number** UN 3082

**14.2 UN proper shipping name** Environmentally Hazardous Substance, Liquid, N.O.S.

**Technical name** Epoxy Resin

**14.3 Transport hazard class(es)** 9

**Subsidiary shipping hazard** Not applicable

**14.4 Packing group** III

**14.5 Environmental hazards** Marine Pollutant: Yes (Epoxy Resin)

**14.6 Special precautions for user** Unknown

**EmS-No.:** F-A, S-F

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code** Unknown

## 15. Regulatory Information

**15.1 Safety, health and environmental regulations/legislation for the substance or mixture:**

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS:**

**WARNING**

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects and other reproductive harm.

No Proposition 65 Reproductive Toxins exist in this product.

**CALIFORNIA PROPOSITION 65 CARCINOGENS:**

**WARNING**

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

No Proposition 65 Carcinogens exist in this product.

## 16. Other Information

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

| | |
|---|---|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |

**Reasons for revision**

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

| | |
|---|---|
| CLP | Classification, Labeling & Packaging Regulation |
| EC | European Commission |
| EU | European Union |
| US | United States |
| CAS | Chemical Abstract Service |

| | |
|---|---|
| EINECS | European Inventory of Existing Chemical Substances |
| REACH | Registration, Evaluation, Authorization of Chemicals Regulation |
| GHS | Globally Harmonized System of Classification and Labeling of Chemicals |
| LTEL | Long term exposure limit |
| STEL | Short term exposure limit |
| OEL | Occupational exposure limit |
| ppm | Parts per million |
| mg/m3 | Milligrams per cubic meter |
| TLV | Threshold Limit Value |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| OSHA | Occupational Safety & Health Administration |
| PEL | Permissible Exposure Limits |
| VOC | Volatile organic compounds |
| g/l | Grams per liter |
| mg/kg | Milligrams per kilogram |
| N/A | Not applicable |
| LD50 | Lethal dose at 50% |
| LC50 | Lethal concentration at 50% |
| EC50 | Half maximal effective concentration |
| IC50 | Half maximal inhibitory concentration |
| PBT | Persistent bioaccumulative toxic chemical |
| vPvB | Very persistent and very bioaccumulative |
| EEC | European Economic Community |
| ADR | International Transport of Dangerous Goods by Road |
| RID | International Transport of Dangerous Goods by Rail |
| UN | United Nations |
| IMDG | International Maritime Dangerous Goods Code |
| IATA | International Air Transport Association |
| MARPOL | International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978 |
| IBC | International Bulk Container |
| RTI | Respiratory Tract Irritation |
| NE | Narcotic Effects |
| IMO | International Maritime Organization |
| Note P: | The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene |
| Note 10: | The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm. |

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.