


Admiral®

SAFETY DATA SHEET

Carboline Carboguard 880 Comp. A

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Carboline Carboguard 880 Comp. A
Product number 821CG880-A

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier Akis Paint and Chemical Inc.
 Ali Osman Sönmez Cad. No:4
 DOSAB-BURSA/TURKEY
 T: +902242610537
 F: +902242610542
 www.akisboya.com

Contact person Tolga Dıraz - Teknik Müdür, Resmiye Kovancı Savaş - Fabrika Müdürü, H. Tuğba Başkurt
 Fildişi - Kalite Güvence Sorumlusu

1.4. Emergency telephone number

Emergency telephone Company Tel: +90 224 261 05 37 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


Classification

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT RE 1 - H372
Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) F; R11. T; R48/23/24/25. Xi; R36/38. N; R51/53. R43

2.2. Label elements

Pictogram



Signal word

Danger

Carboline Carboguard 880 Comp. A

Hazard statements	<p>H225 Highly flammable liquid and vapour.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H372 Causes damage to organs through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P240 Ground/bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P260 Do not breathe vapour/spray.</p> <p>P261 Avoid breathing vapour/spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P270 Do not eat, drink or smoke when using this product.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P314 Get medical advice/attention if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p>
Contains	reaction product: bisphenol-A-(epichlorhydrin), Quartz, formaldehyde ... %

2.3. Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

reaction product: bisphenol-A-(epichlorhydrin)		25-40%
CAS number: 25068-38-6		EC number: 500-033-5
Classification	Classification (67/548/EEC or 1999/45/EC)	
Eye Irrit. 2 - H319	Xi; R36/38. N; R51/53. R43	
Skin Irrit. 2 - H315		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		

Carboline Carboguard 880 Comp. A

Quartz		10-20%
CAS number: 14808-60-7		
Classification STOT RE 1 - H372	Classification (67/548/EEC or 1999/45/EC) T; R48/25	
xylene		5-10%
CAS number: 1330-20-7		EC number: 215-535-7
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC or 1999/45/EC) Xn; R48/20/21/22, R20/21. Xi; R36/37/38. R10	
butanone-ethyl methyl ketone		1-5%
CAS number: 78-93-3		EC number: 201-159-0
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F; R11. Xi; R36. R66, R67	
formaldehyde ... %		<1%
CAS number: 50-00-0		EC number: 200-001-8
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Muta. 2 - H341 Carc. 1B - H350 STOT SE 3 - H335		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from source of contamination. Chemical burns must be treated by a physician.

Inhalation

If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. First aid personnel should wear appropriate protective equipment during any rescue. If spray/mist has been inhaled, proceed as follows. Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Rinse nose and mouth with water. Consult a physician for specific advice. Keep affected person warm and at rest. Get medical attention if symptoms are severe or persist.

Carboline Carboguard 880 Comp. A

Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove contact lenses, if present and easy to do. Continue rinsing. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
Protection of first aiders	Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	The product contains organic solvents. Toxic if inhaled.
Ingestion	This product is corrosive. Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May cause chemical burns in mouth and throat.
Skin contact	Causes severe burns.
Eye contact	Redness. Conjunctivitis, irritation, tearing. May cause chemical eye burns.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
Specific treatments	No specific chemical antidote is known to be required after exposure to this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use foam, carbon dioxide, dry powder or water fog to extinguish.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Not known. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.
Hazardous combustion products	None known.

5.3. Advice for firefighters

Protective actions during firefighting	Move containers from fire area if it can be done without risk. Control run-off water by containing and keeping it out of sewers and watercourses. Stop leak if safe to do so. Contain and collect extinguishing water. Ventilate closed spaces before entering them. Cool containers exposed to flames with water until well after the fire is out.
Special protective equipment for firefighters	Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure procedures and training for emergency decontamination and disposal are in place. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Take care as floors and other surfaces may become slippery. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.
-----------------------------	---

Carboline Carboguard 880 Comp. A

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. May accumulate in soil and water systems.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Large Spillages: Collect spillage for reclamation or absorb in vermiculite, dry sand or similar material. Flush contaminated area with plenty of water. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Leave small quantities to evaporate, if safe to do so. Allow small quantities to evaporate to the atmosphere in a safe, open place.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Obtain special instructions before use. Avoid contact with skin, eyes and clothing. Read label before use. Wear protective clothing as described in Section 8 of this safety data sheet. For professional users only.

Advice on general occupational hygiene Take off contaminated clothing. Promptly remove any clothing that becomes wet or contaminated. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Contaminated clothing should be placed in a closed container for disposal or decontamination. Good personal hygiene procedures should be implemented. Provide eyewash station. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Protect from sunlight. Keep away from food, drink and animal feeding stuffs. Keep containers upright.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Carboline Carboguard 880 Comp. A

Appropriate engineering controls	As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Clean equipment and the work area every day.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.
Thermal hazards	If there is a risk of contact with hot product, all protective equipment worn should be suitable for use with high temperatures.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Homogeneous
Colour	Dirty Yellow
Flash point	<23C°
Relative density	1,595-1,643 gr/cm ³ (20°C)
Viscosity	5000-10000 cps(#7,100 rpm) (25°C)

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid	Avoid exposure to high temperatures or direct sunlight.
----------------------------	---

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products	Decomposition at ambient temperatures may generate the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂).
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	This product is toxic. Allergic skin reaction may be observed in hypersensitive personnel.
------------------------------	--

Carboline Carboguard 880 Comp. A

Acute toxicity - dermal

ATE dermal (mg/kg) 870,356.0

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Severe eye irritation

Specific target organ toxicity - repeated exposure

STOT - repeated exposure may be toxic to specific target organs after repeated exposure.

Inhalation The product contains organic solvents. May cause drowsiness or dizziness.

Ingestion May be harmful if swallowed. May cause stomach pain or vomiting.

Skin contact Liquid may irritate skin.

Eye contact May irritate eyes.

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment. The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential. May cause long lasting harmful effects to aquatic life. The product may have adverse effects on organisms in soil and water.

12.1. Toxicity

Toxicity No effects known.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential Not known.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations. Product residues retained in emptied containers can be hazardous.

SECTION 14: Transport information

14.1. UN number

Carboline Carboguard 880 Comp. A

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT (CONTAINS reaction product: bisphenol-A-(epichlorhydrin))
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33

Carboline Carboguard 880 Comp. A

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments.
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data This SDS has been created as a result of observations, measurements on the product related to the product and the data that raw material suppliers provide

Revision comments This is first issue.

Issued by Mr. Tolga DIRAZ - Certified SDS Author - Certificate No: 01.40.08/06.03.2015 / tdiraz@iyigullu.com.tr / +90 224 261 05 37

Revision 0

Supersedes date 12/11/2015

SDS number 4891

Risk phrases in full R10 Flammable.
R11 Highly flammable.
R20/21 Harmful by inhalation and in contact with skin.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R34 Causes burns.
R36 Irritating to eyes.
R36/38 Irritating to eyes and skin.
R38 Irritating to skin.
R43 May cause sensitisation by skin contact.
R45 May cause cancer.
R48/25 Toxic: danger of serious damage to health by prolonged exposure if swallowed.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.
R68 Possible risk of irreversible effects.

Carboline Carboguard 880 Comp. A

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H372 Causes damage to organs through prolonged or repeated exposure.
H372 Causes damage to organs through prolonged or repeated exposure if swallowed.
H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.