



SAFETY DATA SHEET

Carboline Carboguard 616 Comp. A Grey

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Carboline Carboguard 616 Comp. A Grey
Product number 821CG616-A-GREY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Primer. Intermediate coat.

1.3. Details of the supplier of the safety data sheet

Supplier Akis Paint and Chemical Inc.
 Ali Osman Sönmez Cad. No:4
 DOSAB-BURSA/TURKEY
 T: +902242610537
 F:+902242610542
 www.akisboya.com

Contact person SDS Preparation Unit

1.4. Emergency telephone number

Emergency telephone Company Tel: +90 224 261 05 37 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335 STOT RE 2 - H373

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.

Carboline Carboguard 616 Comp. A Grey

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

Contains	<p>reaction product: bisphenol-A-(epichlorhydrin), 4,4'-(1-Methylethylidene)bisphenol polymer with 2,2'-[(1-, Quartz, oxirane, mono[(C12-14-alkyloxy)methyl] derivs., m-xylene, o-xylene, p-xylene, ethylbenzene, Amide, Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines</p>
-----------------	--

2.3. Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

reaction product: bisphenol-A-(epichlorhydrin)	10-20%
CAS number: 25068-38-6 EC number: 500-033-5	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335	
4,4'-(1-Methylethylidene)bisphenol polymer with 2,2'-[(1-	10-20%
CAS number: 25036-25-3	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Eye Irrit. 2 - H319 Skin Sens. 1A - H317	
Quartz	5-10%
CAS number: 14808-60-7	
Classification STOT RE 1 - H372	

Carboline Carboguard 616 Comp. A Grey

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	1-5%
CAS number: 68609-97-2	EC number: 271-846-8
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317	
m-xylene	1-5%
CAS number: 108-38-3	EC number: 203-576-3
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Asp. Tox. 1 - H304	
o-xylene	1-5%
CAS number: 95-47-6	EC number: 202-422-2
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Asp. Tox. 1 - H304	
p-xylene	1-5%
CAS number: 106-42-3	EC number: 203-396-5
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Asp. Tox. 1 - H304	

Carboline Carboguard 616 Comp. A Grey

ethylbenzene	1-5%
CAS number: 100-41-4	EC number: 202-849-4
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
STOT SE 3 - H335, H336	
STOT RE 2 - H373	
Amide	1-5%
CAS number: —	
Classification	
Skin Sens. 1B - H317	
Aquatic Chronic 4 - H413	
Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines	<1%
CAS number: 68647-95-0	
M factor (Acute) = 1	M factor (Chronic) = 1
Classification	
Skin Irrit. 2 - H315	
Skin Sens. 1B - H317	
STOT RE 2 - H373	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination. Chemical burns must be treated by a physician.
Inhalation	If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. First aid personnel should wear appropriate protective equipment during any rescue. If spray/mist has been inhaled, proceed as follows. Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Rinse nose and mouth with water. Consult a physician for specific advice. Keep affected person warm and at rest. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

Carboline Carboguard 616 Comp. A Grey

Eye contact	Remove affected person from source of contamination. Remove contact lenses, if present and easy to do. Continue rinsing. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
Protection of first aiders	Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	The product contains organic solvents. Toxic if inhaled.
Ingestion	This product is corrosive. Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May cause chemical burns in mouth and throat.
Skin contact	Causes severe burns.
Eye contact	Redness. Conjunctivitis, irritation, tearing. May cause chemical eye burns.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
Specific treatments	No specific chemical antidote is known to be required after exposure to this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use foam, carbon dioxide, dry powder or water fog to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Not known. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.
Hazardous combustion products	None known.

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk. Control run-off water by containing and keeping it out of sewers and watercourses. Stop leak if safe to do so. Contain and collect extinguishing water. Ventilate closed spaces before entering them. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure procedures and training for emergency decontamination and disposal are in place. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Take care as floors and other surfaces may become slippery. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. May accumulate in soil and water systems.

6.3. Methods and material for containment and cleaning up

Carboline Carboguard 616 Comp. A Grey

Methods for cleaning up

Large Spillages: Collect spillage for reclamation or absorb in vermiculite, dry sand or similar material. Flush contaminated area with plenty of water. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Leave small quantities to evaporate, if safe to do so. Allow small quantities to evaporate to the atmosphere in a safe, open place.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Obtain special instructions before use. Avoid contact with skin, eyes and clothing. Read label before use. Wear protective clothing as described in Section 8 of this safety data sheet. For professional users only.

Advice on general occupational hygiene

Take off contaminated clothing. Promptly remove any clothing that becomes wet or contaminated. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Contaminated clothing should be placed in a closed container for disposal or decontamination. Good personal hygiene procedures should be implemented. Provide eyewash station. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry and cool place. Protect from sunlight. Keep away from food, drink and animal feeding stuffs. Keep containers upright.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Clean equipment and the work area every day.

Carboline Carboguard 616 Comp. A Grey

Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.
Thermal hazards	If there is a risk of contact with hot product, all protective equipment worn should be suitable for use with high temperatures.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Homogeneous
Colour	Grey.
Flash point	>23°C; <60°C
Bulk density	1.541-1.589 g/cm ³ (25°C)

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Decomposition at ambient temperatures may generate the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects This product is toxic. Allergic skin reaction may be observed in hypersensitive personnel.

Acute toxicity - dermal

ATE dermal (mg/kg) 5,978.26

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 458.33

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Causes severe eye irritation.

Skin sensitisation

Skin sensitisation Sensitising.

Germ cell mutagenicity

Carboline Carboguard 616 Comp. A Grey

Genotoxicity - in vitro	May induce heritable mutations in the germ cells of humans.
<u>Carcinogenicity</u>	
Carcinogenicity	Known carcinogen based on animal evidence.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No information available.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No information available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	may be toxic to specific target organs after repeated exposure.
Inhalation	The product contains organic solvents. May cause drowsiness or dizziness.
Ingestion	May be harmful if swallowed. May cause stomach pain or vomiting.
Skin contact	Liquid may irritate skin.
Eye contact	May irritate eyes.

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment. The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential. May cause long lasting harmful effects to aquatic life. The product may have adverse effects on organisms in soil and water.

12.1. Toxicity

Toxicity No effects known.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential Not known.

BCF

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations. Product residues retained in emptied containers can be hazardous.

Carboline Carboguard 616 Comp. A Grey

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30

Carboline Carboguard 616 Comp. A Grey

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments.
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data This SDS has been created as a result of observations, measurements on the product related to the product and the data that raw material suppliers provide

Revision comments This is first issue.

Issued by Mrs. Nesrin Aydin - Certified SDS Author - Certificate No: 01.133.03/18.08.2017 / sds@iyigullu.com.tr / +90 224 261 05 37

Revision date 12/07/2018

Revision 0

Supersedes date 12/07/2018

SDS number 5724

Hazard statements in full H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed or if inhaled.

Carboline Carboguard 616 Comp. A Grey

DRAFT

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.