



SAFETY DATA SHEET

Carboline Multiguard 71TR Comp. B

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Carboline Multiguard 71TR Comp. B

Product number 820MG71TR

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier Akis Paint and Chemical Inc.

Ali Osman Sönmez Cad. No:4 DOSAB-BURSA/TURKEY T: +902242610537

F:+902242610542 www.akisboya.com

Contact person Tolga Dıraz - Teknik Müdür,Resmiye Kovancı Savaş - Fabrika Müdürü,H.Tuğba Başkurt

Fildişi - Kalite Güvence Sorumlusu

1.4. Emergency telephone number

Emergency telephone Company Tel: +90 224 261 05 37 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 2 - H361d STOT SE 3 -

H336 STOT RE 2 - H373 Asp. Tox. 1 - H304

Environmental hazards Aguatic Chronic 3 - H412

Classification (67/548/EEC or F; R11. Xn; R65, R48/20/21/22. Xi; R41, R38. Repr. Cat. 3 R63. R52/53, R43, R67 **1999/45/EC)**

2.2. Label elements

Pictogram









Signal word

Danger

Hazard statements H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe vapour/spray.

P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see medical advice on this label).

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

Contains

toluene, Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine, propan-2-ol

2.3. Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

10-20%

Carboline Multiguard 71TR Comp. B

 toluene
 10-20%

 CAS number: 108-88-3
 EC number: 203-625-9

 Classification
 Classification (67/548/EEC or 1999/45/EC)

 Flam. Liq. 2 - H225
 F; R11. Xn; R65, R48/20/21/22. Xi; R38. Repr. Cat. 3 R63.

Repr. 2 - H361d R67 Asp. Tox. 1 - H304

STOT RE 2 - H373 Skin Irrit. 2 - H315 STOT SE 3 - H336

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

CAS number: 68082-29-1 EC number: 500-191-5

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Irrit. 2 - H315 Xi; R41, R38. N; R51/53. R43

Eye Dam. 1 - H318 Skin Sens. 1A - H317 Aquatic Chronic 2 - H411

xylene 5-10%

CAS number: 1330-20-7 EC number: 215-535-7

 Classification
 Classification (67/548/EEC or 1999/45/EC)

 Flam. Liq. 3 - H226
 Xn; R48/20/21/22, R20/21. Xi; R36/37/38. R10

Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315

propan-2-ol 1-5%

CAS number: 67-63-0 EC number: 200-661-7

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Lig. 2 - H225 F; R11. Xi; R36. R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Remove affected person from source of contamination. Chemical burns must be treated by a

physician.

Revision: 0 Supersedes date: 19/11/2015

Carboline Multiguard 71TR Comp. B

Inhalation If it is suspected that volatile contaminants are still present around the affected person, first

aid personnel should wear an appropriate respirator or self-contained breathing apparatus. First aid personnel should wear appropriate protective equipment during any rescue. If spray/mist has been inhaled, proceed as follows. Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Rinse nose and mouth with water. Consult a physician for specific advice. Keep affected person warm and at rest. Get medical

attention if symptoms are severe or persist.

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to

an unconscious person. Get medical attention.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing

immediately and wash skin with soap and water. Get medical attention if any discomfort

continues.

Eye contact Remove affected person from source of contamination. Remove contact lenses, if present and

easy to do. Continue rinsing. Remove any contact lenses and open eyelids wide apart.

Continue to rinse for at least 15 minutes and get medical attention.

Protection of first aiders Wash contaminated clothing thoroughly with water before removing it from the affected

person, or wear gloves. First aid personnel should wear appropriate protective equipment

during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation The product contains organic solvents. Toxic if inhaled.

Ingestion This product is corrosive. Liquid irritates mucous membranes and may cause abdominal pain

if swallowed. May cause chemical burns in mouth and throat.

Skin contact Causes severe burns.

Eye contact Redness. Conjunctivitis, irritation, tearing. May cause chemical eye burns.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use foam, carbon dioxide, dry powder or water fog to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards Not known. Thermal decomposition or combustion products may include the following

substances: Toxic gases or vapours.

Hazardous combustion

products

None known.

5.3. Advice for firefighters

Protective actions during

firefighting

Move containers from fire area if it can be done without risk. Control run-off water by containing and keeping it out of sewers and watercourses. Stop leak if safe to do so. Contain

and collect extinguishing water. Ventilate closed spaces before entering them. Cool

containers exposed to flames with water until well after the fire is out.

Special protective equipment

for firefighters

Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure procedures and training for emergency decontamination and disposal are in place. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Take care as floors and other surfaces may become slippery. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. May accumulate in soil and water systems.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Large Spillages: Collect spillage for reclamation or absorb in vermiculite, dry sand or similar material. Flush contaminated area with plenty of water. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Leave small quantities to evaporate, if safe to do so. Allow small quantities to evaporate to the atmosphere in a safe, open place.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Obtain special instructions before use. Avoid contact with skin, eyes and clothing. Read label before use. Wear protective clothing as described in Section 8 of this safety data sheet. For professional users only.

Advice on general occupational hygiene

Take off contaminated clothing. Promptly remove any clothing that becomes wet or contaminated. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Contaminated clothing should be placed in a closed container for disposal or decontamination. Good personal hygiene procedures should be implemented. Provide eyewash station. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry and cool place. Protect from sunlight. Keep away from food, drink and animal feeding stuffs. Keep containers upright.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³ Sk

WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

Revision: 0 Supersedes date: 19/11/2015

Carboline Multiguard 71TR Comp. B

8.2. Exposure controls

Protective equipment











Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eve/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

Hygiene measures

Wash hands and any other contaminated areas of the body with soap and water before

leaving the work site. Clean equipment and the work area every day.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk

 $assessment\ indicates\ inhalation\ of\ contaminants\ is\ possible.$

Thermal hazards

If there is a risk of contact with hot product, all protective equipment worn should be suitable

for use with high temperatures.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they

comply with the requirements of environmental protection legislation.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Homogeneous

Colour flavescent

Flash point <23C°

Relative density 1,37-1,47 gr/cm3 (20°C)

Viscosity 60-70 KU (25°C)

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products

Decomposition at ambient temperatures may generate the following substances: Carbon

monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects This product is toxic.

Acute toxicity - dermal

ATE dermal (mg/kg) 1,343,101.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 13,431.0

Skin sensitisation

Skin sensitisation Sensitising.

.

Inhalation The product contains organic solvents. May cause drowsiness or dizziness.

Ingestion May be harmful if swallowed. May cause stomach pain or vomiting.

Skin contact Liquid may irritate skin.

Eye contact May irritate eyes.

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment. The product contains volatile organic compounds (VOCs)

which have a photochemical ozone creation potential. May cause long lasting harmful effects

to aquatic life. The product may have adverse effects on organisms in soil and water.

12.1. Toxicity

Toxicity No effects known.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential Not known.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General informationDisposal of this product, process solutions, residues and by-products should at all times

comply with the requirements of environmental protection and waste disposal legislation and

any local authority requirements.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations. Product residues retained in emptied containers can be hazardous.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263 UN No. (IMDG) 1263 UN No. (ICAO) 1263 UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)

PAINT

Proper shipping name

PAINT

(IMDG)

Proper shipping name (ICAO) PAINT
Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class 3
ADR/RID classification code F1
ADR/RID label 3
IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group || |
IMDG packing group || |
ADN packing group || |
ICAO packing group || |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number 33

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list

of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and

Directive 91/689/EEC on hazardous waste with amendments.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and

sources for data

This SDS has been created as a result of observations, measurements on the product related

to the product and the data that raw material suppliers provide

Revision comments This is first issue.

Issued by Mr. Tolga DIRAZ - Certified SDS Author - Certificate No: 01.40.08/06.03.2015 /

tdiraz@iyigullu.com.tr / +90 224 261 05 37

Revision 0

Supersedes date 19/11/2015

SDS number 4896

Risk phrases in full R10 Flammable.

R11 Highly flammable.

R20/21 Harmful by inhalation and in contact with skin.

R36 Irritating to eyes. R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through

inhalation, in contact with skin and if swallowed.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R63 Possible risk of harm to the unborn child. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.