



## Safety Data Sheet

Prepared in Accordance with HPR  
(SOR/2015-17)

### 1. Identification of the Substance/Mixture and the Company/Undertaking

- 1.1 Product Identifier** 0856B1NL
- Product Name:** URETHANE CONVERTER 811 **Revision Date:** 12/06/2018
- 1.2 Relevant identified uses of the substance or mixture and uses advised against** Hardener for 2 components coatings - Industrial use. **Supersedes Date:** 03/10/2017
- 1.3 Details of the supplier of the safety data sheet**
- Importer:** StonCor Canada  
95 Sunray Street  
Whitby, Ontario L1N 8Y3  
Tel: 905-430-3333
- Manufacturer:** Carboline Company  
2150 Schuetz Road  
St. Louis, MO USA 63146
- Regulatory / Technical Information:  
Contact Carboline Technical Services at  
1-800-848-4645
- Datasheet Produced by:** Schlereth, Ken - ehs@stoncor.com
- 1.4 Emergency telephone number:** CHEMTREC +1 703 5273887 (Outside US)

### 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4  
Hazardous to the aquatic environment, Chronic, category 2  
Flammable Liquid, category 3  
Respiratory Sensitizer, category 1  
STOT, single exposure, category 3, RT1  
Skin Sensitizer, category 1

## 2.2 Label elements

### Symbol(s) of Product



### Signal Word

Danger

### Named Chemicals on Label

HEXAMETHYLENE DIISOCYANATE, HOMOPOLYMER OF HDI, AROMATIC HYDROCARBON

### HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

### PRECAUTION PHRASES

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P341	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342+311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

## 2.3 Other hazards

No Information

### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## 3. Composition/Information On Ingredients

### 3.2 Mixtures

#### Hazardous Ingredients

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
28182-81-2	HOMOPOLYMER OF HDI	75 - 100
123-86-4	N-BUTYL ACETATE	2.5 - <10
64742-95-6	AROMATIC HYDROCARBON	2.5 - <10

822-06-0

HEXAMETHYLENE DIISOCYANATE

0.1 - &lt;1.0

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
28182-81-2	GHS07-GHS09	H317-332-335-411	0
123-86-4	GHS02-GHS07	H226-336	0
64742-95-6	GHS02-GHS07-GHS08-GHS09	H226-304-315-319-332-335-336-411	0
822-06-0	GHS06-GHS08	H302-315-317-319-330-334-335	0

**Additional Information:** The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

### 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

May be harmful if swallowed.

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

## 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Humid air and/or water will produce carbon dioxide which will pressurize the container. Combustible Liquid Provide adequate ventilation. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

### 5.2 Special hazards arising from the substance or mixture

No Information

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Combustible material. Cool containers / tanks with water spray.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Heat, flames and sparks. Exposure to moisture.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
HOMOPOLYMER OF HDI	28182-81-2	N/E	N/E	N/E
N-BUTYL ACETATE	123-86-4	50 PPM	150 PPM	N/E
AROMATIC HYDROCARBON	64742-95-6	300.0 PPM	N/E	N/E
HEXAMETHYLENE DIISOCYANATE	822-06-0	0.005 PPM	N/E	N/E

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
HOMOPOLYMER OF HDI	28182-81-2	N/E	N/E
N-BUTYL ACETATE	123-86-4	710 MGM3, 150 950 MGM3, 200 PPM	200 PPM
AROMATIC HYDROCARBON	64742-95-6	500.0 PPM	N/E
HEXAMETHYLENE DIISOCYANATE	822-06-0	N/E	N/E

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no

exposure limits are established above, air-supplied respirators are generally not required.

**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	Colorless, Mobil Liquid
<b>Physical State</b>	Liquid
<b>Odor</b>	Slight Odor
<b>Odor threshold</b>	N/D
<b>pH</b>	N/D
<b>Melting point / freezing point (°C)</b>	N/D
<b>Boiling point/range</b>	262 F (128 C) - 262F (128C)
<b>Flash Point</b>	127F (53C)
<b>Evaporation rate</b>	Slower Than Ether
<b>Flammability (solid, gas)</b>	Not determined
<b>Upper/lower flammability or explosive limits</b>	0.9 - 7.6
<b>Vapour Pressure, mmHg</b>	N/D
<b>Vapour density</b>	Heavier than Air
<b>Relative density</b>	Not determined
<b>Solubility in / Miscibility with water</b>	Reacts
<b>Partition coefficient: n-octanol/water</b>	Not determined
<b>Auto-ignition temperature (°C)</b>	Not determined
<b>Decomposition temperature (°C)</b>	Not determined
<b>Viscosity</b>	Unknown
<b>Explosive properties</b>	Not determined
<b>Oxidising properties</b>	Not determined

### 9.2 Other information

<b>VOC Content g/l:</b>	Refer to Part A SDS
<b>Specific Gravity (g/cm<sup>3</sup>)</b>	1.12

## 10. Stability and Reactivity

### 10.1 Reactivity

Water reactive

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation does not occur.

**10.4 Conditions to avoid**

Heat, flames and sparks. Exposure to moisture.

**10.5 Incompatible materials**

Never allow product to get in contact with water during storage. Water in the container will lead to increased pressure and risk of explosion. Strong oxidizing agents.

**10.6 Hazardous decomposition products**

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## 11. Toxicological Information

**11.1 Information on toxicological effects****Acute Toxicity:**

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Respiratory Sensitizer / Skin Sensitizer: category 1

Repeated dose toxicity: STOT Single exposure ( Respiratory System): Category 3

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
28182-81-2	HOMOPOLYMER OF HDI	5000 mg/kg, oral, rat	Not Available	390 mg/m <sup>3</sup> , inhalation, rat	0.000	0.000
123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4/h, Inh. rat		
64742-95-6	AROMATIC HYDROCARBON	4700 mg/kg, oral, rat	Not Available	3670 ppm/8 hours, rat, inhalation	0.000	0.000
822-06-0	HEXAMETHYLENE DIISOCYANATE	710 mg/kg, oral rat	>7000 mg/kg, dermal, rat	23 ppm / 4 hrs	0.000	0.000

**Additional Information:**

No Information

## 12. Ecological Information

- 12.1 **Toxicity:**
- |                      |         |
|----------------------|---------|
| EC50 48hr (Daphnia): | Unknown |
| IC50 72hr (Algae):   | Unknown |
| LC50 96hr (fish):    | Unknown |
- 12.2 **Persistence and degradability:** Unknown
- 12.3 **Bioaccumulative potential:** Unknown
- 12.4 **Mobility in soil:** Unknown
- 12.5 **Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.
- 12.6 **Other adverse effects:** Unknown

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
28182-81-2	HOMOPOLYMER OF HDI	>100 mg/l (Zebra Fish)	No information	>100 mg/l (Zebra Fish)
123-86-4	N-BUTYL ACETATE	44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)
64742-95-6	AROMATIC HYDROCARBON	No information	No information	No information
822-06-0	HEXAMETHYLENE DIISOCYANATE	No information	No information	No information

## 13. Disposal Considerations

- 13.1 **WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

- |   |          |
|---|----------|
| 14.1 UN number  | UN 1263  |
| 14.2 UN proper shipping name  | Paint    |
| Technical name  | N/A      |
| 14.3 Transport hazard class(es)   | 3        |
| Subsidiary shipping hazard  | N/A      |
| 14.4 Packing group  | III      |
| 14.5 Environmental hazards  | Unknown  |
| 14.6 Special precautions for user   | Unknown  |
| EmS-No.:  | F-E, S-E |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code | Unknown  |

## 15. Regulatory Information

- 15.1 **Safety, health and environmental regulations/legislation for the substance or mixture:**

**National Regulations:**

<b>Denmark Product Registration Number:</b>	Unknown
<b>Danish MAL Code:</b>	Unknown
<b>Sweden Product Registration Number:</b>	Unknown
<b>Norway Product Registration Number:</b>	Unknown
<b>WGK Class:</b>	No Information

**U.S. Federal Regulations: As follows -****CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Acute Toxicity (any route of exposure), Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

**Sara Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
HEXAMETHYLENE DIISOCYANATE	822-06-0

**Toxic Substances Control Act:**

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
No TSCA 12(b) components exist in this product.	

**International Regulations: As follows -****\* Canadian DSL:**

All chemical ingredients included on inventory (DSL)

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**16. Other Information****Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.



H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Reasons for revision**

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.