
SELECTION & SPECIFICATION DATA

Description	Versatile corrosion resistant coating used as an exterior weathering tank finish. It may be used over properly primed steel or can be used as a self-priming finish for mild to moderate exposures. Unique formulation initiates the desirable self-chalking properties and maintains the white appearance as the coating weathers.
Features	<ul style="list-style-type: none">• Ready to apply after mixing; no sweat-in time or thinning required.• Economical fit for use epoxy• Self-chalking white color is maintained• Attractive long-term appearance• Versatile as a self-priming epoxy• VOC compliant to current AIM regulations

WARRANTY

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Carboline Company to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Carboline quality control. We assume no responsibility for coverage, performance, injuries or damages resulting from use. Carbolines sole obligation, if any, is to replace or refund the purchase price of the Carboline product(s) proven to be defective, at Carbolines option. Carboline shall not be liable for any loss or damage. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY CARBOLINE, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. All of the trademarks referenced above are the property of Carboline International Corporation unless otherwise indicated.