



Safety Data Sheet

Prepared in Accordance with HPR
(SOR/2015-17)

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	8815A1NL	Revision Date:	05/17/2019
Product Name:	CARBOTHANE 8815 PART A	Supersedes Date:	04/15/2016
1.2 Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.	Version Number:	No Information
1.3 Details of the supplier of the safety data sheet			
Importer:	Carboline, a Division of RPM Canada, a General Partnership 200 Confederation Parkway, Unit 2 Concord, Ontario L4K 4T8 Phone:(800) 263-3112		
Manufacturer:	Carboline Global Inc. 2150 Schuetz Road St. Louis, MO USA 63146		
	Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
Datasheet Produced by:	Alotta, Vicki - regulatory@carboline.com		
1.4 Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US)		

2. Hazard Identification

2.1 Classification of the substance or mixture

Carcinogenicity, category 1A
Flammable Liquid, category 2
Reproductive Toxicity, category 1A
STOT, repeated exposure, category 1
STOT, single exposure, category 3, NE

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

METHYL ETHYL KETONE, N-BUTYL ACETATE, MICROCRYSTALLINE SILICA

HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
Reproductive Toxicity, category 1A	H360-1A	May damage fertility or the unborn child.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P235	Keep cool.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P284	Wear respiratory protection.
P308+313	IF exposed or concerned: Get medical advice/attention
P308+P313	IF exposed or concerned: Get medical advice/attention
P314	Get medical advice/attention if you feel unwell.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>
MICROCRYSTALLINE SILICA	238-878-4	14808-60-7	10 - <25	H350-372
TITANIUM DIOXIDE	236-675-5	13463-67-7	10 - <25	
N-BUTYL ACETATE	204-658-1	123-86-4	10 - <25	H226-336

METHYL ETHYL KETONE	201-159-0	78-93-3	2.5 - <10	H225-319-336
1-METHOXY-2- PROPANOL ACETATE	203-603-9	108-65-6	2.5 - <10	H226
METHYL N-AMYL KETONE	203-767-1	110-43-0	2.5 - <10	H226-302-332
CARBON BLACK	215-609-9	1333-86-4	1.0 - <2.5	
ETHOXYPROPIONATE	212-112-9	763-69-9	1.0 - <2.5	H226
META-XYLENE	203-576-3	108-38-3	1.0 - <2.5	H226-312-315-332
ETHYL BENZENE	202-849-4	100-41-4	1.0 - <2.5	H225-304-315-319-332-351-373 -412
2,4-PENTANEDIONE	204-634-0	123-54-6	0.1 - <1.0	H226-302
ORGANIC TIN	201-039-8	77-58-7	0.1 - <1.0	H314-317-341-360-370-400

<u>CAS-No.</u>	<u>M-Factors</u>
14808-60-7	0
13463-67-7	0
123-86-4	0
78-93-3	0
108-65-6	0
110-43-0	0
1333-86-4	0
763-69-9	0
108-38-3	0
100-41-4	0
123-54-6	0
77-58-7	1

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
MICROCRYSTALLINE SILICA	14808-60-7	0.025 MGM3	N/E	N/E
TITANIUM DIOXIDE	13463-67-7	10 mg/m3	N/E	N/E
N-BUTYL ACETATE	123-86-4	50 PPM	150 PPM	N/E
METHYL ETHYL KETONE	78-93-3	200 PPM	300 PPM	N/E
1-METHOXY-2-PROPANOL ACETATE	108-65-6	N/E	N/E	N/E
METHYL N-AMYL KETONE	110-43-0	50 PPM	N/E	N/E
CARBON BLACK	1333-86-4	3 MGM3	N/E	N/E
ETHOXYPROPIONATE	763-69-9	N/E	N/E	N/E
META-XYLENE	108-38-3	100 PPM	150 PPM	N/E
ETHYL BENZENE	100-41-4	20 PPM	125 ppm	
2,4-PENTANEDIONE	123-54-6	25 PPM	N/E	N/E
ORGANIC TIN	77-58-7	N/E	N/E	N/E

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
MICROCRYSTALLINE SILICA	14808-60-7	0.05 MGM3	N/E
TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E
N-BUTYL ACETATE	123-86-4	710 MGM3, 150 PPM	150 MGM3, 200 PPM
METHYL ETHYL KETONE	78-93-3	590 MGM3, 200 PPM	85 MGM3, 300 PPM
1-METHOXY-2-PROPANOL ACETATE	108-65-6	N/E	N/E
METHYL N-AMYL KETONE	110-43-0	465 MGM3, 100 PPM	N/E
CARBON BLACK	1333-86-4	3.5 MG/M3	N/E
ETHOXYPROPIONATE	763-69-9	N/E	N/E
META-XYLENE	108-38-3	100.00 PPM	N/E
ETHYL BENZENE	100-41-4	435 MGM3, 100 PPM	145 MGM3, 125 PPM
2,4-PENTANEDIONE	123-54-6	N/E	N/E
ORGANIC TIN	77-58-7	0.10 mg/m3	N/E

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified at the EU level under the dangerous substances and preparations regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Viscous Liquid, Various Colors
Physical State	Liquid
Odor	Solvent
Odor threshold	N/D
pH	N/D
Melting point / freezing point (°C)	N/D
Boiling point/range (°C)	149 F (65 C) - 300 F (148 C)
Flash Point (°C)	58F (14C)
Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	0.6 - 13.1
Vapour Pressure, mmHg	N/D
Vapour density	Heavier than Air
Relative density	Not determined
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Unknown
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	395
Specific Gravity (g/cm ³)	app. 1.16

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: N/D

Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Carcinogenicity, category 1A

Mutagenicity: Unknown

Toxicity for reproduction: Reproductive Toxicity, category 1A

STOT-single exposure: STOT, single exposure, category 3, NE

STOT-repeated exposure: STOT, repeated exposure, category 1

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
14808-60-7	MICROCRYSTALLINE SILICA	22500 mg/kg	Not Available	Not Available	0.000	0.000
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available	No Information	No Information

123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4/h, Inh. rat		
78-93-3	METHYL ETHYL KETONE	2194 mg/kg rat, oral	Not Available	34.5 mg/L/ 4 hour rat, inhalation	0.000	0.000
108-65-6	1-METHOXY-2-PROPANOL ACETATE	8532 mg/kg, oral (rat)	>5000 mg/kg	101 ppm/4 hr, rat, inh	0.000	0.000
110-43-0	METHYL N-AMYL KETONE	1670 mg/kg rat oral	Not Available	2000 ppm, 4 hours	0.000	0.000
1333-86-4	CARBON BLACK	8000 mg/kg oral, rat	Not Available	Not Available		
763-69-9	ETHOXYPROPIONATE	5000 mg/kg, oral, rat	4080 mg/kg, dermal, rat	Not Available	0.000	0.000
108-38-3	META-XYLENE	Not Available	Not Available	Not Available	0.000	0.000
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	0.000	0.000
123-54-6	2,4-PENTANEDIONE	55 mg/kg oral, rat	Not Available	10 mg/24 hours rabbit	0.000	0.000
77-58-7	ORGANIC TIN	2071 mg/kg, oral, rat	Not Available	Not Available	0.000	0.000

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This product contains silica which is classified by IARC as a known human carcinogen (Group 1). Crystalline silica is known to cause silicosis. The classification(s) is/are relevant when exposed to these respirable substances in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	Unknown
IC50 72hr (Algae):	Unknown
LC50 96hr (fish):	Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: Unknown

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
14808-60-7	MICROCRYSTALLINE SILICA	No information	No information	No information
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
123-86-4	N-BUTYL ACETATE	44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)
78-93-3	METHYL ETHYL KETONE	308 mg/l (Daphnia magna)	No information	2993 mg/l (Pimephales promelas)

108-65-6	1-METHOXY-2-PROPANOL ACETATE	408 mg/l (Daphnia Magna)	>1000 mg/l (Green Algae)	161 mg/l (Fathead Minnow)
110-43-0	METHYL N-AMYL KETONE	No information	No information	126 - 137 mg/L - Pimephales promelas
1333-86-4	CARBON BLACK	No information	No information	No information
763-69-9	ETHOXYPROPIONATE	785 mg/l (daphnia magna)	115 mg/l (algae)	67.65 mg/l (fathead minnow)
108-38-3	META-XYLENE	No information	No information	No information
100-41-4	ETHYL BENZENE	1.8 mg/l (Daphnia Magna)	4.6 mg/l (Green Algae)	4.2 mg/l (Rainbow Trout)
123-54-6	2,4-PENTANEDIONE	No information	No information	No information
77-58-7	ORGANIC TIN	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1	UN number	UN 1263
14.2	UN proper shipping name	Paint
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	II
14.5	Environmental hazards	Unknown
14.6	Special precautions for user	Unknown
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:	Unknown
Danish MAL Code:	Unknown
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	Unknown
Norway Product Registration Number:	Unknown
WGK Class:	Not available

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Reproductive toxicity, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>%</u>
META-XYLENE	108-38-3	1.55
ETHYL BENZENE	100-41-4	1.01

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
No TSCA 12(b) components exist in this product.	

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.

H412

Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

